WP1

WP2

WP5



WP6

LED
Wall Packs

Wide choice of energy-efficient wall-mount utility lights. Ideal for garages, workshops, studios and other work areas. Choice of ambient lighting to high-intensity punches of light, depending on light levels required.

MODEL NUMBER	POWER (WATTS)	LED QTY	LUMENS	DIMENSIONS	COLOR TEMPERATURE
WP1	13	5	751	L11” X W6.9” X H5.24” (L280 X W175 X H133)	4700K
WP2-V1	38	15	1890	L13.4” X W9.37” X H7.125” (L340 X W238 X H18)	4700K
WP2-V2	77	30	3780	L13.4” X W9.37” X H7.125” (L340 X W238 X H181)	4700K
WP5	20	1	1400		4000K
WP6	36	2	2700		4000K



WP2-V2

Three-year limited warranty

Manufactured under ISO 9001:2000 management system

Certifications: cUL, CE, RoHS

Complete protection against short circuits, over-currents and overloads.

Optical Specs

Color: 4000K, 4700K
CRI: > 75
General Specs
Operating temperature: -30°C ~ 50°C
Storage temperature: -30°C ~ 45°C
IP Rating: IP66, Class I
Lifespan: 70,000 hours (L70)

Electrical Specs

Input Voltage: 120-277 VAC / 347 VAC
Power Factor: > 0.95
Driver Current: 700mA

Material

LED Brand: CREE XTE R2
Housing: Die-cast aluminum