YOU DESERVE ARANI™ 15 YEARS GREAT SERVICE

Date:	Project:
Prepared for:	Type:
Comments:	


GFCI OUTLETS




GF1-20A-TR-BK-V2
(Front View)





GF1-20A-TR-WH-V2
(Front View)



GF1-15A-TR-BK-V2
(Rear View)







SPECIFICATIONS

Characteristics	• Super tiny LED indicator light • Self-test function • Tamper resistant & Weather resistant
Input voltage	125Vac
Rated Working Current	15A / 20A
Maximum power	1875W (15A) / 2500W (20A)
Environment	Suitable for Dry Locations.
Wire size	#12- #14 AWG
Conductor Material	Solid copper only
Color Options	White / Black
Weight	113g
Material	Polycarbonate Body with Copper Contacts
Warranty	2 Years
Certifications	cULus
Dielectric voltage	Withstands 2000V per UL498
Flammability	Rated V-2 per UL94
Operating Temperature	-35°C to 66°C
Trigger threshold	4 to 6 mA
Tripping time	<8ms

GUARANTEE 2 Years

CERTIFIED

ORDERING INFORMATION:

Stock item. Same Day Shipping for orders placed by 3pm EST

SERIES	RATED WORKING CURRENT	FINISH	ORDERING CODE
GFCI OUTLETS	15A	WHITE	GF1-15A-TR-WH-V2
		BLACK	GF1-15A-TR-BK-V2
	20A	WHITE	GF1-20A-TR-WH-V2
		BLACK	GF1-20A-TR-BK-V2

© Arani All rights reserved. Arani reserves the right to change the design, materials and finish.

ARANI.CA — 2555 LEGER STREET, LASALLE, QC H8N 2V9, CANADA
#4-801 30ST NE, CALGARY, AB T2A 5L7, CANADA