Specifications of LED Instant Flexilight:

Structure	Voltage	Max. Loading Length (Color)	Cutting Unit (Color)	Bulb Spec.	Number of Bulbs/Unit	Wattage
	110-120V	600′ (WW, CW, B, G)	40″ (WW, CW, B, G)	LED	36	0.8W/foot
		900′ (R, Y)	54″ (R, Y)	LED	54	0.53W/foot
	24V	100′ (WW, CW, B, G)	6″ (WW, CW, B, G)	LED	6	0.88W/foot
		200′ (R, Y)	4″ (R, Y)	LED	12	0.44W/foot
	12V	50′ (WW, CW, B, G)	3″ (WW, CW, B, G)	LED	6	0.88W/foot
		100′ (R, Y)	6″ (R, Y)	LED	12	0.44W/foot

Packages Available

Item Number	Length	Package
ER-LED-120-150	150′	/Roll
ER-LED-24-150	150′	/Roll
ER-LED-12-150	150′	/Roll

No Driver Required/ Rectifier Included

ER-LED - 120 - 150 - COLOR

Item No. | Voltage | Length | Specify color

(Available in 150’ Rolls only, no custom cut)

NOTE: Each Roll Includes; 3pcs ERIFL-XXX Power Cords, 3pcs F4 End Caps

NOTE:

LED Magnetic Transformer

Cat#	LED Voltage	LED Lenght	Max. Wattage
M100L-12-DC	12V	50′	75w
M100L-24-DC	24V	100′	100w

LED Instant Flexilight Accessories:

ERIFL-F106 -120V LED Flexilight 6ft. Power Cord w/ Power Connector

ERIFL-F107 -24V LED Flexilight 6ft. Power Cord w/ Power Connector

ERIFL-F107 -12V LED Flexilight 6ft. Power Cord w/ Power Connector

ERIFL-F106



F4	LED Flexilight End Caps	F10	LED Flexilight Y-Cable Connector
F5	LED Flexilight Tie Strap	F14	Housing Clam for Splice Connector
F6	LED Flexilight Mounting Clip	F103	LED Flexilight PVC Connector
F7	LED Flexilight Suction Cup	F22	LED Flexilight PVC T-Connector
F8	LED Flexilight 6 ft. Channel	F23	LED Flexilight PVC X-Connector

F4

F5

F6

F7

F8

F10

F14

F22

F23

F103

Due to the changes of constant improvement in lighting technology, all details are subject to change without notice.
Consult factory for up to date information.