


Specifications of Super-Brite Flexilight:

Structure	Voltage	Max. Loading Length (Color)	Cutting Unit (Color)	Bulb Spec.	Number of Bulbs/Unit	Wattage
	110-120V	100'	20"	6.5V 0.07A 0.46W	12	8.0W/foot

Packages Available

Item Number	Length	Package	ERIU	- 120	- 150	- COLOR
			Item No.	Voltage	Length	Specify color


ERIU-120-150

150'

/Roll

(Available in 150' Rolls only, no custom cut)

NOTE: EACH ROLL INCLUDES; 3pcs ERIU-1 Power Cords, 3pcs IU3 Splice Connectors, 3pcs IU4 End Caps



Super-Brite Flexilight Accessories:

ERIU-1	120V Super-Brite Flexilight 6ft. Power Cord w/ Power Connector
IU3	Super-Brite Flexilight Splice Connector
IU4	Super-Brite Flexilight End Caps
F5	Super-Brite Flexilight Tie Strap
IU6	Super-Brite Flexilight Mounting Clips
F7	Super-Brite Flexilight Suction Cup
IU8	Super-Brite Flexilight 6ft. Channel
IU9	Super-Brite Flexilight Easy Splice Connector
IU10	Super-Brite Flexilight Y-cord
IU14	Housing Clamp for Splice Connector
IU103	Super-Brite Flexilight PVC Connector
IU22	Super-Brite Flexilight PVC T-Connector
IU23	Super-Brite Flexilight PVC X-Connector

ERIU1

F5



F7



IU4




IU6



IU8



IU9



IU10



IU14



IU22



IU103



IU23



FLEXIBLE ROPELIGHT

Standard Controller

MODEL	VOLTAGE AVAILABLE	MAX. LENGTH	FUNCTIONS
ERWL-2C-110	120V	150 FT.	Static/Flashing Gradual Color-Change

