

## K-Type Grips

Kellems® Rotating Eye, K-Type Pulling Grips are made of high strength galvanized steel strand. All Grips feature double weave mesh for greater strength and added mesh contact on the table, to handle longer or heavier pulling jobs. The forged eye mates easily with a swivel or shackle.

### IMPORTANT

Read all breaking strength, safety and technical data relating to this product. Pages V-17 to V-26.



## K-Type Grips

| Cable Diameter Range<br>Inches (cm) | Approx. Breaking<br>Strength Lbs. (N) | E<br>Inches (cm) | M<br>Inches (cm) | Rotating Eye Dia.<br>Inches (cm) | Catalog Number   |
|-------------------------------------|---------------------------------------|------------------|------------------|----------------------------------|------------------|
| <b>Short</b>                        |                                       |                  |                  |                                  |                  |
| .50"-.62" (1.27-1.57)               | 5,600 (24,909)                        | 5" (12.70)       | 11" (27.94)      | 7/8" (2.22)                      | <b>03301001</b>  |
| .63"-.74" (1.60-1.88)               | 6,800 (30,246)                        | 5" (12.70)       | 11" (27.94)      | 7/8" (2.22)                      | <b>03301002</b>  |
| .75"-.99" (1.90-2.51)               | 6,800 (30,246)                        | 6" (15.24)       | 20" (50.80)      | 1" (2.54)                        | <b>03301013</b>  |
| 1.00"-1.24" (2.54-3.15)             | 12,800 (56,934)                       | 7" (17.78)       | 20" (50.80)      | 1 1/8" (3.49)                    | <b>03301014</b>  |
| 1.25"-1.49" (3.17-3.78)             | 12,800 (56,934)                       | 7" (17.78)       | 21" (53.34)      | 1 1/8" (3.49)                    | <b>03301016</b>  |
| 1.50"-1.99" (3.81-5.05)             | 16,400 (72,941)                       | 7" (17.78)       | 25" (63.50)      | 1 1/8" (3.49)                    | <b>03301017</b>  |
| 2.00"-2.49" (5.08-6.32)             | 27,200 (120,986)                      | 8" (20.32)       | 26" (66.04)      | 1 5/8" (4.13)                    | <b>03301018</b>  |
| 2.50"-2.99" (6.35-7.59)             | 33,000 (146,784)                      | 10" (25.40)      | 28" (71.12)      | 1 7/8" (4.76)                    | <b>03301019</b>  |
| 3.00"-3.49" (7.62-8.86)             | 41,000 (182,368)                      | 10" (25.40)      | 30" (76.20)      | 1 7/8" (4.76)                    | <b>03301020</b>  |
| 3.50"-3.99" (8.89-10.13)            | 48,000 (213,504)                      | 10" (25.40)      | 32" (81.28)      | 1 7/8" (4.76)                    | <b>03301021</b>  |
| 4.00"-4.49" (10.16-11.40)           | 48,000 (213,504)                      | 10" (25.40)      | 33" (83.82)      | 1 7/8" (4.76)                    | <b>033011017</b> |
| <b>Standard</b>                     |                                       |                  |                  |                                  |                  |
| .50"-.62" (1.27-1.57)               | 5,600 (24,909)                        | 5" (12.70)       | 16" (40.64)      | 7/8" (2.22)                      | <b>03301011</b>  |
| .63"-.74" (1.60-1.88)               | 6,800 (30,246)                        | 5" (12.70)       | 16" (40.64)      | 7/8" (2.22)                      | <b>03301012</b>  |
| .75"-.99" (1.90-2.51)               | 9,600 (42,701)                        | 6" (15.24)       | 32" (81.28)      | 1" (2.54)                        | <b>03301024</b>  |
| 1.00"-1.49" (2.54-3.78)             | 16,400 (72,947)                       | 7" (17.78)       | 33" (83.82)      | 1 1/8" (3.49)                    | <b>03301025</b>  |
| 1.50"-1.99" (3.81-5.05)             | 16,400 (72,947)                       | 7" (17.78)       | 34" (86.36)      | 1 1/8" (3.49)                    | <b>03301026</b>  |
| 2.00"-2.49" (5.08-6.32)             | 27,200 (120,986)                      | 9" (22.86)       | 36" (91.44)      | 1 5/8" (4.13)                    | <b>03301027</b>  |
| 2.50"-2.99" (6.35-7.59)             | 33,000 (146,784)                      | 10" (25.40)      | 38" (96.52)      | 1 7/8" (4.76)                    | <b>03301028</b>  |
| 3.00"-3.49" (7.62-8.86)             | 41,000 (182,368)                      | 10" (25.40)      | 39" (99.06)      | 1 7/8" (4.76)                    | <b>03301029</b>  |
| 3.50"-3.99" (8.89-10.13)            | 48,000 (213,504)                      | 10" (25.40)      | 41" (104.14)     | 1 7/8" (4.76)                    | <b>03301030</b>  |
| 4.00"-4.49" (10.16-11.40)           | 48,000 (213,504)                      | 10" (25.40)      | 42" (106.68)     | 1 7/8" (4.76)                    | <b>03301031</b>  |
| 4.50"-4.99" (11.43-12.67)           | 48,000 (213,504)                      | 10" (25.40)      | 58" (147.32)     | 1 7/8" (4.76)                    | <b>03301039</b>  |
| 5.00"-5.99" (12.70-15.21)           | 40,000 (177,920)                      | 10" (25.40)      | 60" (152.40)     | 1 7/8" (4.76)                    | <b>03301047</b>  |
| 6.00"-6.99" (15.24-17.75)           | 48,000 (213,504)                      | 10" (25.40)      | 66" (167.64)     | 1 7/8" (4.76)                    | <b>03301045</b>  |

Note: E- Eye length. M-Mesh length at nominal diameter.  
 See page V-25 for multiple cables in a single pulling grip.