




Non-Conductive Grips

Kellems® Non-Conductive Pulling Grips, made of a high strength, non-conductive aramid fiber, are available for pulling single cable or cable bundles. Their braided double weave design adds strength and positive holding power.

IMPORTANT
 Read all breaking strength, safety and technical data relating to this product. Pages V-17 to V-26.




Non-Conductive Grips, Single Eye, Double Weave, Non-Metallic

| Cable Diameter Range Inches (cm) | Approx. Breaking Strength Lbs. (N) | E Inches (cm) | M Inches (cm) | A Inches (cm) | Color Code | Catalog Number |
|----------------------------------|------------------------------------|---------------|----------------|---------------|------------|-----------------|
| .50"- .62" (1.27-1.57) | 4,000 (17,792) | 5.5" (13.97) | 24" (60.96) | .44" (1.12) | Green | 03628001 |
| .63"- .74" (1.60-1.88) | 5,000 (22,240) | 5.5" (13.97) | 26" (66.04) | .44" (1.12) | Yellow | 03628002 |
| .75"- .99" (1.90-2.51) | 6,000 (26,688) | 6.0" (15.24) | 31" (78.74) | .63" (1.60) | Red | 03628003 |
| 1.00"-1.24" (2.54-3.15) | 6,000 (26,688) | 6.5" (16.51) | 36" (91.44) | .63" (1.60) | Blue | 03628004 |
| 1.25"-1.49" (3.17-3.78) | 6,000 (26,688) | 6.7" (17.02) | 41.5" (105.41) | .63" (1.60) | White | 03628005 |
| 1.50"-1.99" (3.815-05) | 6,000 (26,688) | 8.0" (20.32) | 44.0" (121.76) | .63" (1.60) | Pink | 03628006 |

Slack Pulling Grips

Slack Pulling Grips are offered in three styles made of galvanized steel. The closed type is used when the cable end is accessible. When not accessible, there are split lace and split rod closing styles. All grips feature a single offset eye for easy attachment to a pulling line.



Slack Grip-Closed Mesh, Offset Eye, Double Weave, Galvanized Steel

| Cable Diameter Range Inches (cm) | Approx. Breaking Strength Lbs. (N) | E Inches (cm) | M Inches (cm) | Catalog Number |
|----------------------------------|------------------------------------|---------------|---------------|-----------------|
| Standard | | | | |
| .75"- .99" (1.90-2.51) | 2,600 (11,565) | 7" (17.78) | 12" (30.48) | 03308003 |
| 1.00"-1.24" (2.54-3.15) | 4,000 (17,792) | 8" (20.32) | 15" (38.10) | 03308004 |
| 1.25"-1.49" (3.17-3.78) | 5,400 (24,019) | 8" (20.32) | 16" (40.64) | 03308005 |
| 1.50"-1.74" (3.81-4.42) | 6,600 (29,357) | 8" (20.32) | 20" (50.80) | 03308006 |
| 1.75"-1.99" (4.44-5.05) | 10,000 (44,480) | 10" (25.40) | 18" (45.72) | 03308007 |
| 2.00"-2.49" (5.08-6.32) | 11,000 (48,928) | 10" (25.40) | 19" (48.26) | 03308008 |
| 2.50"-2.99" (6.35-7.59) | 11,000 (48,928) | 10" (25.40) | 20" (50.80) | 03308009 |
| 3.00"-3.49" (7.62-8.86) | 14,500 (64,496) | 12" (30.48) | 21" (53.34) | 03308010 |
| 3.50"-3.99" (8.89-10.13) | 14,500 (64,496) | 12" (30.48) | 22" (55.88) | 03308011 |

Note: E- Eye length. M-Mesh length at nominal diameter.
 See page V-25 for multiple cables in a single pulling grip.