


**CONDUIT FITTINGS**

**Metallic Conduit Connectors**

Liquid Tight - Flexible - 90° Angle - Insulated



No.			
Appleton	Crouse-Hinds	O-Z/Gedney	T&B
STB-9038	LTB3890	4Q-938T	5351
STB-9050	LTB5090	4Q-950T	5352
STB-9075	LTB7590	4Q-975T	5353
STB-90100	LTB10090	4Q-9100T	5354
STB-90125	LTB12590	4Q-9125T	5355
STB-90150	LTB15090	4Q-9150T	5356
STB-90200	LTB20090	4Q-9200T	5357
STB-90250	LTB25090	4Q-9250T	5358
STB-90300	LTB30090	4Q-9300T	5359
.....	.....	.....	.....
STB-90400	LTB40090	4Q-9400T	5360

Trade Size	KO Size	Pkg. Qty.
In.	In.	
3/8	1/2	25
1/2	3/4	25
3/4	1	10
1	1 1/4	5
1 1/4	1 1/2	5
1 1/2	2	2
2	2 1/2	1
2 1/2	3	1
3	3 1/2	1
3 1/2	4	1
4		1

**CONDUIT FITTINGS**

Liquidtight Flexible Metallic Conduit Ring & Retainer Assemblies



No.	Crouse-Hinds	O-Z/Gedney	T&B	Trade Size	Pkg. Qty.
Appleton	SG1	4Q-050	5262	1/2	50
STG-50	SG2	4Q-075	5263	3/4	25
STG-75	SG3	4Q-100	5264	1	25
STG-100	SG4	4Q-G125	5265	1 1/4	5
STG-125	SG5	4Q-G150	5266	1 1/2	5
STG-150	SG6	4Q-G200	5267	2	5
STG-200	SG7	4Q-G250	5268	2 1/2	1
STG-250	SG8	4Q-G300	5269	3	1
STG-300	SG10	4Q-G400	5270	4	1
STG-400					

**KELLEMS®**

Conduit Support Grips For Sealite® w/Raco Fittings



Straight Male



Straight w/Chase Connector

UL Listed 898D.

No.	UPC	Dia. In.	Lgth. In.
<b>Straight w/Male Fittings</b>			
074093511	33187	3/8*	3
074093512	33188	1/2	3 1/2
074093513	33189	3/4	4
074093514	33190	1	5
074093515	33191	1 1/4	6
074093516	33192	1 1/2	6 3/4

No.	UPC	Dia. In.	Lgth. In.
074093518	33193	2	8
074093520	33194	2 1/2	9 3/4
074093522	33195	3	11
074093526	33196	4	14
074093401	33160	3/8*	3
074093402	33161	1/2	3 1/2
074093403	33162	1	5
074093404	33163	3/4	4
074093405	33164	1	5
074093406	33165	1 1/4	6
074093408	33166	1 1/2	6 3/4
074093412	.....	3	11
074093416	.....	4	14

**90° w/Male Fittings**

074093541	33197	3/8*	3
074093542	33198	1/2	3 1/2
074093543	33199	3/4	4
074093544	33200	1	5
074093545	33201	1 1/4	6
074093546	33202	1 1/2	6 3/4
074093548	33203	2	8
074093550	33204	2 1/2	9 3/4
074093552	33205	3	11
074093556	49792	4	14
074093421	33170	3/8*	3
074093422	33171	1/2	3 1/2
074093423	33172	3/4	4
074093424	33173	1	5
074093425	33174	1 1/4	6
074093426	.....	1 1/2	6 3/4
074093428	.....	2	8
074093430	.....	2 1/2	9 3/4
074093432	.....	3	11
074093436	.....	4	14

**45° w/Male Fittings**

074093561	33207	3/8*	3
074093562	33208	1/2	3 1/2
074093563	33209	3/4	4
074093564	33210	1	5
074093565	33211	1 1/4	6
074093566	33212	1 1/2	6 3/4
074093568	33213	2	8
074093441	.....	3/8*	3
074093442	33181	1/2	3 1/2
074093443	.....	3/4	4
074093444	33183	1	5
074093445	33184	1 1/4	6
074093446	.....	1 1/2	6 3/4
074093448	.....	2	8

No.	UPC	Dia. In.	Lgth. In.
<b>Straight w/Female Fittings</b>			
07406021	.....	3/8*	3
07406022	32451	1/2	3 1/2
07406023	32452	3/4	4
07406024	32453	1	5
07406025	32454	1 1/4	6
<b>Straight w/Chase Connectors</b>			
07406078	32485	3/8*	3
07406079	32486	1/2	3 1/2
07406080	32487	3/4	4
07406081	32488	1	5
07406082	32489	1 1/4	6
07406083	32490	1 1/2	6 3/4
07406084	32491	2	8
07406085	32492	2 1/2	9 3/4
07406086	32493	3	11
07406087	.....	4	14

\*Flexible conduit size is 3/8", fitting thread size is 1/2".

**KELLEMS®**

Sealite Conduit Grips



Straight Male

No.	UPC	Desc.	Trade Size In.	Mesh In.	Lgth. In.	Insulation
07402011		STB-38K	3/8	3		Insulated
07402012		STB-50K	1/2	3 1/2		Insulated
07402013		STB-75K	3/4	4		Insulated
07402014		STB-100K	1	5		Insulated
07402015		STB-125K	1 1/4	6		Insulated
07402016		STB-150K	1 1/2	6 3/4		Insulated
07402017		STB-200K	2	8		Insulated
07402018		STB-250K	2 1/2	9 3/4		Insulated
07402019		STB-300K	3	11		Insulated
07402020		STB-400K	4	14		Insulated
07402001		ST-38K	3/8	3		Noninsulated
07402002		ST-50K	1/2	3 1/2		Noninsulated
07402003		ST-75K	3/4	4		Noninsulated

Continued on next page

Continued from previous page

No.	UPC	Desc.	Trade Mesh		Insulation
			Size	Lgth.	
07402004		ST-100K	1	5	Noninsulated
07402005		ST-125K	1 1/4	6	Noninsulated
07402006		ST-150K	1 1/2	6 3/4	Noninsulated
07402007		ST-200K	2	8	Noninsulated
07402008		ST-250K	2 1/2	9 1/4	Noninsulated
07402009		ST-300K	3	11	Noninsulated
07402010		ST-400K	4	14	Noninsulated
07406011		K-5331	3/8	3	Insulated
07406012		K-5332	1/2	3 1/2	Insulated
07406013		K-5333	3/4	4	Insulated
07406014		K-5334	1	5	Insulated
07406015		K-5335	1 1/4	6	Insulated
07406016		K-5336	1 1/2	6 3/4	Insulated
07406017		K-5337	2	8	Insulated
07406018		K-5338	2 1/2	9 1/4	Insulated
07406019		K-5339	3	11	Insulated
07406020		K-5340	4	14	Insulated
07406001		K-5231	1/8	3	Noninsulated
07406002		K-5232	1/2	3 1/2	Noninsulated
07406003		K-5233	3/4	4	Noninsulated
07406004		K-5234	1	5	Noninsulated
07406005		K-5235	1 1/4	6	Noninsulated
07406006		K-5236	1 1/2	6 3/4	Noninsulated
07406007		K-5237	2	8	Noninsulated
07406008		K-5238	2 1/2	9 1/4	Noninsulated
07406009		K-5239	3	11	Noninsulated
07406010		K-5240	4	14	Noninsulated



90° Male

No.	UPC	Desc.	Trade Mesh		Insulation
			Size	Lgth.	
07402061		STB-38K90	3/8	3	Insulated
07402062		STB-50K90	1/2	3 1/2	Insulated
07402063		STB-75K90	3/4	4	Insulated
07402064		STB-100K90	1	5	Insulated
07402065		STB-125K90	1 1/4	6	Insulated
07402066		STB-150K90	1 1/2	6 3/4	Insulated
07402067		STB-200K90	2	8	Insulated
07402068		STB-250K90	2 1/2	9 1/4	Insulated
07402069		STB-300K90	3	11	Insulated
07402070		STB-400K90	4	14	Insulated
07402041		ST-38K90	3/8	3	Noninsulated
07402042		ST-50K90	1/2	3 1/2	Noninsulated
07402043		ST-75K90	3/4	4	Noninsulated
07402044		ST-100K90	1	5	Noninsulated
07402045		ST-125K90	1 1/4	6	Noninsulated
07402046		ST-150K90	1 1/2	6 3/4	Noninsulated
07402047		ST-200K90	2	8	Noninsulated
07402048		ST-250K90	2 1/2	9 1/4	Noninsulated
07402049		ST-300K90	3	11	Noninsulated
07402050		ST-400K90	4	14	Noninsulated
07406061		K-5351	3/8	3	Insulated
07406062		K-5352	1/2	3 1/2	Insulated
07406063		K-5353	3/4	4	Insulated
07406064		K-5354	1	5	Insulated
07406065		K-5355	1 1/4	6	Insulated
07406066		K-5356	1 1/2	6 3/4	Insulated
07406067		K-5357	2	8	Insulated
07406068		K-5358	2 1/2	9 1/4	Insulated
07406069		K-5359	3	11	Insulated
07406070		K-5360	4	14	Insulated
07406041		K-5251	3/8	3	Noninsulated
07406042		K-5252	1/2	3 1/2	Noninsulated
07406043		K-5253	3/4	4	Noninsulated
07406044		K-5254	1	5	Noninsulated
07406045		K-5255	1 1/4	6	Noninsulated
07406046		K-5256	1 1/2	6 3/4	Noninsulated
07406047		K-5257	2	8	Noninsulated

No.	UPC	Desc.	Trade Mesh		Insulation
			Size	Lgth.	
07406048		K-5258	2 1/2	9 1/4	Noninsulated
07406049		K-5259	3	11	Noninsulated
07406050		K-5260	4	14	Noninsulated



45° Male

No.	UPC	Desc.	Trade Mesh		Insulation
			Size	Lgth.	
07402088		STB-38K45	3/8	3	Insulated
07402089		STB-50K45	1/2	3 1/2	Insulated
07402090		STB-75K45	3/4	4	Insulated
07402093		STB-100K45	1	5	Insulated
07402094		STB-125K45	1 1/4	6	Insulated
07402095		STB-150K45	1 1/2	6 3/4	Insulated
07402096		STB-200K45	2	8	Insulated
07402097		STB-250K45	2 1/2	9 1/4	Insulated
07402098		STB-300K45	3	11	Insulated
07402099		STB-400K45	4	14	Insulated
07402031		ST-38K45	3/8	3	Noninsulated
07402032		ST-50K45	1/2	3 1/2	Noninsulated
07402033		ST-75K45	3/4	4	Noninsulated
07402034		ST-100K45	1	5	Noninsulated
07402035		ST-125K45	1 1/4	6	Noninsulated
07402036		ST-150K45	1 1/2	6 3/4	Noninsulated
07402037		ST-200K45	2	8	Noninsulated
07402038		ST-250K45	2 1/2	9 1/4	Noninsulated
07402039		ST-300K45	3	11	Noninsulated
07402040		ST-400K45	4	14	Noninsulated



Female

No.	UPC	Desc.	Trade Mesh	
			Size	Lgth.
07402021	...	ST-38FK	3/8	3
07402022	...	ST-50FK	1/2	3 1/2
07402023	...	ST-75FK	3/4	4
07402024	...	ST-100FK	1	5

**KELLEMS®**  
Cord Grips  
Deluxe



Aluminum fittings with stainless steel mesh. Liquidtight. For insulated cables. Suitable for use in hazardous locations per Class I Div. 2, Class II Div. 1 and 2, Class III Div. 1 and 2 of National Electric Code Sections 501-4(b), 502-4(a), 502-4(b), 503-3(a) and 503 3(b).

UL Listed 899D.

No.	UPC	Desc.	Grip Dia. Range	
			In.	In.
07401001	32181	CG-305	250-	312
07401002	32182	CG-306	312-	375
07401003	32183	CG-307	375-	437

No.	UPC	Desc.	Grip Dia. Range
<b>Male Thread Size NPT—1/2"</b>			
07401004	32184	CG-404	.187-250
07401006	32186	CG-406	.250-375
07401008	32189	CG-408	.375-500
07401010	32191	CG-410	.56-62
074011247*	33030	CG-412	.625-750
074011248	33903	CG-414	.750-875

No.	UPC	Desc.	Grip Dia. Range
<b>Male Thread Size NPT—3/4"</b>			
07401011	32192	CG-604	.187-250
07401013	32194	CG-606	.310-370
07401015	32196	CG-608	.440-500
07401017	32198	CG-610	.560-625
07401018	32199	CG-612	.620-750
074011249*	33904	CG-614	.750-875

No.	UPC	Desc.	Grip Dia. Range
<b>Male Thread Size NPT—1"</b>			
074011195	33033	CG-808	.375-500
07401019	32200	CG-810	.500-625
07401021	32202	CG-812	.625-750
07401023	32204	CG-814	.750-875
07401025	32206	CG-816	.875-1.000
074011250*	33905	CG-818	1.000-1.125
074011028*	32282	CG-820	1.125-1.250
074011029*	32283	CG-822	1.250-1.375

No.	UPC	Desc.	Grip Dia. Range
<b>Male Thread Size NPT—1 1/4"</b>			
074011251	33906	CG-1014	.750-875
07401026	32207	CG-1016	.875-1.000
07401027	32208	CG-1018	1.000-1.125
07401028	32209	CG-1020	1.125-1.250
074011178*	33898	CG-1022	1.250-1.375

No.	UPC	Desc.	Grip Dia. Range
<b>Male Thread Size NPT—1 1/2"</b>			
074011252	33039	CG-1214	.750-875
07401029	32210	CG-1216	.875-1.000
07401030	32211	CG-1218	1.000-1.125
07401031	32212	CG-1220	1.125-1.250
07401032	32213	CG-1222	1.250-1.375
074011253	49782	CG-1223	1.312-1.437
074011254*	48784	CG-1225	1.437-1.562
074011255*	33083	CG-1227	1.562-1.687
074011256*	.....	CG-1229	1.687-1.812
074011257*	49786	CG-1230	1.750-1.875

No.	UPC	Desc.	Grip Dia. Range
<b>Male Thread Size NPT—2"</b>			
074011258	33086	CG-1622	1.250-1.375
074011259	.....	CG-1623	1.312-1.437
07401033	32214	CG-1625	1.437-1.562
07401034	32214	CG-1627	1.562-1.687
07401035	32216	CG-1629	1.687-1.812
074011260	33087	CG-1630	1.750-1.875
074011261	33088	CG-1631	1.812-1.937
074011262*	.....	.....	1.937-2.062
074011263*	33090	.....	2.062-2.187
074011264*	.....	.....	2.187-2.312
074011265*	.....	.....	2.312-2.437

No.	UPC	Desc.	Grip Dia. Range
<b>Male Thread Size NPT—2 1/2"</b>			
074011030	.....	.....	1.688-1.812
074011031	32285	.....	1.812-1.937
074011032	32286	.....	1.937-2.062
074011033	32287	.....	2.062-2.187
074011034	32288	.....	2.187-2.312
074011266*	.....	.....	2.312-2.437

No.	UPC	Desc.	Grip Dia. Range
<b>Male Thread Size NPT—3"</b>			
074011036	.....	.....	1.937-2.062
074011037	.....	.....	2.062-2.187
074011038	.....	.....	2.187-2.312
074011039	32293	.....	2.312-2.437
074011186	49780	.....	2.437-2.625
074011187	.....	.....	2.625-2.812
074011188	33063	.....	2.812-3.000
074011189*	33064	.....	3.000-3.250

\*Cable jacket may have to be stripped to pass through connector body.