



Kellems® Wire Management Products

Strain Relief for Liquidtight Conduit

Steel Fitting, Stainless Steel Mesh for Liquidtight Metal Conduit and PolyTuff I Non-Metallic Conduit

WARNING!

It is important that you read all breaking strength, safety and technical data relating to this product on pages T-77, T-79 and T-80.



Straight with Male Fitting



90° Angle with Male Fitting

Benefits

- Helps prevent conduit pull-out and damage at the fitting.
- Reduces equipment downtime.

Straight With Male Fitting

Conduit Trade Size (Inches)	Fitting Size N.P.T. (Inches)	Mesh Length Inches (cm)	Catalog Numbers (Insulated)	Catalog Numbers (Non-insulated)
3/8	1/2	3" (7.62)	074093511	074093401
1/2	1/2	3.5" (8.89)	074093512	074093402
3/4	3/4	4" (10.16)	074093513	074093403
1	1	5" (12.70)	074093514	074093404
1 1/4	1 1/4	6" (15.24)	074093515	074093405
1 1/2	1 1/2	6.75" (17.14)	074093516	074093406
2	2	8" (20.32)	074093518	074093408
2 1/2	2 1/2	9.75" (24.76)	074093520	074093410
3	3	11" (27.94)	074093522	074093412
4	4	14" (35.56)	074093526	•

90° Angle With Male Fitting

Conduit Trade Size (Inches)	Fitting Size N.P.T. (Inches)	Mesh Length Inches (cm)	Catalog Numbers (Insulated)	Catalog Numbers (Non-insulated)
3/8	1/2	3" (7.62)	074093541	074093421
1/2	1/2	3.5" (8.89)	074093542	074093422
3/4	3/4	4" (10.16)	074093543	074093423
1	1	5" (12.70)	074093544	074093424
1 1/4	1 1/4	6" (15.24)	074093545	074093425
1 1/2	1 1/2	6.75" (17.14)	074093546	074093426
2	2	8" (20.32)	074093548	074093428
2 1/2	2 1/2	9.75" (24.76)	074093550	•
3	3	11" (27.94)	074093552	•

Note: For use with Liquidtight Metal conduit and PolyTuff I Non-Metallic conduit.

Strain Relief for Liquidtight Conduit

Steel Fitting, Stainless Steel Mesh for Liquidtight Metal Conduit and PolyTuff I Non-Metallic Conduit

Straight With Chase Fitting

Conduit Trade Size (Inches)	Fitting Size N.P.T. (Inches)	Mesh Length Inches (cm)	Catalog Numbers
1/2	1/2	3.5" (8.89)	07406079
3/4	3/4	4" (10.16)	07406080
1	1	5" (12.70)	07406081
1 1/4	1 1/4	6" (15.24)	07406082
1 1/2	1 1/2	6.75" (17.14)	07406083

WARNING!

It is important that you read all breaking strength, safety and technical data relating to this product on pages T-77, T-79 and T-80.



Straight with Chase Connector

45° Angle With Male Fitting

Conduit Trade Size (Inches)	Fitting Size N.P.T. (Inches)	Mesh Length Inches (cm)	Catalog Numbers (Insulated)	Catalog Numbers (Non-insulated)
3/8	1/2	3" (7.62)	074093561	074093441
1/2	1/2	3.5" (8.89)	074093562	074093442
3/4	3/4	4" (10.16)	074093563	074093443
1	1	5" (12.70)	074093564	074093444
1 1/4	1 1/4	6" (15.24)	074093565	074093445
1 1/2	1 1/2	6.75" (17.14)	074093566	074093446
2	2	8" (20.32)	074093568	074093448

Note: For use with Liquidtight Metal conduit and PolyTuff I Non-Metallic conduit.



45° Angle with Male Fitting