

IP55*
 SUITABILITY

Insulgrip®

Weatherproof, Seal-Tite®, Triple Seal Boots

Description	Catalog Number
Seal-Tite® triple seal cover for plug when used on a cord set or when used with flush receptacles or connector bodies when used with flanged inlets. Black elastomer.	HBL6035
Same as above except yellow.	HBL60CM35
Seal-Tite triple seal cover for connector bodies, when used on interconnecting cord sets. Black elastomer.	HBL6036
Same as above except yellow.	HBL60CM36



HBL6035



HBL6036

Angle Adapter

Description	Catalog Number
Nylon, angle adapter for Insulgrip plugs and connectors, cord grip range .350"-1.15" (8.9-29.2).	HBL45WAA



HBL45WAA

PLUGOUT® Lockout Device

Description	Catalog Number
Lockout device for attachable 20 and 30A plugs, straight body or angle types, with or without weatherproof covers.	HLD
Lockout device for 20 and 30A, 4 and 5 wire angle plugs and watertight Safety-Shroud® Twist-Lock® plugs.	HLD2

Note: See page Z-3 for additional information on PLUGOUT Lockout devices.
 *When installed and used properly, with plug and connector body combinations.



HLD

Insulgrip® Plug and Connector Body Latching Kit

When you want to make doubly sure that plugs and connector bodies stay connected, the Hubbell latching kit provides both improved safety and security through a double locking feature that makes unintentional disconnection virtually impossible – even under high vibration situations. The plug and connector body lock once when first connected, then again when you push the special position locking slide into place.

Insulgrip® Latching Kit

Description	Catalog Number
For all 20 and 30A, 4 and 5 wire Twist-Lock Insulgrip plugs and connectors.	SK3



SK3

Twist-Lock® 3-Phase Circuit Tester

Description	Rating	20 Amp NEMA L21-20	30 Amp NEMA L21-30
		HBL3PT2511	HBL3PT2811
3-Phase Circuit Tester	3Ø 120/208V AC Min. Voltage: 90V AC		

Note: Testers in other NEMA configurations can be developed upon request.



HBL3PT2511



HBL3PT2811

Dimensions in Inches (mm)