

## 2-Gang Rectangular Floor Boxes, Covers and Plates



### AFB2G Series – Rectangular Box

- Designed for wood and tile applications
- 5 in. deep box allows for 2 in. conduits - ideal for furniture feed applications
- 2 ½ in. provides a solution for floors using short pedestals

| Catalog Number    | Box Type | Knockouts       | Box Depth | Max Tile Thickness | Plate Depth | Device Volume | Cover Series |
|-------------------|----------|-----------------|-----------|--------------------|-------------|---------------|--------------|
| <b>AFB2G50</b>    | Standard | ½ in. to 2 in.  | 5 in.     | 2 in.              | 2 ½ in.     | 60 cu. in.    | <b>2GAFB</b> |
| <b>AFB2G50CHI</b> | Chicago  | None            |           |                    |             |               |              |
| <b>AFB2G25</b>    | Standard | ½ in. and ¾ in. | 2 ½ in.   | 2 in.              | 2 ½ in.     | 30 cu. in.    | <b>2GAFB</b> |
| <b>AFB2G25CHI</b> | Chicago  | None            |           |                    |             |               |              |



### Rectangular Covers (for use with raised access tiles and wood floors)

- Die cast construction available in five finishes
- UL 514A listed
- Furniture feed includes one 2 in. conduit hub and one 1 in. conduit hub with reducer to ¾ in.
- Maximum static load of 800 lbs with 2x safety factor\*

| Finish                     | Surface Style Cover | Surface Style Cover with Insert | Furniture Feed Cover |
|----------------------------|---------------------|---------------------------------|----------------------|
| Aluminum Powder Coated     | <b>2GAFBCVRLU</b>   | <b>2GAFBCVRLUC</b>              | <b>2GAFBFFCVRLU</b>  |
| Black Powder Coated        | <b>2GAFBCVRBK</b>   | <b>2GAFBCVRBKC</b>              | <b>2GAFBFFCVRBK</b>  |
| Brass Powder Coated        | <b>2GAFBCVRBRS</b>  | <b>2GAFBCVRBRSC</b>             | <b>2GAFBFFCVBRRS</b> |
| Bronze Powder Coated       | <b>2GAFBCVRBRZ</b>  | <b>2GAFBCVRBRZC</b>             | <b>2GAFBFFCVBRZ</b>  |
| Satin Nickel Powder Coated | <b>2GAFBCVRNK</b>   | <b>2GAFBCVRNKC</b>              | <b>2GAFBFFCVRNK</b>  |

\* Load applied through a 3 in. (76mm) mandrel in center of the cover.



### Plates - for use in 2, 4 and 6-Gang Floor Boxes

- UL 514A listed

| Plate Style | (1) Decorator Opening | (1) Duplex Opening | (2) Extron® MAAP Openings | (2) Extron® Openings |
|-------------|-----------------------|--------------------|---------------------------|----------------------|
| Cat. No.    | <b>FBMPREC</b>        | <b>FBMPDUP</b>     | <b>FBMPMAAP</b>           | <b>FBMPAAP</b>       |



| Plate Style | (2) 1U Hubbell iStation Openings | (1) 1.5U Hubbell iStation Opening | (1) Simplex Opening 1.40 in. Diameter | (1) Twist-Lock® Opening 1.60 in. Diameter |
|-------------|----------------------------------|-----------------------------------|---------------------------------------|-------------------------------------------|
| Cat. No.    | <b>FBMP2IM</b>                   | <b>FBMP15IM</b>                   | <b>FBMP139</b>                        | <b>FBMP156</b>                            |



| Plate Style | 1-Gang Blank   | Cable Feed Through with Bushing | (1) Opening for TracJack® or Series II® | (1) Opening w/ Hubbell ISF6 Frame for Keystone Jacks |
|-------------|----------------|---------------------------------|-----------------------------------------|------------------------------------------------------|
| Cat. No.    | <b>FBMPBNK</b> | <b>FBMPFT</b>                   | <b>FBMPTRAC</b>                         | <b>FBMP6KS</b>                                       |



Extron® is a registered trademark of Extron Electronics.  
 Crestron® is a registered trademark of Crestron Electronics, Inc.  
 FSR® is a registered trademark of FSR Inc.  
 TracJack®, Series II® and Ortronics® are registered trademarks of Ortronics/Legrand.

## Hubbell SystemOne 4-Gang Rectangular Raised Access Floor Box

The Hubbell SystemOne 4-Gang Recessed Raised Access Floor Box delivers AV plus power. Similar to the 2-Gang recessed raised access floor box, the 4-Gang 2 ½ inch box depth provides a solution for floors using short pedestals. The 5 inch depth is ideal for applications with a lot of requirements. Rectangular covers in a variety of finishes will match any existing or new style.

### Cover

- 180° cover opening
- Two large cable egress doors
- Listed to UL 514A and UL scrub water compliant
- Die cast aluminum cover construction
- All covers are ADA compliant



### Box

- 16 gauge galvanized sheet metal construction
- 6 in. solid conductor ground pigtail in each gang
- 2 ½ in. or 5 in. box depths
- 5.0 in. deep box allows for 2 in. conduits
- Mounts in tiles ¾ in. to 2 in. thick
- Fits in 11 in. x 11 in. opening
- Patent Pending, labor saving, easy mount device plates

## 4-Gang Floor Rectangular Boxes, Covers and Plates



### AFB4G Series – Rectangular Box

- Designed for wood and tile applications
- 2 ½ in. provides a solution for floors using short pedestals
- 5 in. deep box allows for 2 in. conduits - ideal for furniture feed applications

| Catalog Number    | Box Type | Knockouts       | Box Depth | Max Tile Thickness | Plate Depth | Device Volume | Cover Series |
|-------------------|----------|-----------------|-----------|--------------------|-------------|---------------|--------------|
| <b>AFB4G50</b>    | Standard | ½ in. to 2 in.  | 5 in.     | 2 in.              | 2 ½ in.     | 57.5 cu. in.  | <b>4GAFB</b> |
| <b>AFB4G50CHI</b> | Chicago  | None            |           |                    |             |               |              |
| <b>AFB4G25</b>    | Standard | ½ in. and ¾ in. | 2 ½ in.   | 2 in.              | 2 ½ in.     | 26.5 cu. in.  | <b>4GAFB</b> |
| <b>AFB4G25CHI</b> | Chicago  | None            |           |                    |             |               |              |



### Rectangular Covers (for use with raised access tiles and wood floors)

- Die cast construction available in five finishes
- UL 514A listed
- Maximum static load of 1500 lbs with 2x safety factor\*

| Finish                     | Surface Style Cover | Surface Style Cover with Insert |
|----------------------------|---------------------|---------------------------------|
| Aluminum Powder Coated     | <b>4GAFBCVRLU</b>   | <b>4GAFBCVRLUC</b>              |
| Black Powder Coated        | <b>4GAFBCVRBK</b>   | <b>4GAFBCVRBKC</b>              |
| Brass Powder Coated        | <b>4GAFBCVRBRS</b>  | <b>4GAFBCVRBRSC</b>             |
| Bronze Powder Coated       | <b>4GAFBCVRBRZ</b>  | <b>4GAFBCVRBRZC</b>             |
| Satin Nickel Powder Coated | <b>4GAFBCVRNK</b>   | <b>4GAFBCVRNKC</b>              |

\* Load applied through a 3 in. (76mm) mandrel in center of the cover.



### Plates for use in 2, 4 and 6-Gang Floor Boxes

- UL 514A listed

| Plate Style | (1) Decorator Opening            | (1) Duplex Opening                | (2) Extron® MAAP Openings               | (2) Extron® Openings                                 |
|-------------|----------------------------------|-----------------------------------|-----------------------------------------|------------------------------------------------------|
| Cat. No.    | <b>FBMPREC</b>                   | <b>FBMPDUP</b>                    | <b>FBMPMAAP</b>                         | <b>FBMPAAP</b>                                       |
|             |                                  |                                   |                                         |                                                      |
| Plate Style | (2) 1U Hubbell iStation Openings | (1) 1.5U Hubbell iStation Opening | (1) Simplex Opening 1.40 in. Diameter   | (1) Twist-Lock® Opening 1.60 in. Diameter            |
| Cat. No.    | <b>FBMP2IM</b>                   | <b>FBMP15IM</b>                   | <b>FBMP139</b>                          | <b>FBMP156</b>                                       |
|             |                                  |                                   |                                         |                                                      |
| Plate Style | 1-Gang Blank                     | Cable Feed Through with Bushing   | (1) Opening for TracJack® or Series II® | (1) Opening w/ Hubbell ISF6 Frame for Keystone Jacks |
| Cat. No.    | <b>FBMPBNK</b>                   | <b>FBMPFT</b>                     | <b>FBMPTRAC</b>                         | <b>FBMP6KS</b>                                       |
|             |                                  |                                   |                                         |                                                      |

Extron® is a registered trademark of Extron Electronics.  
 Crestron® is a registered trademark of Crestron Electronics, Inc.  
 FSR® is a registered trademark of FSR Inc.  
 TracJack®, Series II® and Ortronics® are registered trademarks of Ortronics/Legrand.

## Hubbell SystemOne 4-Gang Round Raised Access Floor Box

With an 8 in. diameter, the Hubbell SystemOne 4-Gang Round Recessed Floor Box is ideal for use in raised access floors with pre-cut tile or wood floor coverings. With a variety of finish selections, the round covers blend in with the flooring and overall design of the building. Deep, 2 ¾ in. wiring compartments are ready to accommodate today's most advanced, high-performance power, data, and AV needs to supply reliable connectivity.



*Incorporates four equally sized device mounting plates that accommodate NEMA devices and an array of 3rd party modules.*

### Cover

- 180° cover opening
- Two large cable egress doors
- UL scrub water compliant
- Die cast aluminum cover construction
- All covers are ADA compliant 



### Box

- Fits in 8 in. diameter air diffuser holes
- 16 gauge galvanized sheet metal construction
- Individual grounding screws for each gang
- 2 in. knock-out on the bottom allows for large amounts of data and/or AV devices
- Mounts in tiles ¾ in. to 2 in. thick

## 4-Gang Round Floor Boxes, Covers and Plates



### RAFB4 Series – Round Floor Box

Includes:

- Base box shipped with temporary install cover

| Catalog Number   | Cover Series   | Depth     | Tile Thickness  | Plate Depth | Knockouts       | Diameter |
|------------------|----------------|-----------|-----------------|-------------|-----------------|----------|
| <b>RAFB4BASE</b> | <b>CFBS1R8</b> | 6 1/4 in. | 3/4 in. - 2 in. | 2 3/4 in.   | 3/4 in. - 2 in. | 8 in.    |

### RAFB4 Series – Round Floor Box with Cover


Includes:

- **RAFB4BASE** and 8 in. cover

| Cover Finish        | Catalog Number  |
|---------------------|-----------------|
| Brushed Aluminum    | <b>RAFB4ALU</b> |
| Black Powder Coated | <b>RAFB4BLK</b> |
| Brass Plated        | <b>RAFB4BRS</b> |
| Bronze Plated       | <b>RAFB4BRZ</b> |
| Satin Nickel Plated | <b>RAFB4NKL</b> |

### RAFB4 Series – Plates

- All **RAFB4SP** series plates are powder coated white

| Plate Style | (1) Decorator                                                                       | (1) Duplex                                                                          | Blank                                                                                |
|-------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------|
| Cat. No.    | <b>RAFB4SPDECO</b>                                                                  | <b>RAFB4SPDUPLEX</b>                                                                | <b>RAFB4SPBLANK</b>                                                                  |
|             |  |  |  |
| Plate Style | (1) Simplex Opening<br>1.40 in. Dia.                                                | (1) Twist-Lock® Opening<br>1.60 in. Diameter                                        | (1) Hubbell iStation<br>Opening for 3 Units                                          |
| Cat. No.    | <b>RAFB4SPTL14</b>                                                                  | <b>RAFB4SPTL16</b>                                                                  | <b>RAFB4SP3UIS</b>                                                                   |
|             |  |  |  |
| Plate Style | Opening to Accept Bezels<br>for Ortronics TracJack®                                 | (3) Extron®<br>MAAP Modules                                                         | (2) Extron®<br>AAP Modules                                                           |
| Cat. No.    | <b>RAFB4SPORT</b>                                                                   | <b>RAFB4SP3MAAP</b>                                                                 | <b>RAFB4SP2AAP</b>                                                                   |
|             |  |  |  |



Extron® is a registered trademark of Extron Electronics.  
 Crestron® is a registered trademark of Crestron Electronics, Inc.  
 FSR® is a registered trademark of FSR Inc.  
 TracJack®, Series II® and Ortronics® are registered trademarks of Ortronics/Legrand.