

Flush Round Single Service Metal Concrete Floor Boxes


ScrubShield™
Complies with UL514A



Dimensions Inches (mm)

Cast Iron

Stamped Steel

							
Collar Material Brass Aluminum	B2536 B253641 BA2536 -		B2503 -	B2506 B2506415 - -	B2537 BA2537	B2527 BA2527	B2529 BA2529
Min. Depth of Pour	3.75" (95.3)		3.75" (95.3)	4.75" (120.7)	3.00" (76.2)	4.00" (101.6)	3.00" (76.2)
Adjustability	Fully		Fully	Fully	Fully	Fully	Fully
Cubic Inch (cm³) Capacity	33.0 cu. in. (540.7 cm³)		36.0 cu. in. (590.0 cm³)	50.8 cu. in. (832.5 cm³)	33.0 cu. in. (540.7 cm³)	54.0 cu. in. (885.0 cm³)	37.3 cu. in. (611.2 cm³)
Dimensions – A	3.05" (77.5)		3.75" (95.3)	4.75" (120.7)	2.87" (72.9)	3.88" (98.6)	2.91" (73.9)
Dimensions – B	4.84" (122.9)		5.00" (127.0)	5.00" (127.0)	4.84" (122.9)	6.00" (152.4)	6.00" (152.4)
Dimensions – C	4.84" (122.9)		4.66" (118.4)	4.66" (118.4)	4.84" (122.9)	4.81" (122.2)	4.81" (122.2)
Dimensions – D	4.19" (106.4)		4.19" (106.4)	4.19" (106.4)	4.19" (106.4)	4.19" (106.4)	4.19" (106.4)
Threaded Access Holes	(4) ¾" (4) 1"		(4) ¾"	(4) 1¼" (4) 1½"	(4) ¾"	-	-
Knockouts – Sides	- -		-	- -	-	(1) 1" & (1) ¾"	(2) ½" & (1) ¾"
Knockouts – Ends	- -		-	- -	-	(1) 1¼" & (1) ¾"	(1) ½" & (1) ½"
Knockouts – Bottom	- -		-	- -	-	(3) ½" & (2) ¾"	(3) ½" & (2) ¾"
Concrete Cover Included	✓		✓	✓	✓	✓	✓
Closure Plugs Included	✓		✓	✓	✓	-	-

Notes: UL File Number E31999.
CSA File Number LR18416.
Suitable for single service applications only.

Single Service Covers

Brass
Aluminum
3.88 in. Dia.

S3925 SA3925	S3725 SA3725	S2525 SA2525	S2725 SA2725	S2925 SA2925	S3525 –	S3325 –
Duplex Flap	Duplex Screw	2 1/8" x 3/4" Combination	2 1/8" x 1" Combination	2 1/8" Single Receptacle	2 3/8" Single Receptacle	2 1/8" Single Receptacle (Terrazzo Floor)

Carpet Flanges

5.25 in. Diameter

S3182	SA3182	S3079
Brass	Aluminum	Clear Polycarbonate

6.25 in. Diameter

S3082	S3082AL
Brass	Alum. Finish

One Piece Brass Cover and Carpet Flange

6.25 in. Diameter


SF3925	SF2525	SF2725	SF2925
Duplex Flap	2 1/8" x 3/4" Combination	2 1/8" x 1" Combination	2 1/8" Single Receptacle

Flush Rectangular Non-Metallic Concrete Floor Boxes with Non-Metallic Covers

ScrubShield™
Complies with UL514A



Dimensions Inches (mm)

Style	1-Gang	2-Gang	3-Gang
	 PFBRG1*	 PFBRG2	 PFBRG3
Min. Depth of Pour	3.00" (76.2)	3.00" (76.2)	3.00" (76.2)
Adjustability	Fully	Fully	Fully
Cubic Inch (cm³) Capacity Per Gang	14.3 cu. in. (234.3 cm³) per 1" depth	14.3 cu. in. (234.3 cm³) per 1" depth	14.3 cu. in. (234.3 cm³) per 1" depth
Dimensions – A	6.00" (152.4)	6.00" (152.4)	6.00" (152.4)
Dimensions – B	3.60" (91.4)	6.82" (173.2)	10.04" (255.0)
Dimensions – C	5.42" (137.7)	5.42" (137.7)	5.42" (137.7)
Dimensions – D	6.90" (175.3)	6.90" (175.3)	6.90" (175.3)
Dimensions – E	5.44" (138.2)	8.66" (220.0)	11.87" (301.5)
Hubs	(4) 1"	(6) 1"	(8) 1"
Reducers	(4) 1" to 3/4"	(6) 1" to 3/4"	(8) 1" to 3/4"
Concrete Cover Included	✓	✓	✓
Closure Plugs Included	✓	✓	✓
Removable LV Barrier	–	✓	✓

Notes: UL File Number E92074.

CSA File Number LR18416.

* Suitable for single service applications only.

Flush Rectangular Non-Metallic Covers and Flanges

Required Components for Carpet Applications

Carpet Flanges

Number of Gangs	1-Gang	2-Gang	3-Gang
Dimensions	6.00" x 4.88"	6.00" x 8.13"	6.00" x 11.35"
Black	PFBRFBL1	PFBRFBL2	PFBRFBL3
Brown	PFBRFBR1	PFBRFBR2	PFBRFBR3
Gray	PFBRFGY1	PFBRFGY2	PFBRFGY3
Ivory	PFBRFI1	PFBRFI2	PFBRFI3



Cover with Duplex and Style Line® Inserts included

One Required per Gang
4.15" x 2.97"
PFBR826BLA
PFBR826BRA
PFBR826GYA
PFBR826IA



Duplex
Insert

Cover

Style Line®
Decorator Insert

Required Components for Tile Applications

Mounting Collar

One Required per Gang

PFBRMC



Cover Frame

One Required per Gang
Dim. 4.47" x 3.25"

PFBRFRA



Cover with Duplex and Style Line® Inserts included – Gray

One Required per Gang
Cover Dim. 4.15" x 2.97"

PFBR826GYA



Duplex
Insert

Cover

Style Line®
Decorator Insert

Flush Rectangular Non-Metallic Concrete Floor Boxes with Metal Covers

ScrubShield™
Complies with UL514A



Dimensions Inches (mm)

Style	1-Gang	2-Gang	3-Gang
	PFBRG1*	PFBRG2	PFBRG3
Min. Depth of Pour	3.00" (76.2)	3.00" (76.2)	3.00" (76.2)
Adjustability	Fully	Fully	Fully
Cubic Inch (cm³) Capacity Per Gang	14.3 cu. in. (234.3 cm³) per 1" depth	14.3 cu. in. (234.3 cm³) per 1" depth	14.3 cu. in. (234.3 cm³) per 1" depth
Dimensions – A	6.00" (152.4)	6.00" (152.4)	6.00" (152.4)
Dimensions – B	3.60" (91.4)	6.82" (173.2)	10.04" (255.0)
Dimensions – C	5.42" (137.7)	5.42" (137.7)	5.42" (137.7)
Dimensions – D	6.90" (175.3)	6.90" (175.3)	6.90" (175.3)
Dimensions – E	5.44" (138.2)	8.66" (220.0)	11.87" (301.5)
Hubs	(4) 1"	(6) 1"	(8) 1"
Reducers	(4) 1" to ¾"	(6) 1" to ¾"	(8) 1" to ¾"
Concrete Cover Included	✓	✓	✓
Closure Plugs Included	✓	✓	✓
Removable LV Barrier	–	✓	✓

Notes: UL File Number E92074.

CSA File Number LR18416.

* Suitable for single service applications only.

Flush Rectangular Metal Covers and Flanges

Required Components for Carpet and Tile Applications

Adapter Collar – One Required per Gang
Gray **PFBRAC**



Adapter Frame with Grounding Lug – One Required per Gang
Dim. 4.36" x 3.20"

Brass
Aluminum

S5017G
SA5017G



Covers – One Required per Gang

Brass
Aluminum
Dimensions
4.15" x 2.99"



Duplex
Flap



Duplex
Screw



Style Line®
Opening



2 1/8" x 3/4"
Combination



2 1/8" x 1"
Combination



2 1/8" Single
Receptacle



Blank

Carpet Flanges (Not Required for Tile Applications)

Tapered Flange

Number of Gangs
Dimensions
Brass
Aluminum

1-Gang
6.00" x 4.85"
SB3083
SA3083



2-Gang
6.00" x 8.13"
SB3084
SA3084




3-Gang
6.00" x 11.34"
SB3085
SA3085



Flush Rectangular Cast Iron Concrete Floor Boxes

ScrubShield™
Complies with UL514A



Dimensions Inches (mm)		Cast Iron				
Style  Collar Material Brass Aluminum	1-Gang Deep	2-Gang Deep	3-Gang Deep	1-Gang Shallow	2-Gang Shallow	3-Gang Shallow
						
	B2436* B243641* BA2436* –	B4233 B423341 BA4233 –	B4333 B433361 BA4333 –	B2414* –	B4214 –	B4314 –
Min. Depth of Pour	3.75" (95.3)	3.75" (95.3)	3.75" (95.3)	2.00" (50.8)	2.00" (50.8)	2.00" (50.8)
Adjustability	Fully	Fully	Fully	Semi	Semi	Semi
Cubic Inch (cm³) Capacity Per Gang	33.0 cu. in. (540.7 cm³)	36.5 cu. in. (598.1 cm³)	34.8 cu. in. (570.3 cm³)	16.0 cu. in. (262.2 cm³)	16.0 cu. in. (262.2 cm³)	16.0 cu. in. (262.2 cm³)
Dimensions – A	3.20" (81.3)	3.38" (85.9)	3.38" (85.9)	2.00" (50.8)	2.00" (50.8)	2.00" (50.8)
Dimensions – B	4.69" (119.1)	4.84" (122.9)	4.90" (122.5)	5.46" (138.7)	5.46" (138.7)	5.46" (138.7)
Dimensions – C	4.69" (119.1)	8.06" (204.7)	11.41" (289.8)	4.19" (106.4)	7.49" (190.2)	10.7" (271.8)
Dimensions – D	4.36" (110.7)	4.36" (110.7)	4.36" (110.7)	4.38" (111.3)	4.38" (111.3)	4.38" (111.3)
Dimensions – E	3.19" (81.0)	6.42" (163.1)	9.64" (244.9)	3.19" (81.0)	6.38" (162.1)	9.56" (242.8)
Threaded Access Holes	(4) ¾" (4) 1"	(6) ¾" (4) 1" & (2) ¾"	(8) ¾" (4) 1" & (2) ¾"	(2) ¾"	(4) ¾"	(6) ¾"
Concrete Cover Included	✓	✓	✓	✓	✓	✓
Closure Plugs Included	✓	✓	✓	✓	✓	✓
Removable LV Barrier	–	✓	✓	–	✓	✓

Notes: UL File Number E92074.

CSA File Number LR18416.

* Suitable for single service applications only.

Flush Rectangular Floor Box Covers

Brass	S3825	S3625	S3826	S2425	S2625	S2825	S3425	S3813
Aluminum	SA3825	SA3625	SA3826	SA2425	SA2625	–	–	SA3813
Dimensions 4.15" x 2.99"								
	Duplex Flap	Duplex Screw	Style Line® Opening	2 1/8" x 3/4" Combination	2 1/8" x 1" Combination	2 1/8" Single Receptacle	2 3/8" Single Receptacle	Blank



Carpet Flanges

Tapered Flange			
Number of Gangs	1-Gang	2-Gang	3-Gang
Dimensions	6.00" x 4.85"	6.00" x 8.13"	6.00" x 11.34"
Brass	SB3083	SB3084	SB3085
Aluminum	SA3083	SA3084	SA3085
Clear Polycarbonate	S3083	S3084	S3085

Flush Rectangular Stamped Steel Concrete Floor Boxes

ScrubShield™
Complies with UL514A



Dimensions Inches (mm)				Stamped Steel				
Style	1-Gang Deep	2-Gang Deep	3-Gang Deep	1-Gang Shallow	2-Gang Shallow	3-Gang Shallow	1-Gang Deep	1-Gang Shallow
 Collar Material Brass Aluminum								
	B2431* BA2431*	B2432 BA2432	B2433 BA2433	B2421* BA2421*	B2422 BA2422	B2423 BA2423	B2427* —	B2429* —
Min. Depth of Pour	3.75" (95.3)	3.75" (95.3)	3.75" (95.3)	2.75" (69.9)	2.75" (69.9)	2.75" (69.9)	3.75" (95.3)	2.75" (69.9)
Adjustability	Fully	Fully	Fully	Fully	Fully	Fully	Fully	Fully
Cubic Inch (cm³)	60.0 cu. in.	52.8 cu. in.	50.8 cu. in.	39.5 cu. in.	35.0 cu. in.	34.0 cu. in.	54.0 cu. in.	37.3 cu. in.
Capacity Per Gang	(983.2 cm³)	(865.2 cm³)	(832.5 cm³)	(647.3 cm³)	(573.5 cm³)	(557.2 cm³)	(884.9 cm³)	(611.2 cm³)
Dimensions – A	3.72" (94.5)	3.72" (94.5)	3.72" (94.5)	2.74" (69.6)	2.74" (69.6)	2.74" (69.6)	3.91" (99.3)	2.81" (71.4)
Dimensions – B	4.81" (122.2)	4.81" (122.2)	4.81" (122.2)	4.81" (122.2)	4.81" (122.2)	4.81" (122.2)	4.81" (122.2)	4.81" (122.2)
Dimensions – C	6.00" (152.4)	9.25" (235.0)	12.50" (317.5)	6.00" (152.4)	9.25" (235.0)	12.50" (317.5)	6.00" (152.4)	6.00" (152.4)
Dimensions – D	4.38" (111.3)	4.38" (111.3)	4.38" (111.3)	4.38" (111.3)	4.38" (111.3)	4.38" (111.3)	4.38" (111.3)	4.38" (111.3)
Dimensions – E	3.19" (81.0)	6.44" (163.6)	9.67" (245.6)	3.19" (81.0)	6.44" (163.6)	9.67" (245.6)	3.19" (81.0)	3.19" (81.0)
Knockouts – Sides	(1) ¾", 1", 1¼"	(2) ¾", 1", 1¼"	(3) ¾", 1", 1¼"	(2) ½", (1) ¾"	(4) ½", (1) ¾"	(6) ½", (1) ¾"	(1) ½", (1) 1¼"	(2) ½", (1) ¾"
Knockouts – Ends	(1) ¾", 1", 1¼"	(1) ¾", 1", 1¼"	(1) ¾", 1", 1¼"	(1) ½", (1) ¾"	(2) ½", (1) ¾"	(2) ½", (1) ¾"	(1) ¾", (1) 1"	(1) ½", (1) ¾"
Knockouts – Bottom	(2) ¾", 1", 1¼"	(4) ¾", 1", 1¼"	(6) ¾", 1", 1¼"	(2) ¾", 1", 1¼"	(4) ¾", 1", 1¼"	(6) ¾", 1", 1¼"	(3) ½", (2) ¾"	(3) ½", (2) ¾"
Concrete Cover Included	✓	✓	✓	✓	✓	✓	✓	✓
Closure Plugs Included	—	—	—	—	—	—	—	—
Removable LV Barrier	—	✓	✓	—	✓	✓	—	—

Notes: UL File Number E92074.

CSA File Number LR18416.

* Suitable for single service applications only.

Flush Rectangular Floor Box Covers

Brass	S3825	S3625	S3826	S2425	S2625	S2825	S3425	S3813
Aluminum	SA3825	SA3625	SA3826	SA2425	SA2625	—	—	SA3813
Dimensions 4.15" x 2.99"								
	Duplex Flap	Duplex Screw	Style Line® Opening	2 1/8" x 3/4" Combination	2 1/8" x 1" Combination	2 1/8" Single Receptacle	2 3/8" Single Receptacle	Blank

Carpet Flanges

Tapered Flange

Number of Gangs
Dimensions
Brass
Aluminum
Clear Polycarbonate

1-Gang
6.00" x 4.85"
SB3083
SA3083
S3083



2-Gang
6.00" x 8.13"
SB3084
SA3084
S3084




3-Gang
6.00" x 11.34"
SB3085
SA3085
S3085



Recessed 4- and 8-Gang Concrete Floor Boxes

ScrubShield™
Complies with UL514A



Dimensions Inches (mm)	Stamped Steel			Cast Iron
Style	4-Gang Deep	4-Gang Shallow	8-Gang Deep	4-Gang Shallow
	 HBLCFB301BASE	 HBLCFB401BASE	 HBLCFB501BASE	 HBLCFB401CB
Min. Depth of Pour	4.25" (107.6)	3.00" (76.2)	5.25" (133.4)	3.25" (82.6)
Adjustability	Fully	Fully	Fully	Fully
Cubic Inch (cm³) Capacity Per Chamber	29.5 cu. in. (483.4 cm³)	25.5 cu. in. (417.9 cm³)	49.5 cu. in. (811.2 cm³)	25.5 cu. in. (417.9 cm³)
Dimensions – A	4.0" (101.6)	2.63" (66.8)	5.13" (130.3)	3.13" (79.5)
Dimensions – B	10.0" (254.0)	10.0" (254.0)	10.0" (254.0)	10.0" (254.0)
Dimensions – C	10.0" (254.0)	10.0" (254.0)	10.0" (254.0)	10.0" (254.0)
Threaded Access Holes – Per Chamber	–	–	–	(2) 1"
Knockouts – Per Chamber	(1) Concentric ½", ¾" (1) Concentric ¾", 1" (1) 1¼"	(3) Concentric ½", ¾"	(1) Concentric ½", ¾" (1) Concentric ¾", 1" (1) 1¼"	–
Concrete Cover Included	✓	✓	✓	✓
Closure Plugs Included	–	–	–	✓

Notes: UL File Number E197203.
CSA File Number LR702145.

Floor Box Covers

Die Cast Zinc Cover and Flange Assembly

Dimensions 10.69" x 10.69"

HBLTCGNTSW



Granite

HBLTCGNTBKS



Black

Hubbell – Screw Type Face Plates*

HBLST302SGY



Duplex

HBLDE301SGY



Style Line®

HBLT0310SGY



Toggle

HBLTL318GY



Single Receptacle
(1.56" Boss Dia.)

HBLTL319SGY



Single Receptacle
(1.39" Boss Dia.)

HBLBL300SGY



Blank

HBLIMFSGY



Hubbell iSTATION™
(See pages 166 & 167
for module options)

HBL317SGY



Hubbell
6-Port

Open Systems – Screw Type Face Plates*

HBLAM303SGY HBLAMP313SGY HBLKR314SGY HBLLT309SGY HBLPA308SGY HBLN0309SGY HBLSI305SGY HBLSI315SGY HBLOR306SGY HBLORT322SGY



AMP-ACO



AMP 6-Port



Krone®/Leviton®



SYSTIMAX®



Panduit
Mini-Com®



NORDX® 6-Port
(Cat. 5e jacks only)



Siemon
CT® Series



Siemon
MAX® Series



Ortronics
Series II®



Ortronics
TracJack®

Note: *Catalog number indicated is gray, replace "GY" with the following to designate color: "BK" for Black, "WA" for White, "I" for Ivory.

AMP is a registered trademark of Tyco Electronics Corp. Krone® is a registered trademark of Krone, Inc. Leviton® is a registered trademark of Leviton. SYSTIMAX® is a registered trademark of CommScope, Inc. Mini-Com® and Panduit® are registered trademarks of Panduit Corp. NORDX® is a registered trademark of Belden/CDT, Inc. MAX® and CT® Series are registered trademarks of The Siemon Company. TracJack®, Series II® and Ortronics® are registered trademarks of Ortronics/Legrand.




Nobody delivers like Hubbell Commercial Solutions

Recessed 6-Gang Concrete Floor Boxes

ScrubShield™
Complies with UL514A



Dimensions Inches (mm)	Stamped Steel	Cast Iron
Style 	6-Gang  LCFBSSA	6-Gang  LCFBCA
Min. Depth of Pour	3.50" (88.9)	3.65" (92.7)
Adjustability	Fully	Fully
Cubic Inch (cm³) Capacity Per Chamber	(4) at 38.2 cu. in. (626.0 cm³) (2) at 25.4 cu. in. (416.2 cm³)	(4) at 36.8 cu. in. (603.0 cm³) (2) at 25.4 cu. in. (416.2 cm³)
Dimensions – A	6.18" (157.0)	6.35" (161.3)
Dimensions – B	12.95" (328.9)	13.11" (333.0)
Dimensions – C	12.95" (328.9)	13.11" (333.0)
Threaded Access Holes – Per Chamber	–	(1) ¾" (1) 1¼"
Knockouts – Per Chamber	(1) Concentric 1", 1¼" (1) ¾"	–
Concrete Cover Included	✓	✓
Closure Plugs Included	–	✓
Cover Mounting Brackets Included	✓	✓

Notes: UL File Number E31999.
CSA File Number LR18416.

Floor Box Covers Recessed Floor Box Covers

Smooth Metallic Cover, Flange and Cable Doors for Carpet Applications	Cover Dimensions 10.30" x 10.30"	Aluminum Finish Brass Finish Black Gray	LCFBCALT LCFBCBRSTC LCFBCBKTC LCFBCGYTC	
Metallic Cover, Flange and Cable Doors for Carpet Applications – Carpet Insert Required	Cover Dimensions 10.30" x 10.30"	Aluminum Finish Brass Finish Black Gray	LCFBCALC LCFBCBRSC LCFBCBKC LCFBCGYC	
Reinforced Non-Metallic Cover, Flange and Cable Doors for Carpet Applications – Carpet Insert Required	Cover Dimensions 10.30" x 10.30"	Black Brown Gray Ivory	LCFBCBKA LCFBCBRA LCFBCGYA LCFBCIA	
Smooth Metallic Cover and Cable Doors for Tile Applications	Cover Dimensions 8.31" x 7.70"	Aluminum Finish Brass Finish Black Gray	LCFBCALT LCFBCBRST LCFBCBKT LCFBCGYT	

Face Plates

LCFBP8  Duplex	LCFBP26  Style Line®	LCFBP720  Single Receptacle (for 1.56" boss dia.)	LCFBIM  3-Unit iSTATION™ (See pages 166 & 167 for module options)	LCFBP14  Blank
--	--	--	--	--

Recessed 3-Service Concrete Floor Boxes

ScrubShield™
Complies with UL514A



Dimensions Inches (mm)	Stamped Steel	Cast Iron
	 3SFBS	 3SFBC
Min. Depth of Pour	3.00" (76.2)	3.00" (76.2)
Adjustability	Fully	Fully
Cubic Inch (cm³) Capacity Per Chamber	22.4 cu. in. (367.1 cm ³)	21.6 cu. in. (354.0 cm ³)
Dimensions – A	12.20" (309.9)	12.88" (327.2)
Dimensions – B	5.52" (140.2)	6.00" (152.4)
Dimensions – C	2.88" (73.2)	3.00" (76.2)
Threaded Access Holes	–	Sides (2) ¾" Ends (1) 1¼" Center Area (1) 1¼" (each side)
Knockouts	Sides (2) ¾" Ends (1) 1" Center Area (1) Concentric 1", 1¼" (each side)	–
Concrete Cover Included	✓	✓
Closure Plugs Included	–	–

Notes: UL File Number E31999.
CSA File Number LR18416.

Recessed Floor Box Covers – Carpet Applications

Reinforced Non-Metallic Cover,
Flange and Cable Doors –
Carpet Insert Required –
Dimensions
11.88" x 5.20"

3SFBCBRA



Brown

3SFBCIA



Ivory

3SFBCGYA



Gray

3SFBCBKA



Black

Face Plates

3SFBRP



Duplex
Knockout

3SFBDS



Style Line®
Opening

3SFBS



Single Receptacle
Opening
(for 1.39" boss dia.)

3SFB



Blank

3SFBTP



Voice/Data
(2) Jack Knockouts
(.6" x .75")

3SFBIM





3-Unit iSTATION™
Opening (See pages
166 & 167 for
module options)

Flush Floor Boxes for Wooden Floors

ScrubShield™
Complies with UL514A



Dimensions Inches (mm)		Rectangular Stamped Steel			Round Cast Iron	
	 Collar Material Brass	1-Gang  B2481*	2-Gang  B2482	3-Gang  B2483	1-Gang  B2588*	1-Gang  B2588275*
Adjustability		Semi	Semi	Semi	Non	Non
Cubic Inch (cm³) Capacity Per Gang		42.0 cu. in. (658.3 cm³)	42.5 cu. in. (696.5 cm³)	42.5 cu. in. (696.5 cm³)	18.5 cu. in. (303.2 cm³)	18.5 cu. in. (303.2 cm³)
Dimensions – A		3.13" (79.5)	3.13" (79.5)	3.13" (79.5)	3.65" (92.7)	3.65" (92.7)
Dimensions – B		4.50" (114.3)	4.50" (114.3)	4.50" (114.3)	3.22" (81.8)	3.22" (81.8)
Dimensions – C		3.20" (81.3)	6.42" (163.1)	9.64" (244.9)	4.09" (103.9)	4.09" (103.9)
Threaded Access Holes		–	–	–	Bottom (2) ½"	Sides (2) ¾" Bottom (2) ½"
Knockouts – Sides		(1) ½", ¾", 1"	(2) ½", ¾", 1"	(3) ½", ¾", 1"	–	–
Knockouts – Ends		–	–	–	–	–
Knockouts – Bottom		(1) ½" - 1¼"	(2) ½" - 1¼"	(3) ½" - 1¼"	–	–
Debris Cover Included		✓	✓	✓	–	–
Closure Plugs Included		–	–	–	✓	✓
Removable LV Barrier		–	✓	✓	–	–

Notes: UL File Number E31999.

CSA File Number LR18416.

* Suitable for single service applications only.

Rectangular Covers

Brass
Aluminum
Dimensions
4.15" x 2.99"



Duplex
Flap



Duplex
Screw



Style Line®
Opening



2½" x ¾"
Combination



2½" x 1"
Combination



2½" Single
Receptacle



2⅜" Single
Receptacle



Blank

Round Covers

Brass
Aluminum
3.88" Dia.



Duplex
Flap



Duplex
Screw



2½" x ¾"
Comb.



2½" x 1"
Comb.



2½" Single
Receptacle



2⅜" Single
Receptacle



2½" Single Rec.
(Terrazzo Floor)

Round Flanges

S3182 SA3182 5.25" Dia.
S3082 6.25" Dia.



Rectangular Flanges (Required)


Brass
Aluminum



1-Gang
Dimensions 6.00" x 4.85"



2-Gang
Dimensions 6.00" x 8.13"



3-Gang
Dimensions 6.00" x 11.34"

One Piece Brass Cover and Carpet Flange

Brass
6.25" Dia.



Duplex
Flap



2½" x ¾"
Combination



2½" x 1"
Combination



2½" Single
Receptacle