



## Hubbell SystemOne 2-Gang Floor Boxes


### CFB2G30 Series - Rectangular Cover for 3 in. Minimum Pour

- Designed for applications requiring up to 2 in. conduits (with use of **CFBHUB2**) and a rectangular cover
- When a 3 in. concrete pour is required the insert is removed and requires the finished floor type to be carpet or another engineered floor type

Includes:

- Two removable knock-out plates (1 per gang) can be replaced with 2 in. zinc conduit hub (**CFBHUB2**) when needed
- A ½ in. plastic cover insert is included and allows for easy use in tile, finished concrete or other mediums

Catalog Number	Box Type	Min.Pour Depth	Plate Depth	Device Volume	Cover Series	Knockouts
<b>CFB2G30</b> <b>CFB2G30CR</b>	Standard On-grade	3 in.	2 ½ in.	35 cu. in.	<b>24G/2GFF</b>	½ in. to 2 in.*




### CFB2G25 Series - Rectangular Cover for 2 ½ in. Minimum Pour

- Designed for applications requiring up to 1 in. conduits and a rectangular cover
- When a 2 ½ in. concrete pour is required the insert is removed and requires the finished floor type to be carpet or another engineered floor type

Includes:

- A ½ in. plastic cover insert is included and allows for easy use in tile, finished concrete or other mediums

Catalog Number	Box Type	Min.Pour Depth	Plate Depth	Device Volume	Cover Series	Knockouts
<b>CFB2G25</b> <b>CFB2G25CR</b>	Standard On-grade	2 ½ in.	2 ½ in.	30 cu. in.	<b>24G/2GFF</b>	½ in. to 1 in.



### CFB2G30R Series - Round Cover for 3 ¾ in. Minimum Pour

- Designed for applications requiring up to 2 in. conduits (with use of **CFBHUB2**) and a round cover
- Minimum concrete pour of 3 ¾ in. and includes a collar for post pour adjustment of ¼ in.
- Suitable for all floor finish types

Includes:

- Two removable knock-out plates (1 per gang) can be replaced with 2 in. zinc conduit hub (**CFBHUB2**) when needed


Catalog Number	Box Type	Min.Pour Depth	Plate Depth	Device Volume	Cover Series	Knockouts
<b>CFB2G30R</b> <b>CFB2G30RCR</b>	Standard On-grade	3 ¾ in.	2 ½ in.	35 cu. in.	<b>CFBS1R6/</b> <b>CFBS1R6FF</b>	½ in. to 2 in.*



### CFB2G25R Series - Round Cover for 3 ¼ in. Minimum Pour

- Designed for applications requiring up to 1 in. conduits and a round cover
- Minimum concrete pour of 3 ¼ in. and includes a collar for post pour adjustment of ¼ in.
- Suitable for all floor finish types

Catalog Number	Box Type	Min.Pour Depth	Plate Depth	Device Volume	Cover Series	Knockouts
<b>CFB2G25R</b> <b>CFB2G25RCR</b>	Standard On-grade	3 ¼ in.	2 ½ in.	30 cu. in.	<b>CFBS1R6/</b> <b>CFBS1R6FF</b>	½ in. to 1 in.



\* 2 in. conduits require the use of **CFBHUB2** (purchased separately). See page 9.