

## 3-Inch Core Hole, Two-Piece Unit

| Description                                                                                                                                                                                                                                           | Catalog No.  |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------|
| Large Capacity Multi-Service Pedestal Through-Floor Fitting with (1) 1 1/4 in. E.M.T. stem for low voltage and (1) 1/2 in. E.M.T. stem for power applications.                                                                                        | <b>PT7XC</b> |
| Specifications:                                                                                                                                                                                                                                       |              |
| <ul style="list-style-type: none"> <li>1 – 4 hour fire rating (1 – 3 hour for steel floor units and concrete topping, D900 Series Design)</li> <li>For 2 1/4 in. to 7 in. floor thickness</li> <li>Approved for use in the City of Chicago</li> </ul> |              |



## 2-Inch Core Hole Two-Piece Unit

| Description                                                                                                                                                                                                                                           | Catalog No.  |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------|
| Multi-Service Pedestal Through-Floor Fitting with (1) 1 1/4 in. E.M.T. stem for low voltage and (1) 1/2 in. E.M.T. stem for power applications.                                                                                                       | <b>PT27A</b> |
| Specifications:                                                                                                                                                                                                                                       |              |
| <ul style="list-style-type: none"> <li>1 – 4 hour fire rating (1 – 3 hour for steel floor units and concrete topping, D900 Series Design)</li> <li>For 2 1/4 in. to 7 in. floor thickness</li> <li>Approved for use in the City of Chicago</li> </ul> |              |



Note: \*Includes pre-wired 20A isolated ground duplex receptacle.

## Pedestal Service Fittings (Order 1 plate per gang)

| Description                                                                        | Color/Material                | Catalog No.                                           | Description                                                                        | Color         | Catalog No.                        | Description                                                                          | Color         | Catalog No.                        |
|------------------------------------------------------------------------------------|-------------------------------|-------------------------------------------------------|------------------------------------------------------------------------------------|---------------|------------------------------------|--------------------------------------------------------------------------------------|---------------|------------------------------------|
| 2-Gang                                                                             | Alum. Finish<br>Black<br>Gray | <b>FR280ALA</b><br><b>FR280BKA</b><br><b>FR280GYA</b> | 4-Gang                                                                             | Black<br>Gray | <b>FR480BKA</b><br><b>FR480GYA</b> | 6-Gang                                                                               | Black<br>Gray | <b>FR680BKA</b><br><b>FR680GYA</b> |
| Use with PT27A only.                                                               |                               |                                                       | Use with PT27A or PT7XC.                                                           |               |                                    | Use with PT27A or PT7XC.                                                             |               |                                    |
|  |                               |                                                       |  |               |                                    |  |               |                                    |
| FR280BKA                                                                           |                               |                                                       | FR480GYA                                                                           |               |                                    | FR680BKA                                                                             |               |                                    |

- Painted aluminum housing with low voltage barrier(s); plates and devices sold separately
- For additional barriers, use Catalog No. FRBR1 (see page Q28)
- UL Listed and CSA Certified

## Pedestal Face Plates (Order 1 plate per gang)

| Description               | Color/Material                | Catalog No.                                                 | Description                    | Color/Material                | Catalog No.                                                 |
|---------------------------|-------------------------------|-------------------------------------------------------------|--------------------------------|-------------------------------|-------------------------------------------------------------|
| Duplex                    | Black<br>Gray                 | <b>SS2309DBKA</b><br><b>SS2309DGYA</b>                      | Furniture Feed (3/4 in. KO)    | Alum. Finish<br>Black<br>Gray | <b>SS2309FALA</b><br><b>SS2309FBKA</b><br><b>SS2309FGYA</b> |
| Style Line®/GFCI          | Black<br>Gray                 | <b>SS2309SLBKA</b><br><b>SS2309SLGYA</b>                    | Furniture Feed (1 in. KO)      | Black<br>Gray                 | <b>SS2309F1BKA</b><br><b>SS2309F1GYA</b>                    |
| Single Rec. (1.39 in. OD) | Black<br>Gray                 | <b>SS2309SBKA</b><br><b>SS2309SGYA</b>                      | Bushed Data Opening (1 in. ID) | Black<br>Gray                 | <b>SS2309TBKA</b><br><b>SS2309TGYA</b>                      |
| Blank                     | Alum. Finish<br>Black<br>Gray | <b>SS2309BALA</b><br><b>SS2309BBKA</b><br><b>SS2309BGYA</b> |                                |                               |                                                             |

- Painted aluminum plates
- UL Listed and CSA Certified

**ScrubShield®**

Complies with UL514 A & C