

# Flush Furniture Feed FRPT 3-Inch Core Hole Units

**ScrubShield™**  
Complies with UL514A



## Large Capacity, Low Voltage Flush Furniture Feed FRPT – Two-Piece Units

### Catalog Numbers

#### PT2FIT

Through floor fitting with (1) 2 in. E.M.T. stem. Will accommodate up to 36 Category 5e cables.

#### Specifications:

- UL Listed and CSA Certified.
- 1-2 hour fire rating.
- For 2¼ to 7 in. floor thickness.
- UL installation spacing. Minimum 2 ft. on center and not more than 1 per 65 sq. ft. of floor area.
- Approved for use in the City of Chicago.

### Large Capacity, Low Voltage Through Floor Fitting



PT2FIT

### Catalog Numbers

#### FF2BRS

Brass Finish

#### FF2BK

Black

#### FF2GY

Gray

### Large Capacity Cover/Flange



FF2BK

#### Specifications:

- UL Listed and CSA Certified.
- Cover/flange with 1¼ in. and 2 in. trade size combination knockout.
- Painted aluminum cover and flange.
- Approved for use in the City of Chicago.

## Flush Furniture Feed FRPT – One-Piece Units

### Catalog Numbers

#### PT73FFSDBK

Black

#### PT73FFSDGY

Gray

#### PT73FFSDI

Ivory

Complete assembled unit includes:

- PT73SD floor fitting.
- Aluminum cover with (2) ½ in. threaded hubs for low voltage and (1) ¾ in. threaded hub for power.
- Painted aluminum flange.
- UL Listed and CSA Certified.

### 3-Service Furniture Feed Poke-Through



PT73FFSDGY

### Catalog Numbers

#### PT7FFSDGY

Gray

#### PT7FFSDI

Ivory

### Single-Service Furniture Feed Poke-Through



PT7FFSDGY

Complete assembled unit includes:

- PT71SD floor fitting.
- Aluminum cover with (1) KO to accept a ¾ in. connector.
- Painted aluminum flange.
- UL Listed and CSA Certified.

## Flush Furniture Feed FRPT – Two-Piece Units

### Through-Floor Fittings

#### Catalog Number

#### PT73SD

Through-floor fitting with (1) ¾ in. E.M.T. stem for power and (2) ½ in. low voltage conduit holes.

#### Specifications:

- UL Listed and CSA Certified.
- 1 – 4 hour fire rating (1 – 3 hour for steel floor units and concrete topping, D900 Series Design).

### 3-Service Furniture Feed Through-Floor Fitting



PT73SD

#### Catalog Number

#### PT71SD

Through-floor fitting with (1) ¾ in. E.M.T. stem for power or low voltage applications.

#### Specifications:

- UL Listed and CSA Certified.
- For 2¼ to 7 in. floor thickness.
- UL installation spacing. Minimum 2 ft. on center and not more than 1 per 65 sq. ft. of floor area.

### Single-Service Furniture Feed Through-Floor Fitting



PT71SD

### Service Fittings

#### Catalog Numbers

#### FRF3BK

Black

#### FRF3GY

Gray

#### FRF3I

Ivory

- Aluminum cover with (2) ½ in. threaded hubs for low voltage and (1) ¾ in. threaded hub for power.
- Painted aluminum flange.
- UL Listed and CSA Certified.

### 3-Service Furniture Feed Service Fitting



FRF3GY

### Catalog Numbers

#### FRF1BK

Black

#### FRF1GY

Gray

#### FRF1BRS

Brass Finish

- Aluminum cover with (1) KO to accept a ¾ in. connector.
- Painted aluminum flange.
- UL Listed and CSA Certified.

### Single-Service Furniture Feed Service Fitting



FRF1GY

Note: See page 152 for 3-inch FRPT accessories.



Nobody delivers like Hubbell Commercial Solutions