



Flush Duplex FRPT 3" Diameter – One Piece Units

Catalog Number			Catalog Number		
PT7FSDBLA	Black	Flush Aluminum Poke-Through 	PT7FSDBRS2A	All Brass	Flush Brass Poke-Through 
PT7FSDGYA	Gray		PT7FSDBRS3A	Black/Brass	
PT7FSDIA	Ivory		PT7IGFSDBRSA*	All Brass	
PT7FSDBRA	Brown		* Includes pre-wired 20A isolated ground duplex receptacle.		
PT7IGFSDGYA*	Gray		Complete assembled unit		
PT7IGFSDIA*	Ivory				
* Includes pre-wired 20A isolated ground duplex receptacle.					
Complete assembled unit			Complete assembled unit		
■ PT7FSD through-floor fitting. ■ Pre-wired 20A duplex receptacle. ■ Non-metallic flip lid cover with (2) 1/2" diameter low voltage feed through holes. ■ Painted aluminum flange.			■ PT7FSD through-floor fitting. ■ Pre-wired 20A duplex receptacle. ■ All brass or black non-metallic cover option. ■ Flip lid cover with (2) 1/2" diameter low voltage feed through holes. ■ Solid brass flange.		

Flush FRPT 3" Diameter – Two Piece Units

Through-Floor Fitting

Catalog Number	
PT7FSD (with Junction Box)	Multi-Channel Through Floor Fitting 
PT73SD (without Junction Box)	
Through-floor fitting with (1) ¾" trade size conduit stem for power and (2) ½" low voltage feed through holes.	
Specifications: ■ UL Listed and CSA Certified. ■ 1 - 4 hour fire rating (1- 3 hour for steel floor units and concrete topping, D900 Series Design). ■ For 2 ¼" to 7" floor thickness. ■ UL installation spacing. Minimum 2 ft. on center and not more than 1 per 65 sq. ft. of floor area.	

Service Fittings

Catalog Number			Catalog Number		
FRFBLA	Black	Flush Aluminum Service Fitting 	FRFBR2A	Solid Brass	Flush Brass Service Fitting 
FRFGYA	Gray		■ Pre-wired 20A duplex receptacle. ■ Non-metallic flip lid cover with (2) ½" diameter low voltage feed-through holes. ■ Painted aluminum flange.		
FRFIA	Ivory				
FRFBRA	Brown				

Accessories

Catalog Number			Catalog Number		
PFBRCLBA	Black	Non-Metallic Replacement Covers 	BRS2RCA	Solid Brass	All Brass Replacement Covers 
PFBRCGYA	Gray				
PFBRCLIA	Ivory				
PFBRCLBRA	Brown				