

PolyTuff I Conduit

Trade Size (metric designator)	Catalog Numbers	Feet (m)	Conduit ID/OD Inches (mm)	Bend Radius Inches (mm)
3/8" (12)	G1038	100 (30.5)	.49"/.70" (12.6/17.8)	2.00" (50.8)
1/2" (16)	G1050	100 (30.5)	.63"/.83" (16.1/21.1)	3.00" (76.2)
3/4" (21)	G1075	100 (30.5)	.83"/1.04" (21.1/26.4)	4.00" (101.6)
1" (27)	G1100	100 (30.5)	1.05"/1.30" (26.0/33.1)	5.00" (127.0)
1 1/4" (35)	G1125	100 (30.5)	1.40"/1.65" (35.4/41.8)	6.30" (158.8)
1 1/2" (41)	G1150	50 (15.2)	1.59"/1.88" (40.3/47.8)	7.50" (190.5)
2" (53)	G1200	50 (15.2)	2.03"/2.36" (51.6/59.9)	10.00" (254.0)



PolyTuff I Conduit

Operating Temperature Range

Wet environment	0°F to +140°F (-18°C to +60°C).
Oil environment	0°F to +158°F (-18°C to +70°C).
Dry environment	0°F to +176°F (-18°C to +80°C).

Certifications

UL Listed	UL Standard 1660. Sunlight resistant approved for outdoor use, direct burial.
CSA Certified	Meets requirements of NEC Article 351-B.

Voltage Rating

Maximum	600V.
---------	-------

Material

Conduit	Co-extruded rigid and flexible PVC.
---------	-------------------------------------

PolyTuff II Tubing

Trade Size (metric designator)	Catalog Numbers	Feet (m)	Conduit ID/OD Inches (mm)	Bend Radius Inches (mm)
1/4" (10)	B2025	100 (30.5)	.36"/.57" (9.3/14.5)	1.50" (38.1)
3/8" (12)	B2038	100 (30.5)	.49"/.70" (12.6/17.8)	2.00" (50.8)
1/2" (16)	B2050	100 (30.5)	.63"/.83" (16.1/21.1)	2.00" (50.8)
3/4" (21)	B2075	100 (30.5)	.83"/1.04" (21.1/26.4)	3.00" (76.2)
1" (27)	B2100	100 (30.5)	1.05"/1.30" (26.0/33.1)	3.00" (76.2)
1 1/4" (35)	B2125	100 (30.5)	1.40"/1.65" (35.4/41.8)	5.00" (127.0)
1 1/2" (41)	B2150	50 (15.2)	1.59"/1.88" (40.3/47.8)	5.00" (127.0)
2" (53)	B2200	50 (15.2)	2.03"/2.36" (51.6/59.9)	5.00" (127.0)



PolyTuff II Tubing

Operating Temperature Range

Operating Environment	0°F to +140°F (-18°C to +60°C).
-----------------------	---------------------------------

Certifications

UL Recognized	
CSA Certified	

Voltage Rating

Maximum	Same as wire insulation rating.
---------	---------------------------------

Material

Tubing	Co-extruded rigid and flexible PVC.
--------	-------------------------------------