

Kellems® Wire Management Products
Strain Relief for Liquidtight Conduit
Liquidtight Conduit Grips

HUBBELL



Features

- Helps prevent conduit pull-out and damage at fitting
- Reduces equipment downtime

Ordering Information

| Description | Style | UPC | Catalog Number |
|--|----------|--------------|----------------|
| Liquidtight Conduit, Straight Male Hubbell Fitting | Straight | 783585334837 | H150CNK |

Listings

UL Listed
CSA Certified

Specifications

| | |
|--------------------|-----------------|
| Strand | Stainless Steel |
| Strand Length | 13.5" (34.29) |
| NPT Fitting Size | 1 1/2 Inch |
| Conduit Trade Size | 1 1/2 Inch |

Performance

| Environmental | |
|-----------------------|--|
| Flammability | UL 94-HB and UL 94-V2 |
| Hazardous Location | Suitable for use in hazardous locations per Class I, Div. 2, Class II, Div. 1 & 2, Class III, Div. 1 & 2 |
| Operating Temperature | -30°F to +225°F (-34°C to +107°C) |



Online Resources

[eCatalog](#)
[Installation Instructions](#)

Dimensions in Inches (mm)

Hubbell Wiring Device-Kellems • Hubbell Incorporated (Delaware) • 40 Waterview Drive • Shelton, CT 06484

Phone (800) 288-6000 • Fax (800) 255-1031 • Specifications subject to change without notice.

