

Marine Products
30 Ampere, 125V AC
 2 Pole 3 Wire
Ship-to-Shore Devices



IP56
 SUITABILITY

Inlets Only.



30A 125V

NEMA L5-30R

30A 125V AC Ship-to-Shore Devices

Description	Catalog Numbers
Stylized UV resistant non-metallic shore power inlet has white Centrex cover which makes unit weatherproof when completely closed. Interior has easy-to-wire terminations and is transparent for quick and easy visual inspection. Mounting holes are 2 ³ / ₈ " (60.3) on centers and match existing mounting patterns. Mounting screws and gasket included. Protective rear enclosure/strain relief also included.	HBL303NM
Stylized type 316 stainless steel shore power inlet has easy to use push-button latch that makes unit watertight when fully engaged. Interior has easy-to-wire terminations and is transparent for quick and easy visual inspection. Mounting holes are 2 ³ / ₈ " (60.3) on centers and match existing mounting patterns. Mounting screws and gasket included. Protective rear enclosure/strain relief also included.	HBL303SSBL
Traditional, stainless steel shore power inlet has new easy-to-wire terminations. Interior is transparent for quick and easy visual inspection. Interior is shielded from the elements by a gasketed, self-closing cover, watertight when cover is screwed in place. Mounting holes are 2 ³ / ₈ " (60.3) on centers. Mounting screws and gasket included. Protective rear enclosure/strain relief also included.	HBL303SS
Traditional stainless steel inlet housing; blank for attaching a circuit breaker (not included). Mounting hardware for Carling series breakers included.	HBLCBISS*
Stylized non-metallic inlet housing; blank for attaching a circuit breaker (not included). Mounting hardware for Carling series breakers included.	HBLCBINM
Protective rear cover. Fits all 30A shore power inlets. Secures to back of inlets with 3 screws which are provided.	SR3050**
Replacement interior for #HBL303SS and #60CM61 shore power inlets.	HBL303INT*
Nickel plated brass adapter plate for mounting traditional round stainless steel shore power inlets to FS/FD box.	HBL60CM75*
Traditional stainless steel power outlet has gasketed, self-closing cover, watertight when cover is screwed in place. Mounting holes are 2 ³ / ₈ " (60.3) on centers. Mounting screws and gasket included.	HBL303SSO

Notes: *Not shown.
 ** Not UL/CSA



HBL303NM



HBL303SSBL



HBL303SS



HBLCBINM



HBL303SSO

30A 125V AC Traditional Stainless Steel Inlets

Base and cover are #316 type stainless steel for strength and corrosion resistance.

Self-closing cover assures the interior is shielded from the elements when the inlet is not in use.


Neoprene gasket on underside of cover. For sealing when the cover is closed.

Contact blades are nickel plated brass for corrosion resistance.

New, easy-to-wire interior is transparent for quick, visual inspection of terminations and high-heat resistance.

Threaded base for making a watertight seal. When in use, it mates to the threaded ring of the weatherproof cover on the connector body. When not in use, it mates to the threaded cover.

Three screws "lock-in" the interior once it is in place.



Contacts are nickel plated brass for corrosion resistance.

New easy-to-wire interior is transparent for quick, visual inspection of terminations.

#SR3050 protective rear enclosure cap attaches to contact carrier with 3 screws.

