

Marine Products  
**50 Ampere, 125V AC**  
 2 Pole 3 Wire  
**Ship-to-Shore Devices**



HBL503NM



HBL503RI



HBL503SS



HBL63CM60



HBL77CM15



HBL77CM17

**50A 125V AC Ship-to-Shore Devices**

Description	Catalog Numbers
Stylized non-metallic shore power inlet has UV resistant white Centrex cover which makes unit weatherproof when completely closed. Interior has easy to wire terminals. Mounting holes are 2 <sup>3</sup> / <sub>8</sub> " (60.3) on centers and match existing mounting patterns. Mounting screws and gasket included. <b>IP56 SUITABILITY.</b>	<b>HBL503NM</b>
Stylized type 316 stainless steel shore power inlet has easy to use push-button latch that makes unit watertight when fully engaged. Interior has easy to wire terminals. Mounting holes are 2 <sup>3</sup> / <sub>8</sub> " (60.3) on centers and match existing mounting patterns. Mounting screws and gasket included. <b>IP56 SUITABILITY.</b>	<b>HBL503RI</b>
Traditional stainless steel shore power inlet has gasketed, self-closing cover so interior is shielded from the elements when not in use. Watertight when cover is securely fastened. Mounting holes are 2 <sup>3</sup> / <sub>8</sub> " (60.3) on centers, and rear portion has 2.171" (55.1) diameter. Mounting screws and gasket included. <b>IP56 SUITABILITY.</b>	<b>HBL503SS</b>
Protective rear cover. Fits all inlets except HBL503SS. Secures to back of inlets with 3 screws which are provided.	<b>SR3050* **</b>
Replacement interior for #HBL503SS and #63CM72 shore power inlets.	<b>CR16277*</b>
Nickel plated brass connector body has heat resistant thermost interior and combination metal and rubber cord grip provides superior strain relief capability. Cord grip range is .437"-1.140" (11.1-29.0). <b>IP20 SUITABILITY.</b>	<b>HBL63CM60</b>
Yellow Seal-Tite® cover for connector bodies when used with 50A shore power inlets. Threaded sealing ring makes connections watertight. <b>IP56 SUITABILITY.</b>	<b>HBL77CM15+</b>
White Seal-Tite® cover for connector bodies when used with 50A shore power inlets. Threaded sealing ring makes connections watertight. <b>IP56 SUITABILITY.</b>	<b>HBL77CM15W*+</b>
Nickel plated brass cord clamp assembly with clamp range of .437"-1.140" (11.1-29.0) provides strain relief for terminations on shore power inlets.	<b>HBL77CM67*</b>
Yellow Seal-Tite® cover for weatherproofing 50A connector bodies on extension cords or adapters. <b>IP55 SUITABILITY.</b>	<b>HBL77CM17+</b>

Notes: \*Not shown.  
 + Boots are not UL listable.  
 \*\* Not UL/CSA.

**50A Traditional Stainless Steel Inlets**

