

Fittings	Catalog Numbers	Color		
Blank End Fitting For closing end of raceway.	HBLALU2010B A: 1.84" (46.74) B: .91" (23.11)	Anodized Aluminum		
	HBLALU2010A A: 1.84" (47.74) B: .91" (23.11) C: 1.51" (38.35)	Anodized Aluminum Plate Steel Fitting		
Entrance End Fitting ½ in. N.P.T.	HBLALU2040A A: 4.12" (104.65) B: 1.84" (46.74)	Anodized Aluminum		
	In-Line Switch Fitting (Switch sold separately).	HBLALU2043* A: 1.84" (46.74) B: 6.00" (152.40)	Anodized Aluminum	
In-Line Receptacle Fitting Use this fitting with single receptacle below.		Single Receptacle - 15A Single Receptacle - 15A, Isolated Ground Single Receptacle - 20A Single Receptacle - 20A, Isolated Ground #12 AWG THHN stranded copper wires with 21 in. leads on each end.	PT1RCGY PT1RCIG PT1RGY PT1RIG A: 2.00" (50.7) B: 1.20" (30.4) C: .87" (22.2)	Gray Orange Gray Orange
Ground Adapter (Plated) For connection of equipment grounding conductor to provide an additional ground to raceway. Screws included.		Ground Adapter (Plated) For connection of equipment grounding conductor to provide an additional ground to raceway. Screws included.	HBLALU2009 A: 2.35" (59.8) B: 1.18" (30.0)	Galvanized Steel
Flush Plate Adaptor For feeding HBL2000 Raceway from an existing wall outlet. Locknut included.		Flush Plate Adaptor For feeding HBL2000 Raceway from an existing wall outlet. Locknut included.	HBLALU2051H A: 4.50" (114.3) B: 4.50" (114.3)	Anodized Aluminum
	Note: * HBLALU2001 couplings included.			