



Single Channel

- Single channel aluminum raceway.
- Satin anodized finish.
- Resists oxidation, corrosion and fading.
- Can be installed as recessed or surface mounted.
- UL Listed and CSA Certified.



Wide Selection of Fittings

- Elbows (external, internal, flat) and tee fitting available to accommodate all types of applications.
- HBLALU2001 Coupling included with elbows and tee fitting.



Aluminum Boxes

- Both in-line and standard boxes available.
- Hubbell Handi-Screw® eliminates difficult to install long screws for easier installation.
- Rounded corners eliminate sharp edges.
- One seam construction provides “clean” look.
- Box design allows standard wallplates to be mounted flush with virtually no perimeter profile exposed.
- Full line of metal wallplates available. See section N for selection.



Aluminum PlugTrak® Featuring Exclusive Receptacle Design

- Satin anodized scratch resistant finish.
- Multiple spacing configurations.
- Hubbell designed and manufactured single receptacle.
- Insulation displacement wiring provides superior wire retention.
- Mates with HBLALU2000 Aluminum Raceway.
- Available in 3 ft. (0.9m), 5 ft. (1.5m) and 6 ft. (1.8m) lengths.
- Tamper-Resistant versions available.

Available in Standard, Isolated Ground (IG) and Tamper-Resistant (TR) versions.

Tamper-Resistant



	Amp	Circuits	# Single Recept.	Receptacle Spacing (in.)	Catalog Number
3 Foot	15	Single	6	6	HBLALU20GB306
	15	IG/Single	6	6	HBLALU20IG306
	15	TR/Single	6	6	HBLALU20GB306TR
	20	Single	6	6	HBLALU24GB306
	20	IG/Single	6	6	HBLALU24IG306
	20	TR/Single	6	6	HBLALU24GB306TR
5 Foot	15	Single	10	6	HBLALU20GB506
	15	Single	5	12	HBLALU20GB512
	15	IG/Single	10	6	HBLALU20IG506
	15	TR/Single	5	12	HBLALU20GB512TR
	20	Single	10	6	HBLALU24GB506
	20	Single	5	12	HBLALU24GB512
	20	IG/Single	10	6	HBLALU24IG506
	20	TR/Single	5	12	HBLALU24GB512TR
6 Foot	15	Single	12	6	HBLALU20GB606
	15	Single	6	12	HBLALU20GB612
	15	Single	4	18	HBLALU20GB618
	15	Two	12	6	HBLALU20GBA606
	15	Two	6	12	HBLALU20GBA612
	15	Two	4	18	HBLALU20GBA618
	15	IG/Single	12	6	HBLALU20IG606
	20	Single	12	6	HBLALU24GB606
	20	Single	6	12	HBLALU24GB612
	20	Single	4	18	HBLALU24GB618
	20	Two	12	6	HBLALU24GBA606
	20	Two	6	12	HBLALU24GBA612
	20	Two	4	18	HBLALU24GBA618
	20	IG/Single	12	6	HBLALU24IG606

Note: IG = Isolated Ground and TR = Tamper-Resistant.
 Hubbell Aluminum PlugTrak is supplied with two HBLALU2010B blank end fittings and one HBLALU2001 coupling.

	Description	Catalog Number
Device Boxes	Standard 1-Gang Device Box	HBLALU2047
	Deep 1-Gang Device Box	HBLALU2044
	Standard 2-Gang Device Box	HBLALU20472
	Deep 2-Gang Device Box	HBLALU20442
	Round Box	HBLALU2038
	Elbows and Tees	External Elbow
Internal Elbow		HBLALU2017
Flat Elbow		HBLALU2011
Tee		HBLALU2015
Fittings		Cover Clip
	Supporting Clip	HBLALU2003
	Coupling	HBLALU2001
	Entrance End Fitting	HBLALU2010A
	In-Line Switch Fitting	HBLALU2040A
	Blank End Fitting	HBLALU2010B

Note: See pages R-34 and R-35 for additional information.