

2X2 Flush FRPT, One-Piece Units (PT2X2FIT)

Description	Color	Catalog No.	Description	Color/Material	Catalog No.
2X2 Poke-Through Non-metallic Cover	Black	PT2X2BL	2X2 Poke-Through	Black/Brass	PT2X2BRS3
	Gray	PT2X2GY		Brass Finish/Brass	PT2X2BRS
	Black	PT2X2IGBL*		Black/Brass	PT2X2IGBRS3*
	Gray	PT2X2IGGY*		Brass Finish/Brass	PT2X2IGBRS*
- Pre-wired 20A duplex Style Line® receptacle and (2) Category 5e data jacks - Painted aluminum flange - Approved for use in the City of Chicago			- Pre-wired 20A duplex Style Line® receptacle and (2) Category 5e data jacks - Solid brass flange - Approved for use in the City of Chicago		
					
PT2X2GY			PT2X2BRS3		

Note: *Includes pre-wired 20A isolated ground duplex Style Line® receptacle.

2X2 Flush FRPT, Two-Piece Units

Description	Catalog No.
Multi-Channel Through-Floor Fitting with (1) 3/4 in. E.M.T. stem with junction box for power and (2) 1/2 in. E.M.T. stems for low voltage.	PT2X2FIT
	
Specifications: 1 – 4 hour fire rating (1 – 3 hour for steel floor units and concrete topping, D900 Series Design) - For 2 1/4 in. to 7 in. floor thickness - UL installation spacing – minimum 2 ft. on center and not more than one per 65 sq. ft. of floor area - Approved for use in the City of Chicago	

Service Fittings

Description	Color	Catalog No.	Description	Color/Material	Catalog No.
2X2 Service Fitting Non-metallic Cover	Black	PT2X2SFBL	2X2 Poke-Through Non-metallic Cover	Black/Brass	PT2X2SFBR3
	Gray	PT2X2SFGY		Brass Finish/Brass	PT2X2SFBR3
- Pre-wired 20A duplex Style Line® receptacle and (2) Category 5e data jacks - Painted aluminum flange			- Pre-wired 20A duplex Style Line® receptacle and (2) Category 5e data jacks - Solid brass flange		
					
PT2X2SFBL			PT2X2SFBR3		

Accessories

Description	Color/Material	Catalog No.
Non-Metallic Replacement Covers	Brass Finish	PT2X2CBRS
	Black	PT2X2CBL
	Gray	PT2X2CGY
		
PT2X2CBL		

Note: See page Q28 for 3 inch closure plug.

ScrubShield®

Complies with UL514 A & C