

# 2X2 Flush FRPT 3-Inch Core Hole Units

## 2X2 Flush FRPT – One-Piece Units

### Catalog Numbers

<b>PT2X2BL</b>	Black
<b>PT2X2GY</b>	Gray
<b>PT2X2IGBL*</b>	Black
<b>PT2X2IGGY*</b>	Gray

### 2X2 Aluminum Poke-Through



**PT2X2GY**

\*Includes pre-wired 20A isolated ground duplex Style Line® receptacle.

Complete assembled unit includes:

- **PT2X2FIT** through-floor fitting.
- Pre-wired 20A duplex Style Line® receptacle & (2) Category 5e data jacks.
- Non-metallic cover.
- Painted aluminum flange.
- UL Listed and CSA Certified.
- Approved for use in the City of Chicago.

### Catalog Numbers

<b>PT2X2BRS3</b>	Black/Brass
<b>PT2X2BRS</b>	Brass Finish/Brass
<b>PT2X2IGBRS3*</b>	Black/Brass
<b>PT2X2IGBRS*</b>	Brass Finish/Brass

### 2X2 Black/Brass Poke-Through



**PT2X2BRS3**

\*Includes pre-wired 20A isolated ground duplex Style Line® receptacle.

Complete assembled unit includes:

- **PT2X2FIT** through-floor fitting.
- Pre-wired 20A duplex Style Line® receptacle & (2) Category 5e data jacks.
- Non-metallic cover.
- Solid brass flange.
- UL Listed and CSA Certified.
- Approved for use in the City of Chicago.

## 2X2 Flush FRPT – Two-Piece Units

### Through-Floor Fitting

#### Catalog Numbers

**PT2X2FIT**

#### Multi-Channel Through-Floor Fitting

Through-floor fitting with (1) 3/4 in. E.M.T. stem with junction box for power and (2) 1/2 in. E.M.T. stems for low voltage.



**PT2X2FIT**

Specifications:

- UL Listed and CSA Certified.
- 1 – 4 hour fire rating (1 – 3 hour for steel floor units and concrete topping (D900 Series Design)).
- For 2 1/4 in. to 7 in. floor thickness.
- UL installation spacing. Minimum 2 ft. on center and not more than one per 65 sq. ft. of floor area.
- Approved for use in the City of Chicago.

### Service Fittings

#### Catalog Numbers

<b>PT2X2SFBL</b>	Black
<b>PT2X2SFGY</b>	Gray

### 2X2 Black Service Fitting



**PT2X2SFBL**

- Pre-wired 20A duplex Style Line® receptacle & (2) Category 5e data jacks.
- Non-metallic cover.
- Painted aluminum flange.
- UL Listed and CSA Certified.

#### Catalog Numbers

<b>PT2X2SFBR33</b>	Black/Brass
<b>PT2X2SFBR3</b>	Brass Finish/Brass

### 2X2 Black/Brass Service Fitting



**PT2X2SFBR33**

- Pre-wired 20A duplex Style Line® receptacle & (2) Category 5e data jacks.
- Non-metallic cover.
- Solid brass flange.
- UL Listed and CSA Certified.

### Accessories

#### Catalog Numbers

<b>PT2X2CBL</b>	Black
<b>PT2X2CGY</b>	Gray
<b>PT2X2CBRS</b>	Brass Finish

### Non-Metallic Replacement Covers



**PT2X2CBL**

Note: See page 152 for 3-inch closure plug.