



## 2X2 Flush Duplex FRPT, One-Piece Units (PT7FSD)

Description	Color	Catalog No.	Description	Color/Material	Catalog No.
Flush Poke-Through	Black Brown Gray Ivory Gray Ivory	<b>PT7FSDBLA</b> <b>PT7FSDBRA</b> <b>PT7FSDGYA</b> <b>PT7FSDIA</b> <b>PT7IGFSDGYA*</b> <b>PT7IGFSDIA*</b>	Flush Brass Poke-Through	All Brass Black/Brass All Brass	<b>PT7FSDBR2A</b> <b>PT7FSDBR3A</b> <b>PT7IGFSDBRSA*</b>
<p>Complete assembled unit includes:</p> <ul style="list-style-type: none"> <li>• Pre-wired 20A duplex receptacle</li> <li>• Non-metallic flip lid cover with (2) 1/2 in. diameter low voltage feed-through holes</li> <li>• Painted aluminum flange</li> </ul>			<p>Complete assembled unit includes:</p> <ul style="list-style-type: none"> <li>• Pre-wired 20A duplex receptacle</li> <li>• All brass or black non-metallic cover option</li> <li>• Flip lid cover with (2) 1/2 in. diameter low voltage feed-through holes</li> <li>• Solid brass flange</li> </ul>		



Note: \*Includes pre-wired 20A isolated ground duplex receptacle.

## Flush FRPT, Two-Piece Units

Description	Catalog No.
Multi-Channel Through-Floor Fitting with (1) 3/4 in. E.M.T. stem for power and (2) 1/2 in. low voltage feed-through holes.	<b>PT7FSD</b> (with Junction Box) <b>PT73SD</b> (without Junction Box)
<p>Specifications:</p> <ul style="list-style-type: none"> <li>• 1 – 4 hour fire rating (1 – 3 hour for steel floor units and concrete topping, D900 Series Design)</li> <li>• For 2 1/4 in. to 7 in. floor thickness</li> <li>• UL installation spacing – minimum 2 ft. on center and not more than one per 65 sq. ft. of floor area</li> </ul>	



## Service Fittings

Description	Color	Catalog No.	Description	Color/Material	Catalog No.
Flush Aluminum Service Fitting	Black Brown Gray Ivory	<b>FRFBLA</b> <b>FRFBRA</b> <b>FRFGYA</b> <b>FRFIA</b>	2X2 Poke-Through	Solid Brass	<b>FRFBR2A</b>
<p>Complete assembled unit includes:</p> <ul style="list-style-type: none"> <li>• Pre-wired 20A duplex receptacle</li> <li>• Non-metallic flip lid cover with (2) 1/2 in. diameter low voltage feed-through holes</li> <li>• Painted aluminum flange</li> </ul>			<p>Complete assembled unit includes:</p> <ul style="list-style-type: none"> <li>• Pre-wired 20A duplex receptacle</li> <li>• Solid brass flip lid cover with (2) 1/2 in. diameter low voltage feed-through holes</li> <li>• Solid brass flange</li> </ul>		



## Accessories

Description	Color	Catalog No.	Description	Color/Material	Catalog No.
Non-Metallic Replacement Covers	Black Brown Gray Ivory	<b>PFBRCBLA</b> <b>PFBRCBRA</b> <b>PFBRGAYA</b> <b>PFBRICIA</b>	All Brass Replacement Covers	Solid Brass	<b>BRS2RCA</b>



Note: See page Q28 for 3-inch FRPT accessories.



Complies with UL514 A & C