

# Fire-Rated Poke-Throughs ScrubShield™ Flush Duplex Series



**One-Piece Units:** Complete with flush service fitting and a through-floor fitting. These units are all pre-wired.



PT7FSDBR2A

**Two-Piece Units:** Order flush service fitting and through-floor fitting separately.



PT7FSD



FRFGYA

## One-Piece Units Standard Duplex – Painted Aluminum

Description	Color	Catalog Numbers	Canadian Series* Catalog Numbers
With Hubbell HBL5352 series (20A) specification grade receptacle & two low-voltage knockouts. Equipped with a cast aluminum carpet flange and a thermoplastic (ABS) duplex flap cover.	Brown	PT7FSDBRA	PT7FSDBRCA
	Black	PT7FSDBLA	—
	Gray	PT7FSDGYA	PT7FSDGYCA
	Ivory	PT7FSDIA	PT7FSDICA

\*Canadian series is CSA Certified and equipped with HBL5252 (15A) duplex receptacle.

## Standard Duplex – Brass

Description	Type	Catalog Numbers
All brass: Includes brass carpet flange and matching brass duplex flap cover. Equipped with a pre-wired Hubbell HBL5352 black receptacle and two brass low-voltage knockouts.	All Brass	PT7FSDBR2A
Partial brass: Same as Hubbell PT7FSDBR2A except with a black thermoplastic (ABS) duplex flap cover.	Partial Brass	PT7FSDBR3A

## Isolated Ground – Painted Aluminum

Description	Color	Catalog Numbers
With Hubbell IG5362 (20A) isolated ground receptacle & two low-voltage knockouts. Equipped with a cast aluminum carpet flange and a thermoplastic (ABS) duplex flap cover.	Gray	PT7IGFSDGYA
	Ivory	PT7IGFSDIA

## Isolated Ground – Brass

Description	Type	Catalog Number
Same as Hubbell PT7FSDBR2A except pre-wired with a Hubbell IG5362 series (20A) isolated ground receptacle.	All Brass	PT7IGFSDBRSA

## Two-Piece Units Flush Service Fittings

Description	Color	Catalog Numbers	Canadian Series* Catalog Numbers
With pre-wired Hubbell HBL5352 series (20A) specification grade receptacle & two low-voltage knockouts. Equipped with a cast aluminum carpet flange and a thermoplastic (ABS) duplex flap cover.	Brown	FRFBRA	—
	Black	FRFBLA	—
	Gray	FRFGYA	FRFGYCNA*
	Ivory	FRFIA	FRFICNA*
	All Brass	FRFBR2A	—

\*Canadian series is CSA Certified and equipped with HBL5252 (15A) duplex receptacle.

## Through-Floor Fittings

Description	Type	Catalog Numbers
Three-service poke-through fittings install in a 3" (76.2) diameter core drilled hole and will accommodate a floor thickness range of 2 1/4" - 7" (57.2 - 177.8). Includes a 3/4" EMT tube for power wiring.	With junction box	PT7FSD
	Without junction box	PT73SD