



### AV Inspired Fire-Rated Poke-Through

The Hubbell S1PTAVXXX offers an industry leading 1½" data/AV EMT and ¾" power EMT to maximize use of the 4" core hole.



### Multiple Sub-Plates

Allow for use of most standard and third party devices.



### Fire Rating

Fire barrier expands during fire conditions to maintain the floor's fire rating up to four hours.



### Unique Cover Design

Durable cast aluminum construction available in black, gray, brass, aluminum and ivory powder coat finishes.

- UL Listed for Use in 1 – 4 Hour Fire Rated Floors at 100% Rated Fill
- Excellent Solution for Retrofit and New Construction
- Features ScrubShield® Technology That Exceeds UL514 Scrub Water Exclusion Requirements
- RoHS Compliant

### Specifications



- UL installation spacing – minimum two feet on center, not more than one per 65 square feet of floor area in each span
- SystemOne Fire-Rated Poke-Throughs are approved for use in the City of Chicago
- Meets ADA standards for accessible design, section 4.3.8












Complies with UL514 A & C



## Hubbell SystemOne 4-Inch Core Hole – One-Piece Poke Throughs

All Hubbell SystemOne 4-inch core, one-piece poke-throughs include the sub-plate and cover to simplify your order and reduce installation time. Units are also available with a power junction box installed. The junction box is also available for purchase separately.

Description	Color	Catalog No. without Junction Box	Catalog No. with Junction Box*	
<p><b>One-Piece 4X4 Poke-Through</b> Assembled-unit includes:</p> <ul style="list-style-type: none"> <li>• Hubbell SystemOne 4X4 floor fitting (S1PT4X4FIT)</li> <li>• 4X4 sub-plate (S1SP4X4)</li> <li>• Finish flange and universal carpet cover assembly (S1CFCxx)</li> <li>• 4-hour fire classification</li> </ul> <p>Keystone openings accept Hubbell modular jacks, X-END connectors and flush multimedia Snap Fit connectors. Receptacles feature single or two circuit wiring and isolated ground capability.</p>	<p>Aluminum Finish Brass Finish Black/Brass Finish Black Gray</p> 	<p><b>S1PT4X4AL</b> <b>S1PT4X4BRS</b> <b>S1PT4X4BRS3</b> <b>S1PT4X4BL</b> <b>S1PT4X4GY</b></p>	<p><b>S1PT4X4ALJ</b> <b>S1PT4X4BRSJ</b> <b>S1PT4X4BRS3J</b> <b>S1PT4X4BLJ</b> <b>S1PT4X4GYJ</b></p>	
<p><b>One-Piece Dual Style Line® Decorator Poke-Through</b> Assembled-unit includes:</p> <ul style="list-style-type: none"> <li>• Hubbell SystemOne dual channel floor fitting (S1PTFIT)</li> <li>• Dual Style Line® Decorator opening sub-plate (S1SP)</li> <li>• Finish flange and universal carpet cover assembly (S1CFCxx)</li> <li>• 4-hour fire classification</li> </ul> <p>Style Line® Decorator openings accept two Style Line® Decorator or one surge or GFCI receptacle and one Style Line® Decorator receptacle. Outlet frames can be used to convert the application to a 6-port multi-service or a 12-port all communication solution. Fitting is 4-hr rated at 100% fill to accommodate (12) Cat 6A cables (0.330" diameter).</p>	<p>Aluminum Finish Brass Finish Black Gray</p> 	<p><b>S1PTAL</b> <b>S1PTBRS</b> <b>S1PTBL</b> <b>S1PTGY</b></p>	<p><b>S1PTALJ</b> <b>S1PTBRSJ</b> <b>S1PTBLJ</b> <b>S1PTGYJ</b></p>	
<p><b>One-Piece Modular AV Poke-Through</b> Assembled-unit includes:</p> <ul style="list-style-type: none"> <li>• Hubbell SystemOne AV floor fitting (S1PTAVFIT)</li> <li>• 20A, 125V power and 3-unit Hubbell iSTATION sub-plate (S1SP3IM)</li> <li>• Finish flange and universal carpet cover assembly (S1CFCxx)</li> <li>• 4-hour fire classification</li> </ul> <p>The Hubbell iSTATION's recessed opening can accommodate datAVoice/audio and video solutions including 15-pin VGA, RCA, S-Video, 3.5mm stereo, X-END, HDMI and XLR microphone jacks.</p>	<p>Aluminum Finish Brass Finish Black Gray</p> 	<p><b>S1PT3IMAL</b> <b>S1PT3IMBRS</b> <b>S1PT3IMBL</b> <b>S1PT3IMGY</b></p>	<p><b>S1PT3IMALJ</b> <b>S1PT3IMBRSJ</b> <b>S1PT3IMBLJ</b> <b>S1PT3IMGYJ</b></p>	
<p><b>One-Piece Furniture Feed Poke-Through</b> Assembled-unit includes:</p> <ul style="list-style-type: none"> <li>• Hubbell SystemOne AV floor fitting (S1PTAVFIT)</li> <li>• Hubbell SystemOne Furniture Feed Cover Plate (S1SPFFxx)</li> <li>• 4-hour fire classification</li> </ul> <p>This solution provides one 3/4 in. conduit for power and one 1 1/2 in. conduit for low-voltage. Furnished with two screw-in flexible metal conduit connectors.</p>	<p>Aluminum Finish Brass Finish Black Gray</p> 	<p><b>S1PTFFAL</b> <b>S1PTFFBRS</b> <b>S1PTFFBL</b> <b>S1PTFFGY</b></p>	<p><b>S1PTFFALJ</b> <b>S1PTFFBRSJ</b> <b>S1PTFFBLJ</b> <b>S1PTFFGYJ</b></p>	 

Note: \*Junction box factory installed on through floor fitting.



Complies with UL514 A & C



## Hubbell SystemOne 4-Inch Core, Three-Piece Units

Description	Catalog No. without Junction Box	Catalog No. with Junction Box*
<p><b>4X4 Through Floor Fitting</b> Through floor fitting with two 3/4 in. E.M.T. for communications and one 3/4 in. E.M.T. for power. For use with Hubbell SystemOne Universal Covers and S1SP4X4 and S1SPTL series sub-plates only. Universal cover and sub-plate ordered separately. 4-hour fire classification.</p>	<b>S1PT4X4FIT</b>	<b>S1PT4X4FITJ</b>
<p><b>Dual Channel Through Floor Fitting</b> Through floor fitting with two 1 in. E.M.T. conduit stems to feed power and/or communication services. For use with Hubbell SystemOne universal covers and all Hubbell sub-plates except S1SP4X4 and S1SPTL series. Universal cover and sub-plate ordered separately. 4-hour fire classification.</p>	<b>S1PTFIT</b>	<b>S1PTFITJ</b>
<p><b>AV Through Floor Fitting</b> Through floor fitting with one 3/4 in. E.M.T. conduit stem for power and one 1 1/2 in. E.M.T. conduit stem for communication services. Ideal for demanding, high capacity audio/video and data requirements. For use with Hubbell SystemOne universal covers and all Hubbell sub-plates except S1SP4X4 and S1SPTL series. Universal cover and sub-plate ordered separately. 4-hour fire classification.</p>	<b>S1PTAVFIT</b>	<b>S1PTAVFITJ</b>



Note: \*Junction box factory installed on through floor fitting.

### Hubbell SystemOne Universal Covers




- Cast aluminum construction
- Durable powder coat finish

Description	Catalog No.
Carpet	<b>S1CFCxx</b>
Tile	<b>S1TFCxx</b>



xx = Color: **AL** (Aluminum Finish), **BRS** (Brass Finish), **BL** (Black), **GY** (Gray) and **I** (Ivory).

















### Poke Through Accessories

Description	Catalog No.								
<p><b>Abandonment Plates</b> Used to cover abandoned SystemOne Fire-Rated Poke-Throughs or Floor Boxes.</p>	 Black <b>S1AP4BL</b> Gray <b>S1AP4GY</b>								
<p><b>Fire-Rated Closure Plug</b> Used to seal a 4-inch core hole when the FRPT is no longer required and the through-floor fitting is removed. Maintains the floor's 1-4 hour fire rating.</p>	 Black <b>S1FRP4BL</b> Gray <b>S1FRP4GY</b>								
<p><b>Power Junction Box</b> For use with SystemOne Fire-Rated Poke-Throughs. Provides 27.0 cubic inches. (1) 3/4 and (1) 1" E.M.T. connector supplied. Trade size knockouts:</p> <table border="0"> <tr> <td>Top</td> <td>(1) 1 inch</td> </tr> <tr> <td>Bottom</td> <td>(1) 3/4 inch</td> </tr> <tr> <td>Sides</td> <td>(2) 1/2 inch</td> </tr> <tr> <td></td> <td>(1) 3/4 inch</td> </tr> </table>	Top	(1) 1 inch	Bottom	(1) 3/4 inch	Sides	(2) 1/2 inch		(1) 3/4 inch	 <b>S1FRPTJB</b>
Top	(1) 1 inch								
Bottom	(1) 3/4 inch								
Sides	(2) 1/2 inch								
	(1) 3/4 inch								






Complies with UL514 A & C



Description	Catalog No.	Description	Catalog No.	Description	Catalog No.
<b>Style Line® Decorator/GFCI</b> (2) Style Line® Decorator openings for power and/or datacom applications.	 <b>S1SP</b>	<b>Duplex/Duplex</b> (2) Duplex openings for power and/or datacom applications.	 <b>S1SPDU</b>	<b>Duplex/Style Line® Decorator</b> (1) Duplex and (1) Style Line® Decorator opening for power and/or datacom applications.	 <b>S1SPDUSL</b>
<b>Hubbell 4 X 4</b> (4) 20A, 125V receptacles. (4) Keystone openings for Hubbell jacks or flush AV connectors. Power can be wired as single or two circuit with isolated ground capability.	 <b>S1SP4X4</b>	<b>Carpet Furniture Feed Cover/Flange*</b> (1) 3/4" and (1) 1 1/2" N.P.T. access holes for power and/or datacom applications. Universal cover not required. Includes carpet flange.		<b>Tile Furniture Feed Cover/Flange*</b> (1) 3/4" and (1) 1 1/2" N.P.T. access holes for power and/or datacom applications. Universal cover not required. Includes tile flange.	
Provided with 15 ft. wire leads	<b>S1SP4X415</b>	Aluminum Fin.	<b>S1SPFFAL</b>	Aluminum Fin.	<b>S1SPFFTAL</b>
Provided with 30 ft. wire leads	<b>S1SP4X430</b>	Brass Fin.	<b>S1SPFFBRS</b>	Brass Fin.	<b>S1SPFFTBR</b>
		Black	<b>S1SPFFBL</b>	Black	<b>S1SPFFTBL</b>
		Gray	<b>S1SPFFGY</b>	Gray	<b>S1SPFTGY</b>
<b>Single Receptacle + Data</b> Opening for 20 or 30A Twist-Lock® receptacle (1.56" OD) and (2) Keystone openings for Hubbell jacks or flush AV connectors.	 <b>S1SPTL</b>	<b>Hubbell DataCom + Power</b> (1) 20A, 125V receptacle and 3-unit recessed Hubbell iSTATION opening for data, voice, and AV applications.	 <b>S1SP3IM</b>	<b>Hubbell DataCom + Duplex</b> (1) Duplex opening, (2) flush Keystone openings and 1.5 unit recessed Hubbell iSTATION opening for data, voice and AV applications.	 <b>S1SPDU2IM</b>
<b>Hubbell DataCom + Style Line® Decorator</b> (1) Style Line® Decorator opening, (2) flush Keystone openings and 1.5 unit recessed Hubbell iSTATION opening for data, voice and AV applications.	 <b>S1SPSL2IM</b>	<b>Hubbell DataCom</b> 1 unit flush Hubbell iSTATION opening and 3-unit recessed Hubbell iSTATION opening for data, voice, and AV applications.	 <b>S1SP4IM</b>	<b>Active Multimedia + Power</b> Single 20A, 125V receptacle; (2) flush Keystone openings; (1) rectangular Style Line® Decorator opening to accommodate active multimedia modules or low voltage outlet frames.	 <b>S1SPAMM20</b>
<b>Extron® or FSR + Power</b> (1) 20A, 125V receptacle. Recessed opening for (3) single Extron® MAAP series adapter plates or FSR IPS plates.	 <b>S1SPEXT1</b>	<b>Extron® or FSR + Power</b> (1) 20A, 125V receptacle. Recessed opening for (1) single Extron® MAAP and (2) single AAP series adapter plates or FSR IPS plates.	 <b>S1SPEXT2</b>	<b>Extron® or FSR Single-Service</b> Recessed opening for (2) single Extron® MAAP and (2) single AAP series adapter plates or FSR IPS plates.	 <b>S1SPEXT3</b>
<b>Extron® AAP + Power</b> (1) 20A, 125V receptacle. (2) flush Keystone and recessed opening for (2) single Extron® AAP Series adapter plates.	 <b>S1SPEXT4</b>				

Note: \*Furnished with two screw-in flexible metal conduit connectors. See Section C for complete offering of Hubbell jacks and frames.  
† See page Q23 for FRPT Configuration Chart.

## Sub-Plate Accessories

Description	Description	Catalog No.
<b>Replacement Threaded Conduit Plugs</b> Used with S1SPFFxx and S1SPFFTxx ONLY. Sub-plate is supplied with plugs.	Black Style Line® decorator blank frame.	 <b>2100BK</b>
 1 1/2" Plug		
 3/4" Plug		
Catalog No.	<b>S1FP15xx</b>	<b>S1FP34xx</b>

xx = Color: **AL** (Aluminum Finish), **BRS** (Brass Finish), **BK** (Black), and **GY** (Gray). See page V30 for color chart.

Extron® is a registered trademark of Extron Electronics.

**ScrubShield®**  
Complies with UL514 A & C

