


















Hubbell SystemOne Non-Metallic Floor Box


| | Round Multi-Service PVC Floor Box | | | |
|---------------|---|---|---------------------|---|
| S1PFB | Features (2) 1 1/2" hubs for low voltage and (2) 1" hubs for power. Includes concrete cover and a variety of reducers and closure plugs that allow a full range of conduit sizes. |  | Min. Depth of Pour | Ranges from 3" to 5" depending on application. See sub-plates below for details. |
| | | | Capacity | 100 cubic inches prior to cutting level to floor (19.5 cubic inches per inch of depth). |
| | | | Diameter (External) | 5.75" |
| | | | Diameter (Internal) | 5.00" |
| | | | Height | 6.00" |
| | | | Hubs | (2) 1 1/2" and (2) 1" conduit hubs |
| | | | Conduit Selection | Accepts 3/4", 1", 1 1/4", 1 1/2" schedule 40 and schedule 80 rigid PVC conduit and E.N.T. (electrical non-metallic tubing). |
| S1DIV1 | Side by Side Divider Required for use with catalog number S1SP (Style Line®/GFCI) sub-plate when used in multi-service applications. All other sub-plates include the appropriate dividers. |  | | |

Hubbell SystemOne Universal Covers

| Universal, Cast Aluminum Carpet Flange & Cover Assembly | | | Universal, Cast Aluminum Tile Flange & Cover Assembly | |
|---|--|---|---|--|
| Catalog Number | |  | Catalog Number |  |
| S1FCBRS Brass | | | S1TFCBRS Brass | |
| S1FCAL Aluminum | | | S1TFCAL Aluminum | |
| S1FCBL Black | | | S1TFCBL Black | |
| S1FCGY Gray | | | S1TFCGY Gray | |
| S1FCFI Ivory | | | S1TFCI Ivory | |
| | <ul style="list-style-type: none"> ■ Cast aluminum construction ■ Powder coat finish | | | <ul style="list-style-type: none"> ■ Cast aluminum construction ■ Powder coat finish |

Sub-Plates

| Catalog Number | | Catalog Number | | Catalog Number | |
|---|--|---|---|---|---|
| S1SP Style Line/GFCI | (2) Style Line openings for power and/or datacom applications. |  | S1SP4X4 Hubbell 4 X 4 | (4) 20A, 125V receptacles. (4) Keystone openings for Hubbell jacks or flush A/V connectors. |  |
| | | 3 | | | 4 |
| S1SP4IM Hubbell Datacom | 1 unit flush INFIneSTATION™ opening. 3 unit recessed INFIneSTATION opening for data, voice, and A/V applications. (See back cover for details) |  | S1SP3IM Hubbell A/V + Power | (1) 20A, 125V receptacle. 3 unit recessed INFIneSTATION opening for data, voice, and A/V applications. (See back cover for details) |  |
| | | 3.5 | | | 5 |
| S1SPFFBRS Brass Furniture | | | S1SPFFAL Alum. Feed Cover/ | | |
| S1SPFFAL Alum. Feed Cover/ | | | S1SPFFBL Black Flange | | |
| S1SPFFBL Black Flange | | | S1SPFFGY Gray | | |
| S1SPFFGY Gray | (1) 3/4" & (1) 1 1/2" KOs for power and/or datacom applications. Universal Cover not required. Includes carpet flange. | | | |  |
| | | | | | 3 |
| S1SPEXT1 Extron® MAAP + Power | (1) 20A, 125V receptacle. Recessed opening for (3) single Extron MAAP Series adapter plates. |  | S1SPEXT2 Extron AAP + Power | (1) 20A, 125V receptacle. Recessed opening for (1) single Extron MAAP and (2) single AAP Series adapter plates. |  |
| | | 4 | | | 4 |
| S1SPEXT3 Extron Datacom | Recessed opening for (2) single Extron MAAP and (2) single AAP Series adapter plates. |  | | | |
| | | 4.5 | | | |
| S1SPORT Ortronics Series II® + Power | (1) 20A, 125V receptacle. Recessed opening for (3) 1 unit Ortronics Series II modules. |  | S1SPTRAC Ortronics TracJack® + Power | (1) 20A, 125V receptacle. Recessed bezel for (6) Ortronics TracJack modules. |  |
| | | 5 | | | 3.5 |
| S1SPMAX Siemon MAX® + Power | (1) 20A, 125V receptacle. Recessed bezel for (6) Siemon MAX modules. |  | | | |
| | | 5 | | | |
| S1SP4X4PA Panduit Mini-Com® 4 X 4 | (4) 20A, 125V receptacles (4) Openings for Panduit Mini-Com Connectivity. |  | S1SP4X4SYS SYSTIMAX® 4 X 4 | (4) 20A, 125V receptacles. (4) Openings for SYSTIMAX Connectivity. |  |
| | | 4 | | | 4 |

 Signifies minimum depth of concrete pour in inches for Hubbell SystemOne S1PFB Floor Box.