

PRODUCT DATASHEET

AREA LIGHT 150W 120-347V D 3CCT T3 BZ

AREA LIGHT DUAL SELECTABLE | Area Light with selectable CCT and wattage



PERFOR-
MANCE
CLASS

TECHNICAL DATA

Additional product data

Ordering Abbreviation	AREAFLD6AS150UNHDSC2T3BZ
Abbrev. With Packaging Info.	AREAFLD6AS150UNHDSC2T3BZ 1/CS 1/SKU
NAED	63851
Family Brand Name	PERFORMANCE CLASS™
General Description	AREA FLOOD 6A, SELECTABLE WATTAGE 90/120/150W, 120-347V, 0-10V DIMMING, CCT SELECTABLE 3000/4000/5000K, TYPE 3 DISTRIBUTION, BRONZE
Warranty	5 years

Electrical data

Nominal Wattage	90.00/120.00/150.00 W
Nominal voltage	120.00...347.00 V
Power factor	≥0.90
Total Harmonic Distortion	< 20 %

Photometrical data

Lumens	13500/18000/22500 lm
Efficacy	150 lm/W
Color Temperature/CCT	3000/4000/5000 K
Color Rendering Index (CRI)	80
Luminaire Type	Area light

Dimensions & Weight

Length	24.75 in
Width	10.62 in
Height	6.3 in
Product weight	9.92 lb

Materials & Colors

Luminaire Finish	Bronze
Housing color	Bronze
Housing	Aluminum
Mercury content	0.0 mg

Application & Mounting

Ambient temperature range	-40...+50 °C
Maximum Operating Temperature	122 °F
Minimum Operating Temperature	-40 °F

Dimming	Yes
Type of Dimming	0-10V
Mounting	Surface
Indoor/Outdoor	Outdoor
Replaceable light source	No
Primary Lamp Type	SMD

Lifespan

Average Rated Life (hr)	100000
-------------------------	--------

Logistical data

Case Qty	1
Case Length (in)	24.213
Case Width (in)	11.811
Case Depth (in)	5.906
Case Cube (ft)	0.977
Case Weight (lbs)	10.692
Pallet Qty	48

Certificates & Standards

Certification Listing	RoHS / FCC / cULus
Replaceable light source (EPREL)	Not replaceable

DOWNLOAD DATA

Spec Sheets and Product Documents	Document name
 Product Family Spec Sheet	DUAL SELECTABLE AREA FLOOD 6A

Photometric and lighting design files	Document name
 IES file (IES)	PERFORMANCE CLASS AREA FLOOD 6A IES

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.