

PRODUCT DATASHEET

BULLET FLOOD S030 UNH D 8 SC2 BZ

BULLET FLOOD DUAL SELECTABLE | Bullet floodlight with selectable CCTs, wattages, and adjustable beam angles



Areas of application

- Landscape lighting
- Billboard and signage lighting
- Flagpole illumination
- Residential patios or yards
- Accent lighting

Product features

- FLEX OPTICS: 15, 25, or 40° beam angle lenses included in the box
- Selectable CCT: 3000/4000/5000K
- Selectable wattage and lumens: 10/20/30W | 1400/2800/4200lm
- Up to 140 LPW
- IP66 and IK08
- DLC Premium Listing assures high energy efficiency
- Product is qualified for utility rebates

TECHNICAL DATA

Additional product data

Ordering Abbreviation	BULLTFL2A/S030UNHD8SC2/BZ
Abbrev. With Packaging Info.	BULLTFL2AS030UNHD8SC2BZ 4/CS 1/SKU
SKU UPC	0046135631948
NAED	63194
Family Brand Name	PERFORMANCE CLASS™
General Description	BULLET FLOOD 2A, SELECTABLE 10.5W/20W/30W, 120-347V, 0-10V DIM, CCT SELECTABLE 3000K/4000K/5000K, BRONZE
Warranty	5 years

Electrical data

Nominal Wattage	30.00/20.00/10.50 W
Nominal voltage	120.00...347.00 V
Power factor	≥ 0.90
Total Harmonic Distortion	< 20 %

Photometrical data

Lumens	4200/2800/1400 lm
Efficacy	140 lm/W
Color Temperature/CCT	3000/4000/5000 K
Color Rendering Index (CRI)	80
Luminaire Type	Flood light

Dimensions & Weight

Diameter	6.1 in
Length	6.6 in
Product weight	5 lb

Materials & Colors

Luminaire Finish	Bronze
Housing color	Bronze
Housing	Aluminum
Mercury content	0.0 mg

Application & Mounting

Ambient temperature range	-40...+40 °C
Maximum Operating Temperature	104 °F
Minimum Operating Temperature	-40 °F
Dimming	Yes

Type of Dimming	0-10V
Mounting	Surface
Indoor/Outdoor	Outdoor
Replaceable light source	No
Primary Lamp Type	SMD

Lifespan

Average Rated Life (hr)	100000
-------------------------	--------

Logistical data

SKU Qty	1
Case Qty	4
Case Length (in)	14.095
Case Width (in)	7.323
Case Depth (in)	15.748
Case Cube (ft)	0.941
Case Weight (lbs)	21.649
SKU UPC	0046135631948
Pallet Qty	180

Certificates & Standards

Certification Listing	RoHS / FCC / cULus
Replaceable light source (EPREL)	Not replaceable

Optional accessories

Product image	Product name	UPC
	BULLET FLOOD 2A LARGE VISOR BL	OS63225
	BULLET FLOOD 2A LARGE VISOR GR	OS63226
	BULLET FLOOD 2A LARGE VISOR BZ	OS60687
	TENON ADAPTER 1A BL	OS61169

Product image	Product name	UPC
	TENON ADAPTER 1A GR	OS61170
	TENON ADAPTER 1A BZ	OS60688
	GARDEN STAKE 1A	OS60689

EQUIPMENT / ACCESSORIES

– ½" IPS knuckle

DOWNLOAD DATA

Spec Sheets and Product Documents		Document name
	Installation Guide	INSTALLATION GUIDE BULLET FLOODLIGHT
	Product Family Spec Sheet	BULLET FLOOD DUAL SELECTABLE
Photometric and lighting design files		Document name
	IES file (IES)	BULLET FLOOD 2A IES

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.