

PRODUCT DATASHEET

DULUX S/E 9W 827

SYLVANIA DULUX® S-E Compact Fluorescent Lamps | 4-pin CFL lamps for electronic ballasts with compact 1/2 inch tube design



Areas of application

- Exit signs
- Showcase and outdoor lighting
- Task and down lights
- Wall sconces
- Recessed and surface ceiling fixtures





Product features

- Dimmable compact fluorescent lamps
- Operates on various ballast systems – Flicker-free start on electronic ballasts
- Less power consumption than incandescent lamps with comparable light output
- Long 20,000 hour average rated life
- Reduces relamping requirements and related costs
- Rare earth tri-phosphor with 82 CRI
- High luminous efficacy
- Static color temperature

TECHNICAL DATA

Additional product data

Base type	2G7
Mercury content	1.3 mg
Ordering Abbreviation	CF9DS/E/827
Abbrev. With Packaging Info.	CF9DSE827 50/CS 1/SKU
SKU UPC	0046135203138
NAED	20313
Family Brand Name	Dulux® S/E
General Description	DULUX 9W single compact fluorescent lamp with 4-pin base, 2700K color temperature, 82 CRI, for use with electronic and dimming ballasts

Electrical data

Nominal Wattage	9.00 W
Nominal voltage	48.00 V

Photometrical data

Lumens	580 lm
Color Temperature/CCT	2700 K
Color Rendering Index (CRI)	82
Light color	827
Rated LLMF at 2,000 h	0.85
Rated LLMF at 4,000 h	0.78
Rated LLMF at 6,000 h	0.76
Rated LLMF at 8,000 h	0.76
Rated LLMF at 12,000 h	0.79
Rated LLMF at 16,000 h	0.78
Rated LLMF at 20,000 h	0.76
Rated lamp efficacy (standard co.)	69 lm/W

Dimensions & Weight

Overall length	145.03 mm
Diameter	1.5 in
Maximum diameter	12 mm
Product weight	0.06 lb

Materials & Colors

Lamp Finish	Coated
Bulb shape	S (T4)

Application & Mounting

Dimming	Yes
---------	-----

Temperatures & operating conditions

Rated ambient temp.w.max.luminous	25.0 °C
-----------------------------------	---------

Lifespan

Rated lamp survival factor at 2,000 h	0.99
Rated lamp survival factor at 4,000 h	0.99
Rated lamp survival factor at 6,000 h	0.99
Rated lamp survival factor at 8,000 h	0.85
Rated lamp survival factor at 12,000 h	0.95
Rated lamp survival factor at 16,000	0.81
Rated lamp survival factor at 20,000 h	0.50
Operation mode LLMF/LSF	50 Hz
Average Rated Life (hr)	20000

Capabilities

Suitable for indoor	Yes
Dimming	Yes

Certificates & Standards

Energy efficiency class	A
Energy consumption	9.57 kWh/1000h
Certification Listing	RoHS

Logistical data

SKU Qty	1
Case Qty	50
Case Length (in)	9.449
Case Width (in)	8.071
Case Depth (in)	7.047
Case Cube (ft)	0.311
Case Weight (lbs)	4.332
SKU UPC	0046135203138

Pallet Qty	8,400
------------	-------

Safety advice

- Minimum starting temperature depends on ballast used.
- May be operated on electronic ballasts, dimming ballasts and preheat magnetic ballasts with external starter switch.
- Equipment manufacturers are advised to consult the relevant ANSI and IEC standards for the maximum allowable dimensions and temperature to insure compatibility with similar products.
- Contains Mercury – Dispose of according to Local, State or Federal laws

DOWNLOAD DATA

Spec Sheets and Product Documents		Document name
	Product Family Spec Sheet	DULUX S/E Compact Fluorescent Lamps

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.