

PRODUCT DATASHEET

EXTRUDED VAPOR S066 UNV D 8 SC7 48 UGR E

VAPOR TIGHT EXTRUDED 1A | Extruded Vapor Tight with selectable CCT and wattage



Areas of application

- Manufacturing facilities
- Agricultural buildings
- Warehouses
- Canopies and loading docks
- Parking garages

Product features

- Selectable wattage and lumen output
- Selectable CCTs: 3500/4000/5000K
- IP66 wet rated
- Up to 115 LPW
- Optional integrated motion/daylight sensor and/or emergency battery backup
- NSF Splash zone
- DLC
- Stainless steel clips and mounting brackets
- 120-277V

TECHNICAL DATA

Additional product data

Ordering Abbreviation	EXVAP1A/S066UNVD8SC7/48U/GR/E
Abbrev. With Packaging Info.	EXVAP1AS066UNVD8SC748UGRE 8/CS 1/SKU
SKU UPC	0046135624353
NAED	62435
General Description	ValueLED Extruded Vapor Tight, 50/55/66W Selectable wattage, 120-277V, 0-10V Dimming, 3500/4000/5000K Selectable, 4 feet long, Gray Polycarbonate Body with Frosted Polycarbonate Lens, internal emergency back-up battery
Warranty	5 years

Electrical data

Nominal Wattage	50.00/55.00/66.00 W
Nominal voltage	120.00...277.00 V
Power factor	≥0.90
Total Harmonic Distortion	< 20 %

Photometrical data

Lumens	5750 lm
Efficacy	115 lm/W
Color Temperature/CCT	3500/4000/5000 K
Color Rendering Index (CRI)	> 80
Luminaire Type	Vapor-tight

Dimensions & Weight

Length	47.99 in
Width	2.6 in
Height	2.4 in
Product weight	5.25 lb

Materials & Colors

Luminaire Finish	Gray
Housing color	Gray
Housing	Polycarbonate (PC)

Application & Mounting

Ambient temperature range	0...40 °C
Maximum Operating Temperature	104 °F
Minimum Operating Temperature	0 °C

Dimming	Yes
Type of Dimming	0-10V
Mounting	Surface
Indoor/Outdoor	Indoor
Replaceable light source	No

Lifespan

Average Rated Life (hr)	75000
-------------------------	-------

BATTERY

Lithium Ion Battery	Li ion battery
Battery size [GMS]	Others

Logistical data

SKU Qty	1
Case Qty	8
Case Length (in)	51.024
Case Width (in)	11.339
Case Depth (in)	6.378
Case Cube (ft)	2.135
Case Weight (lbs)	48.458
SKU UPC	0046135624353
Pallet Qty	168

Certificates & Standards

Certification Listing	RoHS / FCC / cULus
Replaceable light source (EPREL)	Not replaceable

Optional accessories

Product image	Product name	UPC
	Standalone Commissioning Remote REMOTE CONTROL	OS65305
	Standalone Commissioning Remote REMOTE CONTROL	OS60105

EQUIPMENT / ACCESSORIES

– Stainless Steel mounting brackets and V-hooks

DOWNLOAD DATA

Spec Sheets and Product Documents		Document name
	Installation Guide	Extruded Vapor Tight Installation Guide
	Product Family Spec Sheet	ValueLED Dual Selectable Extruded Vapor Tight 1A

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.