

PRODUCT DATASHEET

L 4W CW

SYLVANIA Preheat T5 | Miniature preheat T5 lamps for magnetic ballast systems with starter use



Product features

- 6 inch lamps available in Cool White phosphor
- 9 inch lamps available in Cool White phosphor
- 12 inch lamps available in Soft (Warm) White and Cool White phosphor
- 21 inch lamps available in Soft (Warm) White and Cool White phosphor



TECHNICAL DATA

Additional product data

Base type	G5
Mercury content	5.0 mg
Design / version	Basic T5 short tubular, G5 base
Ordering Abbreviation	F4T5/CW
Abbrev. With Packaging Info.	F4T5CW 25/CS 1/SKU
SKU UPC	0046135213649
NAED	21364
General Description	4W, preheat fluorescent lamp, Cool White phosphor, 4100K color temperature, 60 CRI. 6000 Avg rated life at 3 hrs/start

Electrical data

Nominal Wattage	4.00 W
Rated lamp efficacy (HF data 25 °C)	Under clarification by authority and standardization body

Photometrical data

Lumens	140 lm
Efficacy	31
Color Temperature/CCT	4100 K
Color Rendering Index (CRI)	60
Light color	641
Rated lamp efficacy (HF data 25 °C)	Under clarification by authority and standardization body

Dimensions & Weight

Overall length	135.90 mm
Diameter	0.63 in
Tube diameter	16 mm
Product weight	0.03 lb

Materials & Colors

Lamp Finish	Coated
Bulb shape	T5

Application & Mounting

Starting Method	PREHEAT
-----------------	---------

Lifespan

Service life	4500 h
Average Rated Life (hr)	6000

Logistical data

SKU Qty	1
Case Qty	25
Case Length (in)	6.496
Case Width (in)	4.055
Case Depth (in)	4.291
Case Cube (ft)	0.065
Case Weight (lbs)	1.212
SKU UPC	0046135213649
Pallet Qty	17,250

Safety advice

- Starter required for operation.
- Operate on magnetic ballasts.
- Contains Mercury – Dispose of according to Local, State or Federal laws

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.