

PRODUCT DATASHEET

L 6W CW

SYLVANIA Preheat T5 | Miniature preheat T5 lamps for magnetic ballast systems with starter use



Product features

- 6 inch lamps available in Cool White phosphor
- 9 inch lamps available in Cool White phosphor
- 12 inch lamps available in Soft (Warm) White and Cool White phosphor
- 21 inch lamps available in Soft (Warm) White and Cool White phosphor



TECHNICAL DATA

Additional product data

Base type	G5
Mercury content	2.6 mg
Design / version	Basic T5 short tubular, G5 base
Ordering Abbreviation	F6T5/CW
Abbrev. With Packaging Info.	F6T5CW 25/CS 1/SKU
SKU UPC	0046135213656
NAED	21365
General Description	6W, preheat fluorescent lamp, Cool White phosphor, 4100K color temperature, 60 CRI. 7500 Avg rated life at 3 hrs/start

Electrical data

Nominal Wattage	6.00 W
Rated lamp efficacy (HF data 25 °C)	Under clarification by authority and standardization body

Photometrical data

Lumens	270 lm
Efficacy	45
Color Temperature/CCT	4100 K
Color Rendering Index (CRI)	60
Light color	641
Rated lamp efficacy (HF data 25 °C)	Under clarification by authority and standardization body

Dimensions & Weight

Overall length	212.10 mm
Diameter	0.63 in
Tube diameter	16 mm
Product weight	0.05 lb

Materials & Colors

Lamp Finish	Coated
Bulb shape	T5

Application & Mounting

Starting Method	PREHEAT
-----------------	---------

Lifespan

Service life	4500 h
Average Rated Life (hr)	7500

Logistical data

SKU Qty	1
Case Qty	25
Case Length (in)	9.724
Case Width (in)	4.055
Case Depth (in)	4.291
Case Cube (ft)	0.098
Case Weight (lbs)	1.624
SKU UPC	0046135213656
Pallet Qty	11,250

Safety advice

- Starter required for operation.
- Operate on magnetic ballasts.
- Contains Mercury – Dispose of according to Local, State or Federal laws

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.