

PRODUCT DATASHEET

ULTRA LED™ HO PAR Lamps PAR20 11W HO 3000K NFL 25 1PK

SYLVANIA High Output PAR Lamps | High lumen package LED PAR lamps



Areas of application

- Downlights, pendant fixtures, table lamps, wall sconces
- Healthcare, hospitality, residential, retail
- Grocery
- Houses of worship

Product features

- High CBCP performance
- Up to 100 LPW
- Outstanding color uniformity and beam quality utilizing COB technology
- 277V option allows compatible replacement for HID lamps
- UL1993 & UL1598C tested
- Great replacement options for high power halogen and HID lamp
- 25,000 hours lifetime (L70)
- Dimmable down to 10 %

TECHNICAL DATA

Additional product data

Base type	E26
Mercury content	0.0 mg
Ordering Abbreviation	LED11PAR20HO930NFL25UNV
Abbrev. With Packaging Info.	LED11PAR20HO930NFL25UNV 6/CS 1/SKU
SKU UPC	0046135423499
NAED	42349
General Description	LED PAR20 HO, 11W, 90CRI, 1000 Lumen, 3000K, 25000 life, 120-277V

Electrical data

Nominal Wattage	11.00 W
Nominal voltage	120.00...277.00 V
Claimed Equivalent Lamp Pwr	75 W

Photometrical data

Lumens	1000 lm
Efficacy	91
Color Temperature/CCT	3000 K
Color Rendering Index (CRI)	90
Light color	930

Dimensions & Weight

Overall length	86.70 mm
Diameter	2.57 in
Product weight	0.14 lb

Materials & Colors

Lamp Finish	White
Bulb shape	PAR20
Bulb Glass Type	PLASTICS

Application & Mounting

Dimming	No
---------	----

Temperatures & operating conditions

Ambient temperature range	-20...40 °C
---------------------------	-------------

Lifespan

Average Rated Life (hr)	25000
-------------------------	-------

Capabilities

Dimming	No
---------	----

Certificates & Standards

Certification Listing	RoHS / FCC / cETLus / CEC / NRCAN
-----------------------	-----------------------------------

Logistical data

SKU Qty	1
Case Qty	6
Case Length (in)	8.661
Case Width (in)	5.591
Case Depth (in)	4.488
Case Cube (ft)	0.126
Case Weight (lbs)	1.281
SKU UPC	0046135423499
Pallet Qty	2,220

Safety advice

- Use in fixtures that support a half-pound lamp.
- -4°F to +104°F (-20°C to +40°C)
- Not for use with emergency light fixtures or exit lights.

DOWNLOAD DATA

Spec Sheets and Product Documents		Document name
	Product Family Spec Sheet	ULTRA LED HO PAR Lamps

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.