

PRODUCT DATASHEET

ULTRA LED™ Glass PAR Lamps 11W

PAR30LN DIM 2700K NFL 25 1PK

SYLVANIA ULTRA LED™ PAR Lamps | ULTRA LED PAR Lamps



Areas of application

- Downlights, pendant fixtures, table lamps, wall sconces
- Healthcare, hospitality, residential, retail

Product features

- Longer life than traditional halogen lamps
- Glass body with full optics – similar to halogen PAR lamps
- CRI of 80 ensures good color definition
- RoHS compliant, mercury and lead free
- Dimmable down to 10 %
- Wet rated

TECHNICAL DATA

Additional product data

Base type	E26
Mercury content	0.0 mg
Ordering Abbreviation	LED11PAR30LNDIM827NFL2513YGLWR
Abbrev. With Packaging Info.	LED11PAR30LNDIM827NFL2513YGLWR 6CS 1SKU
SKU UPC	0046135414671
NAED	41467
Family Brand Name	ULTRA GLASS
General Description	LED PAR30LN, 11W, Dimmable, 82CRI, 827 Lumen, 2700K, 15000 life

Electrical data

Nominal Wattage	11.00 W
Nominal voltage	120.00 V
Claimed Equivalent Lamp Pwr	75 W
Centerbeam Candlepower (cp)	4,470 cd

Photometrical data

Lumens	850 lm
Efficacy	77
Color Temperature/CCT	2700 K
Color Rendering Index (CRI)	82
Light color	827

Dimensions & Weight

Overall length	113.00 mm
Diameter	3.74 in
Product weight	0.51 lb

Materials & Colors

Bulb shape	PAR30LN
Bulb Glass Type	HARDGLASS

Application & Mounting

Dimming	Yes
---------	-----

Lifespan

Average Rated Life (hr)	15000
-------------------------	-------

Capabilities

Dimming	Yes
---------	-----

Certificates & Standards

Certification Listing	RoHS / FTC / FCC
-----------------------	------------------

Logistical data

SKU Qty	1
Case Qty	6
Case Length (in)	12.437
Case Width (in)	9.375
Case Depth (in)	7.375
Case Cube (ft)	0.498
Case Weight (lbs)	4.992
SKU UPC	0046135414671
Pallet Qty	540

Safety advice

- Suitable for wet locations.
- -4°F to +113°F (-20°C to +45°C)
- Not for use with emergency light fixtures or exit lights.
- Approved for use in enclosed fixtures.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.