

PRODUCT DATASHEET

Contractor Series 5CCT Selectable A19 14W 5CCT 10YV 4PK

SYLVANIA Contractor Series 5CCT Selectable A19/A21 Lamps | Contractor Series A19/A21 with 80+ CRI and flexible 5CCT selectable



Areas of application

- Downlights, pendant fixtures, table lamps, wall sconces
- Healthcare, hospitality, residential, retail
- Vanity fixtures
- Indoor and outdoor
- Decorative or accent lighting

Product features

- Selectable CCTs: 2700/3000/3500/4000/5000K
- Toggle switch located on the lamp to change between CCTs in the field
- Up to 110 LPW
- Environmentally preferred products: RoHS compliant and contain no mercury, lead or other hazardous materials
- 11,000 hours lifetime (L70)

TECHNICAL DATA

Additional product data

Base type	E26
Mercury content	0.0 mg
Ordering Abbreviation	LED14A19F8SC310YVRP4
Abbrev. With Packaging Info.	LED14A19F8SC310YVRP4 16/CS 4/SKU
SKU UPC	0046135424847
NAED	42484
Family Brand Name	10YV
General Description	LED A1910YR 5CCT Selectable, 14W, 80 CRI, 1500 LUMEN,2700K/3000K/3500K/4000K/5000K, 11,000 HOUR LIFE, MEDIUM BASE FrostedFINISH
Warranty	3 years

Electrical data

Nominal Wattage	14.00 W
Nominal voltage	120.00 V
Claimed Equivalent Lamp Pwr	100 W

Photometrical data

Lumens	1500 lm
Efficacy	107
Color Temperature/CCT	2700/3000/3500/4000/5000 K
Color Rendering Index (CRI)	80
Light color	827

Dimensions & Weight

Overall length	112.00 mm
Diameter	2.36 in
Product weight	0.09 lb

Materials & Colors

Lamp Finish	Frosted
Bulb shape	A19
Bulb Glass Type	PLASTICS

Application & Mounting

Dimming	No
---------	----

Temperatures & operating conditions

Ambient temperature range	-20...40 °C
---------------------------	-------------

Lifespan

Average Rated Life (hr)	11000
-------------------------	-------

Capabilities

Dimming	No
---------	----

Certificates & Standards

Certification Listing	RoHS
-----------------------	------

Logistical data

SKU Qty	4
Case Qty	16
Case Length (in)	12.244
Case Width (in)	5.354
Case Depth (in)	6.417
Case Cube (ft)	0.243
Case Weight (lbs)	2.214
SKU UPC	0046135424847
Pallet Qty	3,024

Safety advice

- -4°F to +113°F (-20°C to +45°C)
- Suitable for damp locations.
- Non-dimmable.

DOWNLOAD DATA

Spec Sheets and Product Documents		Document name
	Product Family Spec Sheet	LED612 SYLVANIA LAMPS Contractor Series 5CCT Selectable LED A19

	Product Family Spec Sheet	LED620 SYLVANIA LAMPS Contractor Series 5CCT Selectable LED family
--	---------------------------	--

Photometric and lighting design files		Document name
	IES file (IES)	Contractor Series Family 5CCT Aline IES FILES

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

