

PRODUCT DATASHEET

LED TT5 DL FG BF 17W 830

SYLVANIA LEDlescent™ DULUX® L LED TT5 Ballast-Free Lamps (UL TYPE B) | Ballast-free DULUX L TT5 lamps deliver long life and energy savings with direct wire



Areas of application

- General illumination
- Hospitality
- Offices
- Retail
- Wall washing

Product features

- Energy saving replacement for fluorescent FT40DL/25W & FT40DL/28W lamps
- Installed directly on 120-277V; no ballast required
- CCT: 3000K
- Lifetime (L70): up to 50,000 h
- Suitable for open and enclosed fixtures
- No warm-up time, instant-on with full light output and stable lamp-to-lamp color
- For use with shunted and non-shunted sockets, therefore no socket change is needed
- Maximize energy savings with occupancy sensors
- 2G11 four pin base
- Optimized glass optical design to mimic traditional fluorescent TT5 lamp
- 5-year limited lamp warranty (24/7 operation)
- Mercury-free and RoHS compliant



TECHNICAL DATA

Additional product data

Base type	2G11
Ordering Abbreviation	LED17TT5/DL/FG/830/BF
Abbrev. With Packaging Info.	LED17TT5DLFG830BF 10/CS 1/SKU
SKU UPC	0046135403316
NAED	40331
Family Brand Name	LEDlescent™
General Description	LEDlescent™ ballast-free DULUX L TT5, 17W 83 CRI, 2100 Lumen, 120-277V, 3000K, 50000 life
Warranty	5 years

Electrical data

Nominal Wattage	17.00 W
Nominal voltage	120.00...277.00 V
Claimed Equivalent Lamp Pwr	40 W

Photometrical data

Lumens	2100 lm
Efficacy	124
Color Temperature/CCT	3000 K
Color Rendering Index (CRI)	83
Light color	830

Dimensions & Weight

Overall length	570.00 mm
Diameter	0.79 in
Product weight	0.66 lb

Materials & Colors

Lamp Finish	Frosted
Bulb shape	T5
Bulb Glass Type	SOFT GLASS

Application & Mounting

Dimming	No
---------	----

Lifespan

Average Rated Life (hr)	50000
-------------------------	-------

Capabilities

Dimming	No
---------	----

Certificates & Standards

Certification Listing	RoHS / CSA / FCC / cULus
-----------------------	--------------------------

Logistical data

SKU Qty	1
Case Qty	10
Case Length (in)	23.625
Case Width (in)	6.313
Case Depth (in)	4.375
Case Cube (ft)	0.378
Case Weight (lbs)	8.274
SKU UPC	0046135403316
Pallet Qty	1,200

Safety advice

- Double ended platform where lamp is wired end-to-end preventing nonpassive failure of a fluorescent lamp should it be inadvertently installed in the fixture.
- All installation, inspection, and maintenance of lighting fixtures should be done with the power to the fixture turned off.
- Lamps should be installed and operated in compliance with the National Electrical Code (NEC), Underwriters Laboratories Inc. (UL) requirements, and all applicable codes and regulations.
- Ensure lamp holders/sockets are in good operating condition before installation.
- Not for emergency lighting.
- Not to be used with dimmers.
- Do not use LEDlescent DULUX L LED TT5 lamps with external LED drivers or ballasts.
- To prevent wiring damage or abrasion, do not expose wiring to edges of sheet metal or other sharp objects.
- Do not make or alter any open holes in an enclosure of wiring or electrical components during kit installation.
- Please read and comply with all instructions before attempting inspection, service or installation.
- Suitable for dry and damp locations (cannot come in direct contact with water).

DOWNLOAD DATA

Spec Sheets and Product Documents	Document name
 Installation Guide	LEDlescent DULUX L LED TT5 Installation Manual

Spec Sheets and Product Documents		Document name
	Product Family Spec Sheet	LEDiescent LED TT5 Ballast Free Lamp

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.