

PRODUCT DATASHEET

LED PB BF 3.5W 2G7 H 830

SYLVANIA DULUX® LEDlescent™ Ultra Thin LED Pin Base Lamps (UL TYPE B) | Ultra Thin LEDlescent pin base lamps wire direct to line voltage for CFL retrofits



Areas of application

- Downlights
- Sconces
- Task Lighting
- Recessed ceiling fixtures

Product features

- LED replacement for conventional compact fluorescent lamps for use wired directly to line voltage
- Static color temperature
- Horizontal orientation lamps have rotatable bases to adjust direction of light output
- CRI ≥ 80
- Frosted plastic finish
- Energy savings up to 68 %
- Ultra thin beam angle 160°, and light emitting area 320°
- 2-pin lamps can be used in sockets intended for 4-pin lamps as the ballast is bypassed
- Compatible with LEDVANCE Emergency Battery Backup (75740)
- 5-year limited lamp warranty (24/7 operation)
- Mercury-free and RoHS compliant
- Power factor: > 0.9

TECHNICAL DATA

Additional product data

Base type	2G7
Mercury content	0.0 mg
Ordering Abbreviation	LED3.5PB2G7H830BF
Abbrev. With Packaging Info.	LED3.5PB2G7H830BF 24/CS 1/SKU
SKU UPC	0046135420696
NAED	42069
Family Brand Name	SYLVANIA LEDlescent™ DULUX®
General Description	DULUX® LEDlescent™ LED Pin Base, 3.5W, 120-277V, 80 CRI, 340 lumens, 3000K, 50,000 hours life, Horizontal Orientation, Ultra thin, 2G7 base, ballast-free
Warranty	5 years

Electrical data

Nominal Wattage	3.50 W
Nominal voltage	120.00...277.00 V
Claimed Equivalent Lamp Pwr	7 W

Photometrical data

Lumens	340 lm
Efficacy	97
Color Temperature/CCT	3000 K
Color Rendering Index (CRI)	82
Light color	830

Dimensions & Weight

Overall length	114.30 mm
Diameter	1.5 in
Product weight	0.06 lb

Materials & Colors

Lamp Finish	Frosted
Bulb shape	T4
Bulb Glass Type	PLASTICS

Application & Mounting

Dimming	No
---------	----

Lifespan

Average Rated Life (hr)	50000
-------------------------	-------

Capabilities

Dimming	No
---------	----

Certificates & Standards

Certification Listing	RoHS / FCC / cULus
-----------------------	--------------------

Logistical data

SKU Qty	1
Case Qty	24
Case Length (in)	6.024
Case Width (in)	5.945
Case Depth (in)	6.772
Case Cube (ft)	0.140
Case Weight (lbs)	2.676
SKU UPC	0046135420696
Pallet Qty	9,408

Optional accessories

Product image	Product name	UPC
	EMBB 2A 21W UNV DIM DC	OS75740

Safety advice

- Refer to the installation manual included inside the packaging.
- Ultra thin lamps can be used in enclosed (lens or diffuser) luminaire.
- Not approved for use in vapor tight or sealed luminaire.
- Ambient Operating Range: -4°F to +104°F (-20°C to +40°C)
- THD < 20 %
- Check Pin Based Socket Guide

DOWNLOAD DATA

Spec Sheets and Product Documents		Document name
	Product Family Spec Sheet	DULUX® LED Pin Base Lamps

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.