

PRODUCT DATASHEET

LED PB AB 5.5W GX23 H 827

SYLVANIA DULUX® DUALescent™ Ultra Thin LED Pin Base Lamps (UL TYPE A+B) | Ultra Thin DUALescent pin base lamps offer ballast or line voltage use for CFL retrofits



Areas of application

- Downlights
- Sconces
- Task Lighting
- Recessed ceiling fixtures

Product features

- LED replacement for conventional compact fluorescent lamps for use with existing ballast or wired directly to line voltage
- Energy savings up to 68 %
- Horizontal orientation lamps have rotatable bases to adjust direction of light output
- As Type A, lamps operate on magnetic ballasts
- CRI ≥ 80
- 2-pin lamps can be used in sockets intended for 4-pin lamps as the ballast is bypassed
- Ultra thin beam angle 160°, and light emitting area 320°
- When used as Type B, compatible with LEDVANCE Emergency Battery Backup (75740)
- 5-year limited lamp warranty (24/7 operation)
- Mercury-free and RoHS compliant
- Power factor: > 0.9

TECHNICAL DATA

Additional product data

Base type	GX23
Mercury content	0.0 mg
Ordering Abbreviation	LED5.5PBGX23H827AB
Abbrev. With Packaging Info.	LED5.5PBGX23H827AB 24/CS 1/SKU
SKU UPC	0046135420641
NAED	42064
Family Brand Name	SYLVANIA DULUX® DUALescent™
General Description	DULUX® DUALescent™ Pin Base, 5.5W, 80 CRI, 550 lumens, 2700K, 50,000 hours life, Horizontal Orientation, GX23 base, Magnetic Ballast-compatible and Ballast-Free operation
Warranty	5 years

Electrical data

Nominal Wattage	5.50 W
Nominal voltage	120.00...277.00 V
Claimed Equivalent Lamp Pwr	13 W

Photometrical data

Lumens	550 lm
Efficacy	100
Color Temperature/CCT	2700 K
Color Rendering Index (CRI)	82
Light color	827

Dimensions & Weight

Overall length	180.34 mm
Diameter	1.5 in
Product weight	0.08 lb

Materials & Colors

Lamp Finish	Frosted
Bulb shape	T4
Bulb Glass Type	PLASTICS

Application & Mounting

Dimming	No
---------	----

Lifespan

Average Rated Life (hr)	50000
-------------------------	-------

Capabilities

Dimming	No
---------	----

Certificates & Standards

Certification Listing	RoHS / FTC / FCC / cULus
-----------------------	--------------------------

Logistical data

SKU Qty	1
Case Qty	24
Case Length (in)	6.024
Case Width (in)	5.945
Case Depth (in)	8.071
Case Cube (ft)	0.167
Case Weight (lbs)	4.242
SKU UPC	0046135420641
Pallet Qty	5,760

Optional accessories

Product image	Product name	UPC
	EMBB 2A 21W UNV DIM DC	OS75740

Safety advice

- For proper use and warranty coverage, installer must consult the ballast compatibility list to ensure that the lamp and ballast combination is deemed compatible and will operate as intended.
- Refer to the installation manual included inside the packaging.
- Can be used in enclosed (lens or diffuser) luminaire.
- Not approved for use in vapor tight or sealed luminaire.
- Ambient Operating Range: -4°F to +104°F (-20°C to +40°C)
- THD < 20 %
- Check Pin Based Socket Guide

DOWNLOAD DATA

Spec Sheets and Product Documents		Document name
	Installation Guide	Install Guide DULUX DUALescent Pin Base 3.5W
	Product Family Spec Sheet	DULUX® LED Pin Base Lamps

Spec Sheets and Product Documents	Document name
-----------------------------------	---------------

Photometric and lighting design files	Document name
---------------------------------------	---------------



IES file (IES)

IES File for 42072, 42064_LED5.5PB2GX7H827BF and LED5.5PBGX23H827AB

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.