

PRODUCT DATASHEET

Contractor Series 5CCT Selectable A19 6W 5CCT 10YV 2PK

SYLVANIA Contractor Series 5CCT Selectable A19/A21 Lamps | Contractor Series A19/A21 with 80+ CRI and flexible 5CCT selectable



Areas of application

- Downlights, pendant fixtures, table lamps, wall sconces
- Healthcare, hospitality, residential, retail
- Vanity fixtures
- Indoor and outdoor
- Decorative or accent lighting

Product features

- Selectable CCTs: 2700/3000/3500/4000/5000K
- Toggle switch located on the lamp to change between CCTs in the field
- Up to 110 LPW
- Environmentally preferred products: RoHS compliant and contain no mercury, lead or other hazardous materials
- 11,000 hours lifetime (L70)

TECHNICAL DATA

Additional product data

Base type	E26
Mercury content	0.0 mg
Ordering Abbreviation	LED6A19F8SC310YVRP2
Abbrev. With Packaging Info.	LED6A19F8SC310YVRP2 8/CS 2/SKU
SKU UPC	0046135424786
NAED	42478
Family Brand Name	10YV
General Description	LED A19 10YR 5CCT Selectable, 6W, 80 CRI, 450 LUMEN,2700K/3000K/3500K/4000K/5000K, 11,000 HOUR LIFE, MEDIUM BASE FrostedFINISH
Warranty	3 years

Electrical data

Nominal Wattage	6.00 W
Nominal voltage	120.00 V
Claimed Equivalent Lamp Pwr	40 W

Photometrical data

Lumens	450 lm
Efficacy	75
Color Temperature/CCT	2700/3000/3500/4000/5000 K
Color Rendering Index (CRI)	80
Light color	827

Dimensions & Weight

Overall length	107.00 mm
Diameter	2.36 in
Product weight	0.06 lb

Materials & Colors

Lamp Finish	Frosted
Bulb shape	A19
Bulb Glass Type	PLASTICS

Application & Mounting

Dimming	No
---------	----

Temperatures & operating conditions

Ambient temperature range	-20...40 °C
---------------------------	-------------

Lifespan

Average Rated Life (hr)	11000
-------------------------	-------

Capabilities

Dimming	No
---------	----

Certificates & Standards

Certification Listing	RoHS
-----------------------	------

Logistical data

SKU Qty	2
Case Qty	8
Case Length (in)	10.669
Case Width (in)	4.724
Case Depth (in)	5.118
Case Cube (ft)	0.149
Case Weight (lbs)	1.003
SKU UPC	0046135424786
Pallet Qty	2,736

Safety advice

- -4°F to +113°F (-20°C to +45°C)
- Suitable for damp locations.
- Non-dimmable.

DOWNLOAD DATA

Spec Sheets and Product Documents		Document name
	Product Family Spec Sheet	LED612 SYLVANIA LAMPS Contractor Series 5CCT Selectable LED A19
	Product Family Spec Sheet	LED620 SYLVANIA LAMPS Contractor Series 5CCT Selectable LED family

Photometric and lighting design files		Document name
	IES file (IES)	Contractor Series Family 5CCT Aline IES FILES

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

