

PRODUCT DATASHEET

LEDMD SLIM SELECT 2A 6" 5CCT 1200LM 120V 4PK

SYLVANIA SLIM MICRODISK CCT SELECTABLE | Slim Microdisk Downlight with selectable 5 CCT

Areas of application

- Residential
- New installations or retrofit of existing installations



Product features

- Canless recessed flush mount downlight with remote driver design for easy installation
- 1/2" height allows installation directly under joists
- Selectable CCTs: 2700/3000/3500/4000/5000K
- Flicker-free dimming, Phase-cut
- Up to 80 LPW
- Energy savings up to 92 %
- Available in 120VAC
- Beam Angle of 112° FWHM
- 90 CRI, R9>50

TECHNICAL DATA

Additional product data

Ordering Abbreviation	LEDMD6R2A1200ST9SC3
Abbrev. With Packaging Info.	LEDMD6R2A1200ST9SC3 16/CS 4/SKU
SKU UPC	0046135614064
NAED	61406
Family Brand Name	Slim Microdisk
General Description	Slim MicroDisk, 6", 1200 lumens, 90 CRI, 5 CCT selectable, 16W, >0.9 PF, 120V, phase-cut dimmable, 4 per pack
Warranty	5 years

Electrical data

Nominal Wattage	16.00 W
Nominal voltage	120.00 V
Power factor	≥0.90
Total Harmonic Distortion	< 20 %

Photometrical data

Lumens	1200 lm
Efficacy	75 lm/W
Color Temperature/CCT	2700/3000/3500/4000/5000 K
Color Rendering Index (CRI)	90
Luminaire Type	Downlight

Dimensions & Weight

Diameter	6.8 in
Height	0.9 in
Product weight	0.67 lb

Materials & Colors

Luminaire Finish	White
Housing color	White
Housing	Plastic

Application & Mounting

Dimming	Yes
Type of Dimming	PHASE CUT
Mounting	Recessed
Replaceable light source	No
Primary Lamp Type	SMD

Lifespan

Average Rated Life (hr)	50000
-------------------------	-------

Logistical data

SKU Qty	4
Case Qty	16
Case Length (in)	14.750
Case Width (in)	7.250
Case Depth (in)	14.875
Case Cube (ft)	0.921
Case Weight (lbs)	13.813
SKU UPC	0046135614064
Pallet Qty	720

Certificates & Standards

Certification Listing	RoHS / FCC / ETL
Replaceable light source (EPREL)	Not replaceable
Energy Star Rated	X

Optional accessories

Product image	Product name	UPC
	MD EXT CABLE 6FT WH	OS60898
	MD EXT CABLE 10FT WH	OS60899
	MD EXT CABLE 20FT WH	OS60900
	SLIM MD FRAME DRYWALL	OS62959
	SLIM MD FRAME T-GRID	OS63743

EQUIPMENT / ACCESSORIES

- Luminaire with interconnected cable to galvanized steel remote driver wiring enclosure via FT6 cable
- 3 Push-on Wire Terminals

Safety advice

- Suitable for indoor, dry, and wet locations.
- IC Rated.
- Not intended for use with emergency light luminaires or exit lights.
- Suitable for use in closets, compliant with NFPA 70, NEC section 410.16 (A)(3) and 410.16 (C)(5).
- For use in housings that can structurally support a lamp weighing one pound.
- Max Ceiling Thickness 0.37" (9.4 mm).

DOWNLOAD DATA

Spec Sheets and Product Documents		Document name
	Product Family Spec Sheet	ValueLED Selectable Slim MICRODISK

Photometric and lighting design files		Document name
	IES file (IES)	IES Files for LEDMD SLIM SELECT 2A

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.