

# PRODUCT DATASHEET

## POST TOP 60W 120-347V D3CCT T2 BL P

POST TOP DUAL SELECTABLE | Post Top with selectable CCT and wattage



### Areas of application

- Parking lots
- Walkways
- General outdoor area lighting

### Product features

- Selectable CCT: 3000/4000/5000K
- IP65-rated housing for long-lasting, weather-resistant performance
- Selectable wattage and lumen outputs
- Offered in Type 2, 3, 4, and 5 distribution options
- Up to 105 LPW
- Optional photocell offers additional energy savings
- CRI >70
- IK08-rated and UV-stabilized polycarbonate lens for durability
- DLC Standard: assures high energy efficient & eligible for utility rebates

## TECHNICAL DATA

### Additional product data

|                              |                                                                                                                          |
|------------------------------|--------------------------------------------------------------------------------------------------------------------------|
| Ordering Abbreviation        | POSTTOP1A/S060UNHD7SC2/T2/BL/P                                                                                           |
| Abbrev. With Packaging Info. | POSTTOP1AS060UNHD7SC2T2BLP 1/CS 1/SKU                                                                                    |
| NAED                         | 63080                                                                                                                    |
| Family Brand Name            | PERFORMANCE                                                                                                              |
| General Description          | Post top, 40/50/60W Selectable, 120-347V, 0-10v Dim, 70 CRI, CCT selectable 3000, 4000, 5000K, Type II, Black, Photocell |
| Warranty                     | 5 years                                                                                                                  |

### Electrical data

|                           |                     |
|---------------------------|---------------------|
| Nominal Wattage           | 60.00/50.00/40.00 W |
| Nominal voltage           | 120.00...347.00 V   |
| Power factor              | ≥0.90               |
| Total Harmonic Distortion | < 20 %              |

### Photometrical data

|                             |                  |
|-----------------------------|------------------|
| Lumens                      | 6300 lm          |
| Efficacy                    | 105 lm/W         |
| Color Temperature/CCT       | 3000/4000/5000 K |
| Color Rendering Index (CRI) | 70               |
| Luminaire Type              | Post top         |

### Dimensions & Weight

|                |          |
|----------------|----------|
| Length         | 19.9 in  |
| Width          | 19.7 in  |
| Height         | 25.3 in  |
| Product weight | 24.25 lb |

### Materials & Colors

|                  |          |
|------------------|----------|
| Luminaire Finish | Black    |
| Housing color    | Black    |
| Housing          | Aluminum |
| Mercury content  | 0.0 mg   |

### Application & Mounting

|                               |              |
|-------------------------------|--------------|
| Ambient temperature range     | -40...+40 °C |
| Maximum Operating Temperature | 104 °F       |
| Minimum Operating Temperature | -40 °F       |
| Dimming                       | Yes          |

|                          |         |
|--------------------------|---------|
| Type of Dimming          | 0-10V   |
| Mounting                 | Surface |
| Indoor/Outdoor           | Outdoor |
| Replaceable light source | No      |
| Primary Lamp Type        | SMD     |

### Lifespan

|                         |       |
|-------------------------|-------|
| Average Rated Life (hr) | 50000 |
|-------------------------|-------|

### Logistical data

|                   |        |
|-------------------|--------|
| Case Qty          | 1      |
| Case Length (in)  | 29.764 |
| Case Width (in)   | 22.677 |
| Case Depth (in)   | 11.260 |
| Case Cube (ft)    | 4.398  |
| Case Weight (lbs) | 28.913 |
| Pallet Qty        | 8      |

### Certificates & Standards

|                       |                    |
|-----------------------|--------------------|
| Certification Listing | RoHS / FCC / cULus |
|-----------------------|--------------------|

### Optional accessories

| Product image                                                                       | Product name                   | UPC     |
|-------------------------------------------------------------------------------------|--------------------------------|---------|
|  | BRACKET 1A POST ADAPTER TEN BZ | OS61171 |
|  | BRACKET 1A POST ADAPTER TEN BL | OS61172 |
|  | BRACKET 1A POST ADAPTER TEN GR | OS61173 |
|  | BRACKET POST TEN ADAPTER WH    | OS62419 |
|  | POLE SQ S 2B MOUNT 4IN BZ      | OS63315 |

| Product image                                                                     | Product name              | UPC     |
|-----------------------------------------------------------------------------------|---------------------------|---------|
|  | POLE SQ S 2B MOUNT 5IN BZ | OS63316 |

DOWNLOAD DATA

| Spec Sheets and Product Documents                                                                          | Document name                                |
|------------------------------------------------------------------------------------------------------------|----------------------------------------------|
|  Product Family Spec Sheet | DUAL SELECTABLE POST TOP LUMINAIRE LEDLUM141 |

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.