

PRODUCT DATASHEET

POST TOP 60W 120-347V D3CCT T2 BZ

POST TOP DUAL SELECTABLE | Post Top with selectable CCT and wattage



Areas of application

- Parking lots
- Walkways
- General outdoor area lighting

Product features

- Selectable CCT: 3000/4000/5000K
- IP65-rated housing for long-lasting, weather-resistant performance
- Selectable wattage and lumen outputs
- Offered in Type 2, 3, 4, and 5 distribution options
- Up to 105 LPW
- Optional photocell offers additional energy savings
- CRI >70
- IK08-rated and UV-stabilized polycarbonate lens for durability
- DLC Standard: assures high energy efficient & eligible for utility rebates

TECHNICAL DATA

Additional product data

Ordering Abbreviation	POSTTOP1A/S060UNHD7SC2/T2/BZ
Abbrev. With Packaging Info.	POSTTOP1AS060UNHD7SC2T2BZ 1/CS 1/SKU
NAED	62620
Family Brand Name	PERFORMANCE
General Description	Post top, 40/50/60W Selectable, 120-347V, 0-10v Dim, 70 CRI, CCT selectable, Type II, Bronze
Warranty	5 years

Electrical data

Nominal Wattage	40.00/50.00/60.00 W
Nominal voltage	120.00...347.00 V
Power factor	≥0.90
Total Harmonic Distortion	< 20 %

Photometrical data

Lumens	4200/5250/6300 lm
Efficacy	105 lm/W
Color Temperature/CCT	3000/4000/5000 K
Color Rendering Index (CRI)	70
Luminaire Type	Post top

Dimensions & Weight

Length	19.9 in
Width	19.7 in
Height	25.3 in
Product weight	24.25 lb

Materials & Colors

Luminaire Finish	Bronze
Housing color	Bronze
Housing	Aluminum
Mercury content	0.0 mg

Application & Mounting

Ambient temperature range	-40...+40 °C
Maximum Operating Temperature	104 °F
Minimum Operating Temperature	-40 °F
Dimming	Yes

Type of Dimming	0-10V
Mounting	Surface
Indoor/Outdoor	Outdoor
Replaceable light source	No
Primary Lamp Type	SMD

Lifespan

Average Rated Life (hr)	130000
-------------------------	--------

Logistical data

Case Qty	1
Case Length (in)	29.764
Case Width (in)	22.677
Case Depth (in)	11.260
Case Cube (ft)	4.398
Case Weight (lbs)	28.913
Pallet Qty	8

Certificates & Standards

Certification Listing	RoHS / FCC / cULus
Replaceable light source (EPREL)	Not replaceable

Optional accessories

Product image	Product name	UPC
	BRACKET 1A POST ADAPTER TEN BZ	OS61171
	BRACKET 1A POST ADAPTER TEN BL	OS61172
	BRACKET 1A POST ADAPTER TEN GR	OS61173
	BRACKET POST TEN ADAPTER WH	OS62419

Product image	Product name	UPC
	POLE SQ S 2B MOUNT 4IN BZ	OS63315
	POLE SQ S 2B MOUNT 5IN BZ	OS63316

DOWNLOAD DATA

Spec Sheets and Product Documents		Document name
	Installation Guide	Performance Class Post Top Install Guide
	Product Family Spec Sheet	DUAL SELECTABLE POST TOP LUMINAIRE LEDLUM141

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.