

PRODUCT DATASHEET

QHE 2X59 T8 UNV IS N SC

SYLVANIA QUICKTRONIC® T8 Ballasts | QHE T8 ballasts with parallel circuitry, LSC, NEMA Premium design for stable operation



Product features

- High Efficiency Systems over 90 % efficient
- Universal voltage (120-277V)
- Low-profile (1.00" High)
- QUICKSENSE® ballast technology (end-of-lamp-life sensing)
- PROStart programmed rapid start
- Min. Starting Temp: -20°F (-29°C)
- High power factor and efficiency
- Low harmonic distortion
- Lightweight
- UL, CSA, FCC
- RoHS compliant
- Lead-free solder and manufacturing process

TECHNICAL DATA

Additional product data

Ordering Abbreviation	QHE 2X59T8/UNV ISN-SC
Abbrev. With Packaging Info.	QHE2X59T8UNVISNSC 10/CS 1/SKU
SKU UPC	0046135498596
NAED	49859
General Description	2-lamp 59wT8 (8') High Efficiency Instant Start electronic ballast, universal voltage, normal ballast factor, 10-pk.

Electrical data

Nominal Wattage	109.00 W
Nominal voltage	120.00...277.00 V
Type of current	AC
Supply Frequency	50...60 Hz

Dimensions & Weight

Length	9.47 in
Width	1.68 in
Height	1.18 in
Product weight	1.29 lb

Application & Mounting

Dimming	No
Number of Lamps	2

Capabilities

Dimming	No
---------	----

Certificates & Standards

Certification Listing	RoHS
-----------------------	------

Logistical data

SKU Qty	1
Case Qty	10
Case Length (in)	11.969
Case Width (in)	10.472
Case Depth (in)	3.189
Case Cube (ft)	0.231
Case Weight (lbs)	13.366
SKU UPC	0046135498596

Pallet Qty	960
------------	-----

DOWNLOAD DATA

Spec Sheets and Product Documents		Document name
	Product Family Spec Sheet	QUICKTRONIC® T8 59W Instant Start UNV Systems

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.