

PRODUCT DATASHEET

QHE QHE/120-277V

SYLVANIA QUICKTRONIC® T8 Ballasts | QHE T8 ballasts with parallel circuitry, LSC, NEMA Premium design for stable operation



Product features

- High Efficiency Systems over 90 % efficient
- Universal voltage (120-277V)
- Low-profile (1.00" High)
- QUICKSENSE® ballast technology (end-of-lamp-life sensing)
- PROStart programmed rapid start
- Min. Starting Temp: -20°F (-29°C)
- High power factor and efficiency
- Low harmonic distortion
- Lightweight
- UL, CSA, FCC
- RoHS compliant
- Lead-free solder and manufacturing process

TECHNICAL DATA

Additional product data

Ordering Abbreviation	QHE 3X32T8/UNV ISH-HT-SC-B
Abbrev. With Packaging Info.	QHE3X32T8UNVISHHTSCB 10/CS 1/SKU
SKU UPC	0046135495007
NAED	49500
General Description	90C Case temp

Electrical data

Nominal Wattage	114.00 W
Nominal voltage	120.00...277.00 V
Type of current	AC
Supply Frequency	50...60 Hz

Dimensions & Weight

Length	9.47 in
Width	1.68 in
Height	1.18 in
Product weight	1.34 lb

Application & Mounting

Dimming	No
Number of Lamps	3

Temperatures & operating conditions

Max.housing temperature in case of fault	110 °C
Permitted rel. humidity during operation	5...85 % ¹⁾

¹⁾ Maximum 56 days/year at 85 %

Capabilities

Dimming	No
---------	----

Certificates & Standards

Certification Listing	RoHS
Protection class	1
Type of protection	IP20

Logistical data

Temperature range at storage	-40...+85 °C
------------------------------	--------------

SKU Qty	1
Case Qty	10
Case Length (in)	10.787
Case Width (in)	10.157
Case Depth (in)	3.268
Case Cube (ft)	0.207
Case Weight (lbs)	14.118
SKU UPC	0046135495007
Pallet Qty	960

DOWNLOAD DATA

Spec Sheets and Product Documents		Document name
	Product Family Spec Sheet	QUICKTRONIC T8 Instant Start

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.