

PRODUCT DATASHEET

DOOR KIT 6A 1x4 (A3)

DOOR KIT DUAL SELECTABLE 6A | Door Kit luminaire with selectable CCT and wattage



Areas of application

- Offices
- Retail
- Hallways
- Multipurpose Rooms
- Hospitality

Product features

- Selectable wattage and lumen outputs
- Selectable CCT: 3500/4000/5000K
- Built-in sensor base allows easy field installation of optional PIR motion sensor
- Up to 125 LPW
- DLC
- DLC Standard
- Ideal in retrofit applications, offering up to 51% energy savings
- Driver includes 12V auxiliary output
- Compatible with field-installable LINK™ components

TECHNICAL DATA

Additional product data

Ordering Abbreviation	RDORKIT6A032UNVD8SC714UWHA3
Abbrev. With Packaging Info.	RDORKIT6A032UNVD8SC714UWHA3 1/CS 1/SKU
NAED	64943
Family Brand Name	UltraLED
General Description	Retrofit Door Kit, series 6A, 32W wattage, 120-277V, 0-10V dimming, 80 CRI, selectable CCT 3500/4000/5000K, 1x4, white, lutron vive sensor
Warranty	5 years

Electrical data

Nominal Wattage	32.00 W
Nominal voltage	120.00...277.00 V
Power factor	≥ 0.90
Total Harmonic Distortion	< 20 %

Photometrical data

Lumens	4000 lm
Efficacy	125 lm/W
Color Temperature/CCT	3500/4000/5000 K
Color Rendering Index (CRI)	> 80
Luminaire Type	Retrofit

Dimensions & Weight

Length	47.76 in
Width	11.87 in
Height	1.57 in
Product weight	7.5 lb

Materials & Colors

Luminaire Finish	White
Housing color	White
Housing	Steel
Mercury content	0.0 mg

Application & Mounting

Ambient temperature range	-20...+40 °C
Maximum Operating Temperature	104 °F
Minimum Operating Temperature	-4 °F

Dimming	Yes
Type of Dimming	0-10V
Mounting	Recessed
Indoor/Outdoor	Indoor
Replaceable light source	No
Primary Lamp Type	SMD

Lifespan

Average Rated Life (hr)	50000
-------------------------	-------

Logistical data

Case Qty	1
Case Length (in)	48.622
Case Width (in)	11.221
Case Depth (in)	3.386
Case Cube (ft)	1.069
Case Weight (lbs)	9.866
Pallet Qty	42

Certificates & Standards

Certification Listing	RoHS / FCC / cULus
-----------------------	--------------------

Optional accessories

Product image	Product name	UPC
	Standalone Commissioning Remote REMOTE CONTROL	OS65305
	LINK POWER PACK 6A UNV BLE	OS62632
	Standalone PIR Motion sensor Snap-in 12ft 12V	OS62711
	LINK POWER PACK 6A UNV BLE	OS62631

Product image	Product name	UPC
	LINK SENSOR CEILING PIR 12V BLE	OS62633
	LINK WIRELESS CONTROLLER 5 KEY BATTERY BLE	OS62636

DOWNLOAD DATA

Spec Sheets and Product Documents		Document name
	User instruction / safety instructions	DUAL SELECTABLE RETROFIT DOOR KIT 6A
	Product Family Spec Sheet	DUAL SELECTABLE RETROFIT DOOR KIT 6A

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.