

PRODUCT DATASHEET

DOOR KIT 6A 2x4 EMBB

DOOR KIT DUAL SELECTABLE 6A | Door Kit luminaire with selectable CCT and wattage



Areas of application

- Offices
- Retail
- Hallways
- Multipurpose Rooms
- Hospitality

Product features

- Selectable wattage and lumen outputs
- Selectable CCT: 3500/4000/5000K
- Built-in sensor base allows easy field installation of optional PIR motion sensor
- Up to 125 LPW
- DLC
- DLC Standard
- Ideal in retrofit applications, offering up to 51% energy savings
- Driver includes 12V auxiliary output
- Compatible with field-installable LINK™ components

TECHNICAL DATA

Additional product data

Ordering Abbreviation	RDORKIT6AS044UNHD8SC724UWHE
Abbrev. With Packaging Info.	RDORKIT6AS044UNHD8SC724UWHE 1/CS 1/SKU
NAED	62833
Family Brand Name	UltraLED
General Description	2x4 Retrofit Door Kit, series 6A, Selectable wattages 24/32/39/44W, 120- 347V, 0-10V dimming, 80 CRI, selectable CCT 3500/4000/5000K, 2x4, white, emergency back-up battery - optional field installable PIR or Bluetooth sensors
Warranty	5 years

Electrical data

Nominal Wattage	44.00/39.00/32.00/24.00 W
Nominal voltage	120.00...347.00 V
Power factor	≥ 0.90
Total Harmonic Distortion	< 20 %

Photometrical data

Lumens	5500/4875/4000/3000 lm
Efficacy	125 lm/W
Color Temperature/CCT	3500/4000/5000 K
Color Rendering Index (CRI)	> 80

Dimensions & Weight

Length	47.76 in
Width	23.88 in
Height	1.98 in
Product weight	12.99 lb

Materials & Colors

Luminaire Finish	White
Housing color	White
Housing	Steel
Mercury content	0.0 mg

Application & Mounting

Ambient temperature range	0...40 °C
Maximum Operating Temperature	104 °F
Minimum Operating Temperature	0 °C

Dimming	Yes
Type of Dimming	0-10V
Mounting	Recessed
Indoor/Outdoor	Indoor
Replaceable light source	No

Lifespan

Average Rated Life (hr)	150000
-------------------------	--------

BATTERY

Lithium Ion Battery	Li ion battery
Battery size [GMS]	Others

Logistical data

Case Qty	1
Case Length (in)	48.250
Case Width (in)	22.750
Case Depth (in)	2.500
Case Cube (ft)	1.588
Case Weight (lbs)	15.895
Pallet Qty	16

Certificates & Standards

Certification Listing	FCC / cULus / RoHS
Replaceable light source (EPREL)	Not replaceable

Optional accessories

Product image	Product name	UPC
	Standalone Commissioning Remote REMOTE CONTROL	OS65305
	LINK POWER PACK 6A UNV BLE	OS62632
	Standalone PIR Motion sensor Snap-in 12ft 12V	OS62711

Product image	Product name	UPC
	LINK POWER PACK 6A UNV BLE	OS62631
	LINK SENSOR CEILING PIR 12V BLE	OS62633
	LINK WIRELESS CONTROLLER 5 KEY BATTERY BLE	OS62636

DOWNLOAD DATA

Spec Sheets and Product Documents		Document name
	User instruction / safety instructions	DUAL SELECTABLE RETROFIT DOOR KIT 6A
	Installation Guide	VOLUME TROFFER 6A
	Product Family Spec Sheet	DUAL SELECTABLE RETROFIT DOOR KIT 6A

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.