

# PRODUCT DATASHEET

## DOOR KIT LINK 2x2 UNV

DOOR KIT LINK™ | Door Kit luminaire featuring built-in LEDVANCE LINK bluetooth low energy mesh connectivity



---

### Areas of application

- Offices
- Retail
- Hallways
- Multipurpose Rooms
- Hospitality

---

### Product features

- Selectable CCT: 3000/3500/4000/5000K
- Bluetooth® Low Energy Mesh and a range of up to 100 ft between luminaires
- Easy to deploy - install, commission, and control
- Convenient control via LINK™ app or wireless wall/controller
- Optional LINK PIR sensor enables field-installable occupancy & daylight control
- DLC listing maximizes rebate opportunities
- Up to 125 LPW
- Optional emergency battery backup versions
- CRI > 80
- Wirelessly sync luminaires and set group/individual scenes using the LINK app

## TECHNICAL DATA

### Additional product data

|                              |                                                                                                                                                                  |
|------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Ordering Abbreviation        | RDORKIT7A/S030UNVD8SC8/22/BLE                                                                                                                                    |
| Abbrev. With Packaging Info. | RDORKIT7AS030UNVD8SC822BLE 2/CS 2/SKU                                                                                                                            |
| NAED                         | 62572                                                                                                                                                            |
| Family Brand Name            | ValueLED                                                                                                                                                         |
| General Description          | 2x2 Retrofit Door Kit, Selectable wattage, 15, 20, 25, 30W, 120-277V, CCT Selectable, 3000, 3500, 4000, 5000K, Bluetooth enabled, motion sensors sold separately |
| Warranty                     | 5 years                                                                                                                                                          |

### Electrical data

|                           |                           |
|---------------------------|---------------------------|
| Nominal Wattage           | 15.00/20.00/25.00/30.00 W |
| Nominal voltage           | 120.00...277.00 V         |
| Power factor              | ≥0.90                     |
| Total Harmonic Distortion | < 20 %                    |

### Photometrical data

|                             |                        |
|-----------------------------|------------------------|
| Lumens                      | 1905/2540/3200/3810 lm |
| Efficacy                    | 125 lm/W               |
| Color Temperature/CCT       | 3000/3500/4000/5000 K  |
| Color Rendering Index (CRI) | > 80                   |
| Luminaire Type              | Retrofit               |

### Dimensions & Weight

|                |          |
|----------------|----------|
| Length         | 23.82 in |
| Width          | 23.86 in |
| Height         | 3.09 in  |
| Product weight | 8.66 lb  |

### Materials & Colors

|                  |        |
|------------------|--------|
| Luminaire Finish | White  |
| Housing color    | White  |
| Housing          | Steel  |
| Mercury content  | 0.0 mg |

### Application & Mounting

|                               |              |
|-------------------------------|--------------|
| Ambient temperature range     | -20...+50 °C |
| Maximum Operating Temperature | 122 °F       |
| Minimum Operating Temperature | -4 °F        |

|                          |          |
|--------------------------|----------|
| Dimming                  | Yes      |
| Type of Dimming          | 0-10V    |
| Mounting                 | Recessed |
| Indoor/Outdoor           | Indoor   |
| Replaceable light source | No       |

### Lifespan

|                         |        |
|-------------------------|--------|
| Average Rated Life (hr) | 125000 |
|-------------------------|--------|

### Logistical data

|                   |        |
|-------------------|--------|
| Case Qty          | 2      |
| Case Length (in)  | 26.614 |
| Case Width (in)   | 25.158 |
| Case Depth (in)   | 5.354  |
| Case Cube (ft)    | 2.075  |
| Case Weight (lbs) | 19.484 |
| Pallet Qty        | 32     |

### Certificates & Standards

|                                  |                    |
|----------------------------------|--------------------|
| Certification Listing            | RoHS / FCC / cULus |
| Replaceable light source (EPREL) | Not replaceable    |

### Optional accessories

| Product image                                                                       | Product name                                  | UPC     |
|-------------------------------------------------------------------------------------|-----------------------------------------------|---------|
|  | AREA DUSK-TO-DAWN 55W 120-277V D 3CCT T5 GR P | OS61751 |

### EQUIPMENT / ACCESSORIES

- Mounting brackets

### Safety advice

- Retrofit luminaire is designed to be installed in existing troffers

### DOWNLOAD DATA

| Spec Sheets and Product Documents | Document name |
|-----------------------------------|---------------|
|-----------------------------------|---------------|

| Spec Sheets and Product Documents                                                |                           | Document name                                                    |
|----------------------------------------------------------------------------------|---------------------------|------------------------------------------------------------------|
|  | Installation Guide        | RETROFIT DOOR KIT 7A                                             |
|  | Installation Guide        | INSTALLATION GUIDE LEDVANCE LINK LOW-VOLTAGE PLUG&PLAY ECOSENSOR |
|  | Product Family Spec Sheet | BLUETOOTH MESH ENABLED CONNECTED RETROFIT DOOR KIT LEDLUM165     |
| Photometric and lighting design files                                            |                           | Document name                                                    |
|  | IES file (IES)            | VOLUME DOORKIT 7A IES                                            |

---

## DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.