

PRODUCT DATASHEET

RT VALUE 4" 2700K 600LM SM

DOWNLIGHT RETROFIT VALUE | Downlight Retrofit with static CCT and wattage



Areas of application

- Residential
- Bedrooms
- Kitchens
- Bathrooms

Product features

- Integrated white trim, E26 medium base socket adapter
- Fixed wattage and CCT
- Available in 120VAC
- Up to 88 LPW
- Energy savings up to 88 %
- Flicker-free dimming, phase-cut down to 10 %
- Color trim rings available as optional accessory

TECHNICAL DATA

Additional product data

Ordering Abbreviation	RT41A600ST927SMWHE26
Abbrev. With Packaging Info.	RT41A600ST927SMWHE26 6/CS 1/SKU
SKU UPC	0046135628580
NAED	62858
Family Brand Name	Value Class
General Description	Value Class Downlight for 4" can, 600lm, 120V, > 90 CRI, 2700K, smooth finish, w/E26 adaptor. Wet rated with plastic housing.Title 20/24 Compliant and Energy Star Listed
Warranty	3 years

Electrical data

Nominal Wattage	7.00 W
Nominal voltage	120.00 V
Power factor	≥0.90
Total Harmonic Distortion	< 20 %

Photometrical data

Lumens	600 lm
Efficacy	61 lm/W
Color Temperature/CCT	2700 K
Color Rendering Index (CRI)	90
Luminaire Type	Downlight

Dimensions & Weight

Diameter	5 in
Height	2.24 in
Product weight	0.4 lb

Materials & Colors

Luminaire Finish	White
Housing color	White
Housing	Aluminum Plastic
Mercury content	0.0 mg

Application & Mounting

Connectors	Plug, quick disconnect
Dimming	Yes
Type of Dimming	PHASE CUT

Mounting	Recessed
Replaceable light source	No

Lifespan

Average Rated Life (hr)	25000
-------------------------	-------

Logistical data

SKU Qty	1
Case Qty	6
Case Length (in)	10.866
Case Width (in)	8.504
Case Depth (in)	5.827
Case Cube (ft)	0.312
Case Weight (lbs)	3.310
SKU UPC	0046135628580
Pallet Qty	912

Certificates & Standards

Certification Listing	RoHS / FCC / cULus / CEC
Replaceable light source (EPREL)	Not replaceable

Safety advice

- Suitable for indoor dry, damp and wet locations.
- For use in housings that can structurally support a lamp weighing one pound.
- RT5/6 designed to install in standard 5" and 6" insulated and non-insulated housings.
- Not intended for use with emergency light luminaires or exit lights.

DOWNLOAD DATA

Spec Sheets and Product Documents		Document name
	Installation Guide	Value Class Downlight Installation Guide
	Product Family Spec Sheet	SCREW-BASE DOWNLIGHTS

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.