

PRODUCT DATASHEET

RT SELECT 1A 4" 5CCT 650LM SM

DOWNLIGHT RETROFIT SELECTABLE | Downlightt Retrofit with selectable 5 CCT and dual selectable models



Areas of application

- Residential
- Bedrooms
- Kitchens
- Bathrooms

Product features

- Integrated white trim, E26 medium base socket adapter
- Selectable CCTs: 2700/3000/3500/4000/5000K
- Available in 120VAC
- Up to 100 LPW
- Energy savings up to 89 %
- Flicker-free dimming, phase-cut down to 10 %
- Color trim rings available as optional accessory
- No warm-up time, instant-on with full light output

TECHNICAL DATA

Additional product data

Ordering Abbreviation	RT41A650ST9SC3SMWHE26
Abbrev. With Packaging Info.	RT41A650ST9SC3SMWHE26 6/CS 1/SKU
SKU UPC	0046135628665
NAED	62866
Family Brand Name	PERFORMANCE
General Description	Performance Class Downlight for 4" can, 650lm, 120V, > 90 CRI, 2700K/3000K/3500K/4000K/5000K, smooth finish, w/E26 adaptor. Wet rated with metal housing. Title 20/24 Compliant and Energy Star Listed
Warranty	5 years

Electrical data

Nominal Wattage	7.00 W
Nominal voltage	120.00 V
Power factor	≥0.90
Total Harmonic Distortion	< 20 %

Photometrical data

Lumens	650 lm
Efficacy	80 lm/W
Color Temperature/CCT	2700/3000/4000/5000 K
Color Rendering Index (CRI)	90
Luminaire Type	Downlight

Dimensions & Weight

Diameter	5 in
Height	2.24 in
Product weight	0.4 lb

Materials & Colors

Luminaire Finish	White
Housing color	White
Housing	Polycarbonate (PC)
Mercury content	0.0 mg

Application & Mounting

Dimming	Yes
Type of Dimming	PHASE CUT

Mounting	Recessed
Replaceable light source	No

Lifespan

Average Rated Life (hr)	50000
-------------------------	-------

Logistical data

SKU Qty	1
Case Qty	6
Case Length (in)	10.866
Case Width (in)	8.504
Case Depth (in)	5.827
Case Cube (ft)	0.312
Case Weight (lbs)	3.310
SKU UPC	0046135628665
Pallet Qty	912

Certificates & Standards

Certification Listing	RoHS / FCC / cULus
Replaceable light source (EPREL)	Not replaceable
Energy Star Rated	X

Optional accessories

Product image	Product name	UPC
	RT TRIM RING RT4 SM BLACK	OS62498
	RT TRIM RING RT4 SM COPPER	OS62499
	RT TRIM RING RT4 SM SATIN NICKEL	OS62500
	RT TRIM RING RT56 SM BLK	OS62501
	RT TRIM RING RT56 SM COPPER	OS62502
	RT TRIM RING RT56 SM SATIN NICKEL	OS62503
	RT TRIM RING RT4 BA BLK	OS63430

Product image	Product name	UPC
	RT TRIM RING RT4 BA COPPER	OS63431
	RT TRIM RING RT4 BA SATIN NICKEL	OS63432
	RT TRIM RING RT56 BA BLK	OS63433
	RT TRIM RING RT56 BA COPPER	OS63434
	RT TRIM RING RT56 BA SATIN NICKEL	OS63435

Safety advice

- Suitable for indoor dry, damp and wet locations.
- For use in housings that can structurally support a lamp weighing one pound.
- RT5/6 designed to install in standard 5" and 6" insulated and non-insulated housings.
- Not intended for use with emergency light luminaires or exit lights.

DOWNLOAD DATA

Spec Sheets and Product Documents	Document name
 PDF	Installation Guide
	Install Guide- Downlights
 PDF	Product Family Spec Sheet
	DUAL SELECTABLE SCREW-BASE DOWNLIGHT

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.